

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.03.96
Test oil : ISO 4113
Combination No. : 0 402 646 762
Injection pump
Pump designation : PE6P120A320LS7834
 : -10
EP type number : 0 412 626 853
Governor
Governor design. : RQV300...1050PA1033
 : -18
Governor no. : 0 421 814 136
Cust. part No. : 0260743602

Customer-spec. information
Customer : MB-NFZ
Motor : OM401 LA
Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Tolerance l/h : ± 10.0
Test nozzle holde
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

A01

Test lines : 1 660 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 20.50
Tolerance mm : ± 0.50
Firing order : 6- 3- 5- 2- 4-
 : 1-
Phasing : 0-60-120-180-240
 : -300-360
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery mark
Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75
Barrel no. : 6

BASIC SETTING

Rated speed rpm : 550
Rack travel in mm : 14.80
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 230.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 6.30
Tolerance mm : +- 0.30

Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.29
Tolerance mm : +- 0.20

Rated speed rpm : 1108
guide sleeve
travel mm : 8.53
Tolerance mm : +- 0.15

Rated speed rpm : 558
guide sleeve
travel mm : 4.53
Tolerance mm : +- 0.25

Rated speed rpm : 608
guide sleeve
travel mm : 5.03
Tolerance mm : +- 0.25

Rated speed rpm : 820

guide sleeve
travel mm : 6.13
Tolerance mm : +- 0.25

Rated speed rpm : 1183
guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.25

Rated speed rpm : 1280
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1145

Rack travel in mm : 13.80
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 550
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 230.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 121.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.80
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1195
Tolerance 1/min : +- 15

rack travel mm : 0.75
Tolerance mm : +- 0.75

Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 66.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.20
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : > 7.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 550
rack travel mm : 14.80
Tolerance mm : +- 0.05

Rated speed rpm : 1050
rack travel mm : 14.80
Tolerance mm : +- 0.10

Rated speed rpm : 700
rack travel mm : 14.80
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1000
rack travel mm : 14.80
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 10.50
Tolerance mm : +- 0.15

Rated speed rpm : 400

Pressure hPa : 400

A03

rack travel mm : 12.90
Tolerance mm : +- 0.20

Pressure hPa : 600
rack travel mm : 14.15
Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 229.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 13.80
Rated speed rpm : 1095
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 210.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 300
rack travel mm : 6.30
Tolerance mm : ± 0.30
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.03.96
Test oil : ISO 4113

Combination No. : 0 402 646 763

Injection pump
Pump designation : PE6P120A320LS7834
: -10

EP type number : 0 412 626 853

Governor
Governor design. : RQV300...1050PA1065
: -2

Governor no. : 0 421 814 135

Cust. part No. : 0260743702

Customer-spec. information

Customer : MB-NFZ
Motor : OM401 LA
Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

A05

Test Lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 6- 3- 5- 2- 4-
: 1

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery mark

Barrel no. : 6

BASIC SETTING

Rated speed rpm : 550

Rack travel in mm : 14.80
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 230.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 6.30
Tolerance mm : +- 0.30

Del. quantity
cm³/1000 strokes : 13.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.13
Tolerance mm : +- 0.25

Rated speed rpm : 1108
guide sleeve
travel mm : 9.82
Tolerance mm : +- 0.25

Rated speed rpm : 370
guide sleeve
travel mm : 2.00
Tolerance mm : +- 0.25

Rated speed rpm : 420
guide sleeve
travel mm : 2.49
Tolerance mm : +- 0.25

Rated speed rpm : 750
guide sleeve
travel mm : 4.87
Tolerance mm : +- 0.25

Rated speed rpm : 1310
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1200

Rack travel in mm : 13.80
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 550
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 230.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 104.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.80
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1195
Tolerance 1/min : +- 15

rack travel mm : 0.75
Tolerance mm : +- 0.75
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 68.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.20
Tolerance mm : ± 0.10

Rated speed rpm : 200

CRT mm min. : > 8.10

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 550
rack travel mm : 14.80
Tolerance mm : ± 0.05

Rated speed rpm : 1050
rack travel mm : 14.80
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 14.80
Tolerance mm : ± 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1000
rack travel mm : 14.80
Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 10.50
Tolerance mm : ± 0.15

Rated speed rpm : 400

Pressure hPa : 400
rack travel mm : 12.90
Tolerance mm : ± 0.20

Pressure hPa : 600
rack travel mm : 14.15
Tolerance mm : ± 0.20

A07

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 229.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 13.80
Rated speed rpm : 1095
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 210.0

Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
rack travel mm : 6.30
Tolerance mm : +- 0.30
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.04.96
Test oil : ISO 4113
Combination No. : 0 402 648 602
Injection pump
Pump designation : PE8P110A32ORS7398
EP type number : 0 412 618 800
Governor
Governor design. : RQV300...900PA1252K
Governor no. : 0 421 815 484

Cust. part No. :

Customer-spec. information
Customer : TATRA
Motor : T3B-928.60
Power KW : 255.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

A09

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 13.00
Tolerance mm : ± 1.00

Firing order : 1- 8- 5- 4- 7
 : - 2- 3- 6

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 14.00
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 191.0

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance cm³/1000s. : ± 4.0

Spreed
 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0

 Rated speed rpm : 250
 Tolerance mm : +- 0.30
 Del. quantity
 cm³/1000 strokes : 26.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.63
 Tolerance mm : +- 0.20

 Rated speed rpm : 958
 guide sleeve
 travel mm : 8.79
 Tolerance mm : +- 0.15

 Rated speed rpm : 777
 guide sleeve
 travel mm : 6.70
 Tolerance mm : +- 0.25

 Rated speed rpm : 520
 guide sleeve
 travel mm : 3.73
 Tolerance mm : +- 0.25

 Rated speed rpm : 1260
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1115
 Rack travel in mm : 13.00

A10

Tolerance mm : +- 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
 Aneroid pressure
 hPa : 1500
 Del. quantity
 cm³/1000 strokes : 191.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 65.0
 tolerance degree : +- 4.0

control lever
 position degree : 119.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.00
 Rated speed rpm : 945
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1065
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1150

LOW IDLE

control lever
 position degree : 70.0
 tolerance degree : +- 4.0

control lever
 position degree : 16.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
Tolerance mm : +- 0.10

Rated speed rpm : 150

CRT mm min. : > 6.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 14.00
Tolerance mm : +- 0.05

Rated speed rpm : 600
rack travel mm : 13.10
Tolerance mm : +- 0.10

Rated speed rpm : 300
rack travel mm : 12.60
Tolerance mm : +- 0.20

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1500
rack travel mm : 14.00
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 9.05
Tolerance mm : +- 0.20

Rated speed rpm : 900

Pressure hPa : 375
rack travel mm : 10.15
Tolerance mm : +- 0.15

Pressure hPa : 750
rack travel mm : 12.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 170

Check
speed 1/min : > 80
Check
speed 1/min : < 190

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 198.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 13.00
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 255.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Tolerance mm : +- 0.30
Del. quantity
cm³/1000 strokes : 26.0

Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.04.96
Test oil : ISO 4113
Combination No. : 0 402 648 602A
Injection pump
Pump designation : PE8P110A320RS7398
EP type number : 0 412 618 800
Governor
Governor design. : RQV300...900PA1252K
Governor no. : 0 421 815 484

Cust. part No. :

Customer-spec. information
Customer : TATRA
Motor : T3B-928.50
Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 5.05
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 13.00
Tolerance mm : +- 1.00
Firing order : 1- 8- 5- 4- 7
 : - 2- 3- 6

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900
Rack travel in mm : 13.30
Tolerance mm : +- 0.05
Del. quantity cm³/1000 strokes : 175.0

Tolerance
 cm³/1000 strokes : +- 1.0

Check tolerance
 cm³/1000S. : +- 4.0

Spreed
 Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 250
 Tolerance mm : +- 0.30
 Del. quantity
 cm³/1000 strokes : 26.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.63
 Tolerance mm : +- 0.20

Rated speed rpm : 957
 guide sleeve
 travel mm : 8.79
 Tolerance mm : +- 0.15

Rated speed rpm : 776
 guide sleeve
 travel mm : 6.70
 Tolerance mm : +- 0.25

Rated speed rpm : 520
 guide sleeve
 travel mm : 3.73
 Tolerance mm : +- 0.25

Rated speed rpm : 1260
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1120
 Rack travel in mm : 12.30
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 175.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 61.0
 tolerance degree : +- 4.0

control lever
 position degree : 115.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.30
 Rated speed rpm : 945
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1095
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1100

LOW IDLE

control lever
 position degree : 72.0

tolerance degree : +- 4.0

control lever
position degree : 18.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
Tolerance mm : +- 0.10

Rated speed rpm : 150

CRT mm min. : > 6.40

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 13.30
Tolerance mm : +- 0.05

Rated speed rpm : 600
rack travel mm : 12.30
Tolerance mm : +- 0.10

Rated speed rpm : 300
rack travel mm : 11.50
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1500
rack travel mm : 13.30
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 8.90
Tolerance mm : +- 0.20

Rated speed rpm : 900

Pressure hPa : 425
rack travel mm : 10.00
Tolerance mm : +- 0.15

Pressure hPa : 750
rack travel mm : 12.25
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 170

Check
speed 1/min : > 80
Check
speed 1/min : < 190

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 182.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 12.30
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 255.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Tolerance mm : +- 0.30
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.03.96
Test oil : ISO 4113

Combination No. : 0 402 676 829

Injection pump
Pump designation : PE6P120A720RS7188
: -10
EP type number : 0 412 626 924

Governor
Governor design. : RSV350...1050P1A543
: -4
Governor no. : 0 421 833 546

Cust. part No. : 1388814

Customer-spec. information
Customer : SCANIA
Motor : DS1159A

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Vibration
damper
(RoBo diaphragm) : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 104

Opening pressure
bar : 251.5
Tolerance bar : ± 1.5

A17

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.45
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 13.15
 Tolerance mm : +- 0.05

Del. quantity
 cm3/1000 strokes : 231.0

Tolerance
 cm3/1000 strokes : +- 1.0

Check tolerance
 cm3/1000S. : +- 4.0

Spreed
 Tolerance
 cm3/1000 strokes : 8.0

Check tolerance
 cm3/1000S. : 12.0

Rated speed rpm : 350

Rack travel in mm : 4.70
 Tolerance mm : +- 0.30
 Del. quantity
 cm3/1000 strokes : 19.0
 Tolerance
 cm3/1000 strokes : +- 3.0
 Check tolerance
 cm3/1000S. : +- 6.0
 Spreed
 Tolerance
 cm3/1000 strokes : 4.0
 Check tolerance
 cm3/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : +- 0.20

governor spring
 pre-tension
 click setting x : 6.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
 Aneroid pressure
 hPa : -

Del. quantity
 cm3/1000 strokes : 231.0
 Tolerance
 cm3/1000 strokes : +- 1.0
 Check tolerance
 cm3/1000S. : +- 4.0
 Spreed
 Tolerance
 cm3/1000 strokes : 8.0
 Check tolerance
 cm3/1000S. : 12.0

CONTROL LEVER

control lever
 position degree : 63.0
 tolerance degree : +- 4.0

control lever
 position degree : 113.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.35
 Rated speed rpm : 1095
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1170
 Tolerance 1/min : +- 15

rack travel mm : 0.85
 Tolerance mm : +- 0.55
 Rated speed rpm : 1300

LOW IDLE

control lever
 position degree : 81.0
 tolerance degree : +- 4.0

control lever
 position degree : 31.0
 tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
 rack travel mm : 4.20

Testing:

Rated speed rpm : 350
 rack travel mm : 4.70

Tolerance mm : +- 0.10
rack travel mm : 2.00
Rated speed rpm : 470
Tolerance 1/min : +- 30

Rated speed rpm : 100
CRT mm min. : > 19.50

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.15
Tolerance mm : +- 0.05

Rated speed rpm : 1050
rack travel mm : 12.35
Tolerance mm : +- 0.05

Rated speed rpm : 860
rack travel mm : 12.80
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 13.15
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.40
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 270
rack travel mm : 11.00
Tolerance mm : +- 0.15

Pressure hPa : 440
rack travel mm : 12.05
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 1050
Del. quantity
cm3/1000 strokes : 212.0
Tolerance
cm3/1000 strokes : +- 4.0
Check tolerance
cm3/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 153.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.35
Rated speed rpm : 1095
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 10.40
Tolerance mm : +- 0.20
Del. quantity
cm3/1000 strokes : 170.0
Tolerance
cm3/1000 strokes : +- 20.0

LOW IDLE

Rated speed rpm : 350
rack travel mm : 4.70
Tolerance mm : +- 0.30
Del. quantity
cm3/1000 strokes : 19.0
Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 6.0
Spreed
Tolerance
cm3/1000 strokes : 4.0
Check tolerance
cm3/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 26.04.96
Test oil : ISO 4113
Combination No. : 0 402 846 302
Injection pump
Pump designation : PE6P120A320RS8520
EP type number : 0 412 826 202
Governor
Governor design. : RQV275...1000PA1269K
Governor no. : 0 421 815 969
Cust. part No. : 1310222/1

Customer-spec. information
Customer : DAF
Motor : XF 355 M
Power KW : 355.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 086
Inlet press. bar : 2.5
Tolerance bar : +- 0.1
Overflow quantity min. l/h : 110
Tolerance l/h : +- 20.0
Test nozzle holder assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 4.85
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 980
Rack travel in mm : 14.15
Tolerance mm : +- 0.05
Del. quantity cm³/1000 strokes : 344.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 275

Rack travel in mm : 6.60
Tolerance mm : +- 0.20

Del. quantity
cm³/1000 strokes : 18.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 13.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 2.04
Tolerance mm : +- 0.20

Rated speed rpm : 1062
guide sleeve
travel mm : 10.05
Tolerance mm : +- 0.15

Rated speed rpm : 697
guide sleeve
travel mm : 6.49
Tolerance mm : +- 0.25

Rated speed rpm : 400
guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.25

Rated speed rpm : 1310
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1150

Rack travel in mm : 13.10
Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 980
Aneroid pressure
hPa : 1500

Del. quantity
cm³/1000 strokes : 344.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 118.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.15
Rated speed rpm : 1050
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1160
Tolerance 1/min : +- 15

rack travel mm : 0.70
Tolerance mm : +- 0.70
Rated speed rpm : 1275

LOW IDLE

control lever
position degree : 73.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : 4.90
Tolerance mm : ± 0.10

Rated speed rpm : 175

CRT mm min. : > 8.20

Rated speed rpm : 300

TORQUE CONTROL

Rated speed rpm : 980
rack travel mm : 14.15
Tolerance mm : ± 0.05

Rated speed rpm : 800
rack travel mm : 13.95
Tolerance mm : ± 0.10

Rated speed rpm : 750
rack travel mm : 13.70
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : 13.20
Tolerance mm : ± 0.10

Rated speed rpm : 600
rack travel mm : 12.75
Tolerance mm : ± 0.10

Rated speed rpm : 500
rack travel mm : 12.50
Tolerance mm : ± 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 980
Pressure hPa : 1500
rack travel mm : 14.15
Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 980
rack travel mm : 9.15
Tolerance mm : ± 0.15

Rated speed rpm : 980

Pressure hPa : 750
rack travel mm : 12.90

Tolerance mm : ± 0.05

Pressure hPa : 380
rack travel mm : 10.30
Tolerance mm : ± 0.10

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 353.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 200.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 5.0

BREAKAWAY

Rack travel in mm : 13.15
Rated speed rpm : 1050
Tolerance 1/min : ± 5

LOW IDLE

Rated speed rpm : 275
rack travel mm : 6.60
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 13.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 30.04.96
Test oil : ISO 4113
Combination No. : 0 402 946 011
Injection pump
Pump designation : PES6P120A320RS8028
EP type number : 0 412 926 021
Governor
Governor design. : RQV275...1250PA1125K
Governor no. : 0 421 815 981
Cust. part No. : CCEP 5140A 66-205

Customer-spec. information
Customer : RENAULT V.I.
Motor : MIDR 06.02.26L51
Power KW : 132.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 078
Inlet press. bar : 2.5
Test nozzle holder assembly : 1 688 901 101
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 5.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 11.00
Tolerance mm : ± 0.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50
Start of delivery mark
°NW after s.o.d. : -0.25
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1
Beginning of delivery difference
betw. rack trav. mm : 21.00
and maximum rack travel : 10.00
Difference °CS : 2.25

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 12.60
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 170.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 325

Rack travel in mm : -6.60
Tolerance mm : +- 0.20

Del. quantity
cm³/1000 strokes : 41.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.00
Tolerance mm : +- 0.15

Rated speed rpm : 1355
guide sleeve
travel mm : 10.10
Tolerance mm : +- 0.10

Rated speed rpm : 929
guide sleeve
travel mm : 6.80
Tolerance mm : +- 0.20

Rated speed rpm : 390
guide sleeve
travel mm : 2.39
Tolerance mm : +- 0.20

Rated speed rpm : 440
guide sleeve
travel mm : 3.01
Tolerance mm : +- 0.20

Rated speed rpm : 550
guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.20

Rated speed rpm : 1650
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1430

Rack travel in mm : 10.90
Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : 1600

Del. quantity
cm³/1000 strokes : 170.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 296.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1330
Tolerance 1/min : +- 15

rack travel mm : -8.60
Rated speed rpm : 1470
Tolerance 1/min : + 5

rack travel mm : -12.10
Tolerance mm : + 0.55
Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 244.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 325
rack travel mm : -6.60
Tolerance mm : + 0.10

Rated speed rpm : 200

CRT mm max. : < -5.20

Rated speed rpm : 360

TORQUE CONTROL

Rated speed rpm : 1250

Rated speed rpm : 650
rack travel mm : -1.10
Tolerance mm : + 0.10

Rated speed rpm : 350
rack travel mm : -1.70
Tolerance mm : + 0.25

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1600
Tolerance mm : + 0.10

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -4.30
Tolerance mm : + 0.20

Rated speed rpm : 1250

Pressure hPa : 200
rack travel mm : -3.70
Tolerance mm : + 0.20

Pressure hPa : 360
rack travel mm : -2.60
Tolerance mm : + 0.05

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 240

Check
speed 1/min : > 155
Check
speed 1/min : < 260

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1600
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 182.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 116.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1330
Tolerance 1/min : + 15

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : + 10.0

Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 325
rack travel mm : -6.60
Tolerance mm : +- 0.20
Del. quantity
cm³/1000 strokes : 41.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.04.96
Test oil : ISO 4113
Combination No. : 0 403 244 052
Injection pump
Pump designation : PES4MW100/720RS1524
EP type number : 0 413 204 021
Governor
Governor design. : RQV300...1200MW132
: -15
Governor no. : 0 420 083 332
Cust. part No. : 0260747602

Customer-spec. information
Customer : MB-NFZ
Motor : OM364LA
Power KW : 77.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test Lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0
Prestroke mm : 4.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 20.00
Tolerance mm : +- 1.00
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1200
Rack travel in mm : 11.00
Tolerance mm : +- 0.05
Del. quantity
cm³/1000 strokes : 89.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 4.5

Check tolerance
 cm³/1000S. : 7.0
 Rated speed rpm : 300
 Rack travel in mm : 4.40
 Tolerance mm : +- 0.20
 Del. quantity
 cm³/1000 strokes : 12.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 2.0
 Check tolerance
 cm³/1000S. : 4.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 0.91
 Tolerance mm : +- 0.20

Rated speed rpm : 1354
 guide sleeve
 travel mm : 9.00
 Tolerance mm : +- 0.15

Rated speed rpm : 1020
 guide sleeve
 travel mm : 5.87
 Tolerance mm : +- 0.25

Rated speed rpm : 1690
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1450
 Rack travel in mm : 10.00
 Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
 Aneroid pressure
 hPa : 700

Del. quantity
 cm³/1000 strokes : 89.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.0

CONTROL LEVER

control lever
 position degree : 115.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.00
 Rated speed rpm : 1245
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1355
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1450

LOW IDLE

control lever
 position degree : 75.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 4.40
 Tolerance mm : +- 0.10

Rated speed rpm : 200
 CRT mm min. : > 5.00

TORQUE CONTROL

Rated speed rpm : 1200
 rack travel mm : 11.00
 Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 11.00
Tolerance mm : \pm 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700
rack travel mm : 11.00
Tolerance mm : \pm 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : \pm 0.10

Rated speed rpm : 500

Pressure hPa : 230
rack travel mm : 0.90
Tolerance mm : \pm 0.10

Pressure hPa : 150
rack travel mm : 0.30
Tolerance mm : \pm 0.10

START CUT-OUT

Rated speed rpm : $>$ 100
Rated speed rpm : $<$ 200

Check speed 1/min : $>$ 80
Check speed 1/min : $<$ 220

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 700
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 83.0
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 56.0
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 3.0

BREAKAWAY

Rack travel in mm : 10.00
Rated speed rpm : 1245
Tolerance 1/min : \pm 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : \pm 5.0
Check tolerance
cm³/1000S. : \pm 8.0

LOW IDLE

Rated speed rpm : 300
rack travel mm : 4.40
Tolerance mm : \pm 0.20
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 4.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 30.04.96
Test oil : ISO 4113
Combination No. : 0 403 466 178
Injection pump
Pump designation : PES6MW100/720/3RS120
: 5-1
EP type number : 0 413 406 245
Governor
Governor design. : RSV675...1250MWOA401
Governor no. : 0 420 085 290
Cust. part No. : 0270749302

Customer-spec. information
Customer : MB-NFZ
Motor : OM 366 LA
Power kW : 185.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0
Prestroke mm : 3.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1230
Rack travel in mm : 15.25
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0
Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 675

Rack travel in mm : 6.00

Tolerance mm : +- 0.50

Del. quantity
cm³/1000 strokes : 12.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spread
Tolerance

cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65

Tolerance mm : +- 0.35

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1230

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 122.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spread
Tolerance

cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 92.0

RATED SPEED

rack travel mm : 1.00

Tolerance mm : +- 0.70

Rated speed rpm : 1400

rack travel mm : 4.00

Rated speed rpm : 1310

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 1270

rack travel mm : 14.25

Rated speed rpm : 1299

Tolerance 1/min : +- 4

rack travel mm : 4.00

Rated speed rpm : 1271

rack travel mm : 14.25

Rated speed rpm : 1300

Tolerance 1/min : +- 4

rack travel mm : 4.00

Rated speed rpm : 1272

rack travel mm : 14.25

Rated speed rpm : 1301

Tolerance 1/min : +- 4

rack travel mm : 4.00

Rated speed rpm : 1273

rack travel mm : 14.25

Rated speed rpm : 1302

Tolerance 1/min : +- 4

rack travel mm : 4.00

Rated speed rpm : 1278

rack travel mm : 14.25

Rated speed rpm : 1307

Tolerance 1/min : +- 4

rack travel mm : 4.00

Rated speed rpm : 1279

rack travel mm : 14.25

Rated speed rpm : 1308

Tolerance 1/min : +- 4

rack travel mm : 4.00

LOW IDLE

control lever
position degree : 73.0

Testing:

Rated speed rpm : 675
rack travel mm : 6.00
Tolerance mm : +- 0.30

rack travel mm : 2.00
Rated speed rpm : 700
Tolerance 1/min : +- 30

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1230
rack travel mm : 15.25
Tolerance mm : +- 0.05

Rated speed rpm : 800
rack travel mm : 15.25
Tolerance mm : +- 0.10

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 800
Del. quantity
cm3/1000 strokes : 122.0
Tolerance
cm3/1000 strokes : +- 1.5
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 7.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm3/1000 strokes : 115.0
Tolerance
cm3/1000 strokes : +- 5.0

Check tolerance
cm3/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 675
rack travel mm : 6.00
Tolerance mm : +- 0.50
Del. quantity
cm3/1000 strokes : 12.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Spreed
Tolerance
cm3/1000 strokes : 3.5
Check tolerance
cm3/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.04.96
Test oil : ISO 4113
Combination No. : 0 403 476 147
Injection pump
Pump designation : PES6MW100/720RS1131
: -1
EP type number : 0 413 406 165
Governor
Governor design. : RSV750...1200MWOA329
: -17
Governor no. : 0 420 085 291
Cust. part No. : 0270747902

Customer-spec. information
Customer : MB-NFZ
Motor : OM366LA
Power KW : 163.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0
Prestroke mm : 3.65
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1180
Rack travel in mm : 13.15
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 104.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 3.0
Speed

Tolerance
 cm³/1000 strokes : 3.5

Check tolerance
 cm³/1000S. : 6.0

Rated speed rpm : 750

Rack travel in mm : 4.70
 Tolerance mm : +- 0.40

Del. quantity
 cm³/1000 strokes : 12.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 4.5

Spreed
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
 Tolerance mm : +- 0.35

governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1180
 Aneroid pressure
 hPa : 1000

Del. quantity
 cm³/1000 strokes : 104.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.0

Spreed
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 6.0

CONTROL LEVER

control lever
 position degree : 98.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 1.00
 Tolerance mm : +- 0.70
 Rated speed rpm : 1400

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 1230
 rack travel mm : 12.10

Rated speed rpm : 1314
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

Rated speed rpm : 1231
 rack travel mm : 12.10

Rated speed rpm : 1315
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

Rated speed rpm : 1232
 rack travel mm : 12.10

Rated speed rpm : 1316
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

Rated speed rpm : 1233
 rack travel mm : 12.10

Rated speed rpm : 1317
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

Rated speed rpm : 1238
 rack travel mm : 12.10

Rated speed rpm : 1322
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

Rated speed rpm : 1239
 rack travel mm : 12.10

Rated speed rpm : 1323
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

LOW IDLE

control lever
position degree : 81.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 750
rack travel mm : 4.70
Tolerance mm : +- 0.25

rack travel mm : 2.00
Rated speed rpm : 775
Tolerance 1/min : +- 25

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1180
rack travel mm : 13.15
Tolerance mm : +- 0.05

Rated speed rpm : 600
rack travel mm : 13.15
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000
rack travel mm : 13.15
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 500
rack travel mm : 2.20
Tolerance mm : +- 0.15

Pressure hPa : 350
rack travel mm : 1.10
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 97.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 43.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 750
rack travel mm : 4.70
Tolerance mm : +- 0.40
Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 01.05.96
Test oil : ISO 4113

Combination No. : 0 402 076 789

Injection pump
Pump designation : PES6P120A720RS3352
EP type number : 0 412 026 780

Governor
Governor design. : RSV450...1050P2A599
: -4
Governor no. : 0 421 833 524

Cust. part No. : RE66245

Customer-spec. information
Customer : DEERE
Motor : 6081AT001
Power KW : 142.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 457 413 010

Inlet press. bar : 2.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 3.60
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.75

Start of delivery mark

°NW after s.o.d. : 6.25
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery difference
and maximum rack
travel : 14.00
Difference °CS : 2.50

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 11.20
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 130.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Del. quantity
cm³/1000 strokes : 22.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.30

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 130.5

Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 92.0
tolerance degree : +- 6.0

RATED SPEED

rack travel mm : 10.20
Rated speed rpm : 1100
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1250

rack travel mm : 4.00
Rated speed rpm : 1150

LOW IDLE

control lever
position degree : 72.0
tolerance degree : +- 6.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 5.00

Testing:

Rated speed rpm : 450
rack travel mm : 5.50
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 11.20
Tolerance mm : +- 0.05

Rated speed rpm : 650
rack travel mm : 12.20
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.90
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 835
rack travel mm : 12.00
Tolerance mm : +- 0.20

Pressure hPa : 620
rack travel mm : 11.25
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100

Check
speed 1/min : > 80

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 650
Del. quantity
cm3/1000 strokes : 159.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 129.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 10.20
Rated speed rpm : 1100
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm3/1000 strokes : 105.0
Tolerance
cm3/1000 strokes : +- 20.0
Check tolerance
cm3/1000S. : +- 25.0

LOW IDLE

Del. quantity
cm3/1000 strokes : 22.5
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Speed
Tolerance
cm3/1000 strokes : 6.0
Check tolerance
cm3/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 28.03.96
Test oil : ISO 4113

Combination No. : 0 402 746 612

Injection pump
Pump designation : PES6P120A32ORS7372
EP type number : 0 412 726 940

Governor
Governor design. : RQV250...1300PA1282K
Governor no. : 0 421 815 515

Cust. part No. : 3866784

Customer-spec. information

Customer : CDC
Motor : 6BTA
Power KW : 187.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 086

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 4.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

°NW after s.o.d. : 11.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1300

Rack travel in mm : 12.65
Tolerance mm : ± 0.05

Del. quantity cm3/1000 strokes	:	177.0
<hr/>		
Tolerance cm3/1000 strokes	:	+ - 1.0
<hr/>		
Check tolerance cm3/1000S.	:	+ - 4.0
<hr/>		
Spreed Tolerance cm3/1000 strokes	:	5.0
<hr/>		
Check tolerance cm3/1000S.	:	9.0
<hr/>		
Del. quantity cm3/1000 strokes	:	33.0
Tolerance cm3/1000 strokes	:	+ - 3.0
Check tolerance cm3/1000S.	:	+ - 5.0
Spreed Tolerance cm3/1000 strokes	:	8.0
Check tolerance cm3/1000S.	:	12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm	:	275
guide sleeve travel mm	:	1.39
Tolerance mm	:	+ - 0.20
<hr/>		
Rated speed rpm	:	1355
guide sleeve travel mm	:	8.32
Tolerance mm	:	+ - 0.15
<hr/>		
Rated speed rpm	:	885
guide sleeve travel mm	:	5.46
Tolerance mm	:	+ - 0.25
<hr/>		
Rated speed rpm	:	480
guide sleeve travel mm	:	3.18
Tolerance mm	:	+ - 0.25
<hr/>		
Rated speed rpm	:	1860
guide sleeve travel mm	:	13.50
Tolerance mm	:	+ - 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm	:	1300
Aneroid pressure hPa	:	1200
Del. quantity cm3/1000 strokes	:	177.0
Tolerance cm3/1000 strokes	:	+ - 1.0
Check tolerance cm3/1000S.	:	+ - 4.0
Spreed Tolerance cm3/1000 strokes	:	5.0
Check tolerance cm3/1000S.	:	9.0

CONTROL LEVER

control lever position degree	:	114.0
tolerance degree	:	+ - 4.0

RATED SPEED

rack travel mm	:	11.60
Rated speed rpm	:	1375
Tolerance 1/min	:	+ - 5
<hr/>		
rack travel mm	:	7.50
Rated speed rpm	:	1470
Tolerance 1/min	:	+ - 15
<hr/>		
rack travel mm	:	0.50
Tolerance mm	:	+ - 0.50
Rated speed rpm	:	1650

LOW IDLE

control lever position degree	:	75.0
tolerance degree	:	+ - 4.0

Testing:

Rated speed rpm	:	300
rack travel mm	:	7.00
Tolerance mm	:	+ - 0.20
<hr/>		
Rated speed rpm	:	250
CRT mm min.	:	> 8.00

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1300
rack travel mm : 12.65
Tolerance mm : +- 0.05

Rated speed rpm : 900
rack travel mm : 12.40
Tolerance mm : +- 0.10

Rated speed rpm : 700
rack travel mm : 12.45
Tolerance mm : +- 0.10

Rated speed rpm : 500
rack travel mm : 12.10
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1300
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1300
rack travel mm : 9.90
Tolerance mm : +- 0.20

Rated speed rpm : 1300

Pressure hPa : 585
rack travel mm : 11.80
Tolerance mm : +- 0.20

Pressure hPa : 255
rack travel mm : 10.50
Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 250

Check
speed 1/min : > 80
Check
speed 1/min : < 260

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 183.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1300
Del. quantity
cm³/1000 strokes : 111.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 11.60
Rated speed rpm : 1375
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 11.90
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 185.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Del. quantity
cm³/1000 strokes : 33.0
Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.04.96
Test oil : ISO 4113

Combination No. : 9 400 030 730

Injection pump
Pump designation : PES6A95D320/3RS2881
EP type number : 9 410 037 215

Governor
Governor design. : RSV475...1100A0C844R
Governor no. : 9 420 034 710

Cust. part No. : 3928599

Customer-spec. information
Customer : CDC
Motor : 6BTA
Power KW : 111.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : +- 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 2.85
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Start of delivery blocking

°NW after s.o.d. : 8.50
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.00
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 103.5

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 3.0

Spreed
Tolerance
cm3/1000 strokes : 4.0

Check tolerance
cm3/1000S. : 6.5

Del. quantity
cm3/1000 strokes : 22.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Spreed
Tolerance
cm3/1000 strokes : 6.0
Check tolerance
cm3/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 5.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 900
Del. quantity
cm3/1000 strokes : 103.5
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 3.0
Spreed
Tolerance
cm3/1000 strokes : 4.0

Check tolerance
cm3/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 99.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.00
Rated speed rpm : 1155
Tolerance 1/min : +- 5

rack travel mm : 4.50
Rated speed rpm : 1225
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1300

rack travel mm : 4.50
Rated speed rpm : 1225

LOW IDLE

control lever
position degree : 76.5
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 475
rack travel mm : 4.70

Testing:

Rated speed rpm : 475
rack travel mm : 5.20
Tolerance mm : +- 0.10

Rated speed rpm : 100
CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.00
Tolerance mm : +- 0.05

Rated speed rpm : 800

rack travel mm : 13.10
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.80
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 600
rack travel mm : 12.30
Tolerance mm : +- 0.20

Pressure hPa : 360
rack travel mm : 10.40
Tolerance mm : +- 0.20

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 800
Del. quantity
cm3/1000 strokes : 118.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 79.5
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 11.00

B21

Rated speed rpm : 1155
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm3/1000 strokes : 120.5
Tolerance
cm3/1000 strokes : +- 10.0
Check tolerance
cm3/1000S. : +- 15.0

LOW IDLE

Del. quantity
cm3/1000 strokes : 22.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Speed
Tolerance
cm3/1000 strokes : 6.0
Check tolerance
cm3/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 07.11.95
 Test oil : ISO 4113
 Combination No. : 9 400 230 107
 Injection pump
 Pump designation : PES6A100D320/3RS2691
 : -2
 EP type number : 9 410 230 028
 Governor
 Governor design. : RQV350...1200AB1233R
 Governor no. : 9 420 231 018
 Cust. part No. : 3912643

Customer-spec. information

Customer : CDC
 Motor : 6CT830
 Power KW : 157.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
 Test oil inlet
 temp. °C : 40
 Tolerance °C : +- 2.0
 Overflow valve : 1 417 413 047
 Inlet press. bar : 1.5
 Test nozzle holde
 assembly : 1 688 901 101
 Opening pressure
 bar : 208.5
 Tolerance bar : +- 1.5
 Test lines : 1 680 750 014
 Outside diameter : 6.0

x inside diameter : 2.0
 x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING .UES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
 Tolerance bar : +- 1.0
 Prestroke mm : 2.85
 Tolerance mm : +- 0.05
 Check
 tolerance mm : +- 0.10
 Rack travel in mm : 10.50
 Tolerance mm : +- 1.50
 Firing order : 1- 5- 3- 6- 2-
 : 4
 Phasing : 0-60-120-180-240
 : -300
 Tolerance : +- 0.50
 Check
 tolerance *NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1200
 Rack travel in mm : 10.80
 Tolerance mm : +- 0.05
 Del. quantity
 cm3/1000 strokes : 113.5
 Tolerance
 cm3/1000 strokes : +- 1.0
 Check tolerance
 cm3/1000S. : +- 3.0
 Spreed
 Tolerance
 cm3/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

 Del. quantity
 cm³/1000 strokes : 19.0
 Tolerance
 cm³/1000 strokes : ± 2.0
 Check tolerance
 cm³/1000S. : ± 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 250
 guide sleeve
 travel mm : 0.10
 Tolerance mm : ± 0.10

Rated speed rpm : 1200
 guide sleeve
 travel mm : 6.90
 Tolerance mm : ± 0.15

Rated speed rpm : 350
 guide sleeve
 travel mm : 1.25
 Tolerance mm : ± 0.25

Rated speed rpm : 450
 guide sleeve
 travel mm : 2.15
 Tolerance mm : ± 0.25

Rated speed rpm : 1350
 guide sleeve
 travel mm : 8.40
 Tolerance mm : ± 0.25

GUIDE SLEEVE POSITION

Rated speed rpm : 1435

 Rack travel in mm : 8.00
 Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200

Aneroid pressure
 hPa : 700
 Del. quantity
 cm³/1000 strokes : 113.5
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 93.0
 tolerance degree : ± 3.0

RATED SPEED

rack travel mm : 9.80
 Rated speed rpm : 1245
 Tolerance 1/min : ± 5

rack travel mm : 4.00
 Rated speed rpm : 1330
 Tolerance 1/min : ± 15

rack travel mm : 0.50
 Tolerance mm : ± 0.50
 Rated speed rpm : 1400

LOW IDLE

control lever
 position degree : 62.0
 tolerance degree : ± 3.0

Testing:

Rated speed rpm : 350
 rack travel mm : 4.70
 Tolerance mm : ± 0.10

Rated speed rpm : 250

 CRT mm min. : > 8.00

TORQUE CONTROL

Rated speed rpm : 1200
 rack travel mm : 10.80

Tolerance mm : +- 0.05
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700
rack travel mm : 10.85
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 345
rack travel mm : 10.50
Tolerance mm : +- 0.20

Pressure hPa : 260
rack travel mm : 9.95
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 290

Check speed 1/min : > 80

Check speed 1/min : < 300

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 87.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 9.80
Rated speed rpm : 1245
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 15.0

LOW IDLE

Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.03.96
Test oil : ISO 4113
Combination No. : 0 402 646 761
Injection pump
Pump designation : PE6P120A320LS7834
: -10
EP type number : 0 412 626 853
Governor
Governor design. : RQ300/1050PA1031-19
Governor no. : 0 421 801 768
Cust. part No. : 0260743802

Customer-spec. information
Customer : MB-NFZ
Motor : OM401 LA
Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Tolerance l/h : ± 10.0
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 20.50
Tolerance mm : ± 0.50
Firing order : 6- 3- 5- 2- 4-
: 1-
Phasing : 0-60-120-180-240
: -300-360
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75
Start of delivery mark
Barrel no. : 6

BASIC SETTING

Rated speed rpm : 550
Rack travel in mm : 14.80
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 230.0

Tolerance
 cm³/1000 strokes : +- 1.0

 Check tolerance
 cm³/1000S. : +- 4.0

 Spreed
 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0
 Rated speed rpm : 300
 Rack travel in mm : 6.30
 Tolerance mm : +- 0.30
 Del. quantity
 cm³/1000 strokes : 13.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.78
 Tolerance mm : +- 0.10

 Rated speed rpm : 1104
 guide sleeve
 travel mm : 6.51
 Tolerance mm : +- 0.10

 Rated speed rpm : 1050
 guide sleeve
 travel mm : 6.00
 Tolerance mm : +- 0.10

 Rated speed rpm : 379
 guide sleeve
 travel mm : 3.11
 Tolerance mm : +- 0.10

 Rated speed rpm : 550
 guide sleeve
 travel mm : 6.00
 Tolerance mm : +- 0.10

Rated speed rpm : 1270
 guide sleeve
 travel mm : 11.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 600
 Rack travel in mm : 20.00
 Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 550
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 230.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 99.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.80
 Rated speed rpm : 1098
 Tolerance 1/min : +- 8

 rack travel mm : 4.00
 Rated speed rpm : 1195
 Tolerance 1/min : +- 15

 rack travel mm : 0.75
 Tolerance mm : +- 0.75
 Rated speed rpm : 1300

LOW IDLE

Control lever
position degree : 60.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 3.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 350
Tolerance 1/min : ± 20

Rated speed rpm : 200

CRT mm min. : > 5.30

TORQUE CONTROL

Rated speed rpm : 550
rack travel mm : 14.80
Tolerance mm : ± 0.05

Rated speed rpm : 1050
rack travel mm : 14.80
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : 14.80
Tolerance mm : ± 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1000
rack travel mm : 14.80
Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 10.50
Tolerance mm : ± 0.15

Rated speed rpm : 400

Pressure hPa : 400
rack travel mm : 12.90
Tolerance mm : ± 0.20

Pressure hPa : 600

rack travel mm : 14.15
Tolerance mm : ± 0.20

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 229.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 13.80
Rated speed rpm : 1098
Tolerance 1/min : ± 8

STARTING FUEL DELIVERY

Rated speed rpm : 100

Del. quantity
cm³/1000 strokes : 210.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 300
rack travel mm : 6.30
Tolerance mm : ± 0.30
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.04.96
Test oil : ISO 4113
Combination No. : 9 400 085 392
Injection pump
Pump designation : PES6A95D320RS2806
EP type number : 0 410 896 898
Governor
Governor design. : RSV375...1150A0C830R
Governor no. : 9 420 083 305
Cust. part No. : 82085500

Customer-spec. information
Customer : VALMET
Motor : 620 DS
Power KW : 125.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 2.75
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Beginning of delivery difference

and maximum rack travel : 10.50
Tolerance mm : ± 1.50
Difference ° CS : 4.00

BASIC SETTING

Rated speed rpm : 1150
Rack travel in mm : 12.75
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 95.0
Tolerance cm³/1000 strokes : ± 1.0
Check tolerance cm³/1000S. : ± 3.0

Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

Del. quantity
cm³/1000 strokes : 12.5

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spreed
Tolerance
cm³/1000 strokes : 5.5

Check tolerance
cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
Tolerance mm : +- 0.35

governor spring
pre-tension
click setting x : 3.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 95.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 37.0
tolerance degree : +- 4.0

control lever
position degree : 87.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.70
Rated speed rpm : 1175
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1255
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 66.0
tolerance degree : +- 4.0

control lever
position degree : 16.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 375
rack travel mm : 5.00

Testing:

Rated speed rpm : 375
rack travel mm : 5.50
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 465
Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19 00

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 12.75

Tolerance mm : +- 0.05
Rated speed rpm : 700
rack travel mm : 13.85
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 13.85
Tolerance mm : +- 0.05

Rated speed rpm : 1100
rack travel mm : 12.75
Tolerance mm : +- 0.05

Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 5.5
Check tolerance
cm³/1000S. : 9.0

End of test specification sheet

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 103.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.70
Rated speed rpm : 1175
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 196.0
Tolerance
cm³/1000 strokes : +- 7.5
Check tolerance
cm³/1000S. : +- 10.0

LOW IDLE

Del. quantity
cm³/1000 strokes : 12.5

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 30.03.96
Test oil : ISO 4113

Combination No. : 9 400 083 426

Injection pump
Pump designation : PES4A80D320/3RS1265
EP type number : 9 400 083 055

Governor
Governor design. : RSV350...1200A2C627R
Governor no. : 9 420 083 288

Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : D225-4

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 003

Outside diameter : 6.0

x inside diameter : 2.0

C04

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270

Beginning of delivery difference

and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1200

Rack travel in mm : 9.45
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 51.0

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000S. : +- 2.0

Speed

Tolerance
 cm³/1000 strokes : 2.5

Check tolerance
 cm³/1000S. : 4.0

Rated speed rpm : 350

Rack travel in mm : 7.00
 Tolerance mm : +- 0.10

Del. quantity
 cm³/1000 strokes : 9.0
 Tolerance
 cm³/1000 strokes : +- 1.5
 Check tolerance
 cm³/1000S. : +- 3.5

Spread
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
 Tolerance mm : +- 0.35

governor spring
 pre-tension
 click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
 Aneroid pressure
 hPa : -

Del. quantity
 cm³/1000 strokes : 51.0
 Tolerance
 cm³/1000 strokes : +- 0.5
 Check tolerance
 cm³/1000S. : +- 2.0

Spread
 Tolerance
 cm³/1000 strokes : 2.5
 Check tolerance
 cm³/1000S. : 4.0

CONTROL LEVER

control lever
 position degree : 101.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 8.40
 Rated speed rpm : 1245
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1300
 Tolerance 1/min : +- 15

rack travel mm : 1.00
 Tolerance mm : +- 0.70
 Rated speed rpm : 1450

LOW IDLE

control lever
 position degree : 74.0
 tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
 rack travel mm : 5.50

Testing:

Rated speed rpm : 350
 rack travel mm : 6.00
 Tolerance mm : +- 0.10

rack travel mm : 2.00
 Rated speed rpm : 500
 Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1200
 rack travel mm : 9.45
 Tolerance mm : +- 0.05

Rated speed rpm : 500
 rack travel mm : 9.50
 Tolerance mm : +- 0.10

Rated speed rpm : 400
 rack travel mm : 10.90

Tolerance mm : +- 0.30

BREAKAWAY

Rack travel in mm : 8.40
Rated speed rpm : 1245
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

Rated speed rpm : 350
rack travel mm : 7.00
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 9.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.5
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.05.95
Test oil : ISO 4113
Combination No. : 0 402 046 827
Injection pump
Pump designation : PES6P120A320RS3284
EP type number : 0 412 026 749
Governor
Governor design. : RQ275/1050PA999-3
Governor no. : 0 421 801 598
Cust. part No. : CCEP5119A

Customer-spec. information
Customer : RVI
Motor : MIDR/PR 062045
Power KW : 186.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 071
Inlet press. bar : 2.5
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0
x inside diameter : 3.0

C07

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 10.35
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 155.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -5.40
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 155.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1118

Tolerance 1/min : +- 8

rack travel mm : -6.30
Rated speed rpm : 1205
Tolerance 1/min : +- 15

rack travel mm : -9.85
Tolerance mm : +- 0.55
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 252.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -5.40
Tolerance mm : +- 0.10

rack travel mm : -8.10
Rated speed rpm : 340
Tolerance 1/min : +- 20

Rated speed rpm : 200

CRT mm max. : < -4.00

TORQUE CONTROL

Rated speed rpm : 1050
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -2.20
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 360
rack travel mm : -0.40
Tolerance mm : +- 0.20

Pressure hPa : 200
rack travel mm : -1.45
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

Check
speed 1/min : > 80
Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 149.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 81.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1118
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 170.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.05.95
 Test oil : ISO 4113
 Combination No. : 0 402 046 829
 Injection pump
 Pump designation : PES6P120A320RS3284
 EP type number : 0 412 026 749
 Governor
 Governer design. : RQV275...1050PA995
 : -1
 Governer no. : 0 421 813 941
 Cust. part No. : CCEP 5120A 66-177

Customer-spec. information
 Customer : RVI
 Motor : MIDR06.20.45 B/3
 Power KW : 195.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
 Test oil inlet temp. °C : 40
 Tolerance °C : +- 2.0
 Overflow valve : 2 417 413 071
 Inlet press. bar : 2.5
 Test nozzle holde assembly : 1 688 901 105
 Opening pressure bar : 208.5
 Tolerance bar : +- 1.5
 Test Lines : 1 680 750 089
 Outside diameter : 8.0

C10

x inside diameter : 3.0
 x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
 Tolerance bar : +- 1.0
 Prestroke mm : 3.55
 Tolerance mm : +- 0.05
 Check tolerance mm : +- 0.10
 Rack travel in mm : 10.50
 Tolerance mm : +- 1.50
 Firing order : 1- 5- 3- 6- 2-
 : 4
 Phasing : 0-60-120-180-240
 : -300
 Tolerance : +- 0.30
 Check tolerance °NW : +- 0.50
 Start of delivery mark
 Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700
 Rack travel in mm : 10.70
 Tolerance mm : +- 0.05
 Del. quantity cm3/1000 strokes : 157.0
 Tolerance cm3/1000 strokes : +- 1.0
 Check tolerance cm3/1000S. : +- 4.0

Spreed	
Tolerance	
cm ³ /1000 strokes :	5.0

Check tolerance	
cm ³ /1000S.	: 9.0
Rated speed rpm :	275
Rack travel in mm :	-5.20
Tolerance mm :	+ - 0.10
Del. quantity	
cm ³ /1000 strokes :	25.0
Tolerance	
cm ³ /1000 strokes :	+ - 2.0
Check tolerance	
cm ³ /1000S.	: + - 5.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	8.0
Check tolerance	
cm ³ /1000S.	: 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm :	1220
Rack travel in mm :	10.50
Tolerance mm :	+ - 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	700
Aneroid pressure	
hPa :	1000
Del. quantity	
cm ³ /1000 strokes :	157.0
Tolerance	
cm ³ /1000 strokes :	+ - 1.0
Check tolerance	
cm ³ /1000S.	: + - 4.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S.	: 9.0

CONTROL LEVER

control lever	
position degree :	300.0
tolerance degree :	+ - 4.0

RATED SPEED

rack travel mm :	-1.00
Rated speed rpm :	1125
Tolerance 1/min :	+ - 5

rack travel mm :	-6.70
Rated speed rpm :	1220
Tolerance 1/min :	+ - 15

rack travel mm :	-10.20
Tolerance mm :	+ - 0.55
Rated speed rpm :	1350

LOW IDLE

control lever	
position degree :	247.0
tolerance degree :	+ - 4.0

Testing:

Rated speed rpm :	275
rack travel mm :	-5.20
Tolerance mm :	+ - 0.10

Rated speed rpm :	200
-------------------	-----

CRT mm max. :	< -3.60
---------------	---------

Rated speed rpm :	390
-------------------	-----

TORQUE CONTROL

Rated speed rpm :	1050
Tolerance mm :	+ - 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm :	500
Pressure hPa :	1000

MEASUREMENT

Pressure hPa :	-
Rated speed rpm :	500

rack travel mm : -1.35
Tolerance mm : +- 0.15

Rated speed rpm : 500

Pressure hPa : 130
rack travel mm : -1.00
Tolerance mm : +- 0.10

Pressure hPa : 240
rack travel mm : -0.35
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 210

Check speed 1/min : > 80
Check speed 1/min : < 230

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1000
Rated speed rpm : 1050
Del. quantity cm3/1000 strokes : 153.0
Tolerance cm3/1000 strokes : +- 3.0
Check tolerance cm3/1000S. : +- 6.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm3/1000 strokes : 108.0
Tolerance cm3/1000 strokes : +- 1.0
Check tolerance cm3/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1125
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Del. quantity cm3/1000 strokes : 175.0
Tolerance cm3/1000 strokes : +- 15.0
Check tolerance cm3/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity cm3/1000 strokes : 25.0
Tolerance cm3/1000 strokes : +- 2.0
Check tolerance cm3/1000S. : +- 5.0
Speed Tolerance cm3/1000 strokes : 8.0
Check tolerance cm3/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 12.05.95
Test oil : ISO 4113
Combination No. : 0 402 046 836
Injection pump
Pump designation : PES6P120A320RS3303
EP type number : 0 412 026 755
Governor
Governor design. : RQV275...1050PA1038K
Governor no. : 0 421 815 313
Cust. part No. : CCEP-5129B 66-195

Customer-spec. information
Customer : RVI
Motor : MIDR 062045 J/3
Power KW : 169.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 071
Inlet press. bar : 2.5
Tolerance bar : +- 0.1
Test nozzle holde assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 0.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050
Rack travel in mm : 11.05
Tolerance mm : +- 0.05
Del. quantity cm3/1000 strokes : 157.0
Tolerance cm3/1000 strokes : +- 1.0
Check tolerance cm3/1000S. : +- 4.0

Spreed
 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0

 Rated speed rpm : 275

 Rack travel in mm : -5.50
 Tolerance mm : +- 0.20
 Del. quantity
 cm³/1000 strokes : 24.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
 guide sleeve
 travel mm : 1.34
 Tolerance mm : +- 0.25

 Rated speed rpm : 1140
 guide sleeve
 travel mm : 9.03
 Tolerance mm : +- 0.25

 Rated speed rpm : 740
 guide sleeve
 travel mm : 6.16
 Tolerance mm : +- 0.25

 Rated speed rpm : 336
 guide sleeve
 travel mm : 2.38
 Tolerance mm : +- 0.25

 Rated speed rpm : 386
 guide sleeve
 travel mm : 3.12
 Tolerance mm : +- 0.25

 Rated speed rpm : 440
 guide sleeve
 travel mm : 3.94

Tolerance mm : +- 0.25
 Rated speed rpm : 1530
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1330
 Rack travel in mm : 9.90
 Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 157.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 56.0
 tolerance degree : +- 4.0

 control lever
 position degree : 287.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1110
 Tolerance 1/min : +- 5

 rack travel mm : -7.00
 Rated speed rpm : 1240
 Tolerance 1/min : +- 15

 rack travel mm : -10.55
 Tolerance mm : +- 0.55
 Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 242.0
tolerance degree : +- 4.0

control lever
position degree : 12.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -5.50
Tolerance mm : +- 0.20

Rated speed rpm : 200

CRT mm max. : < -4.70

Rated speed rpm : 330

TORQUE CONTROL

Rated speed rpm : 1050

Rated speed rpm : 700
rack travel mm : -0.80
Tolerance mm : +- 0.10

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 235

Check
speed 1/min : > 155

Check
speed 1/min : < 255

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 137.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1110
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 170.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 24.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 01.08.95
Test oil : ISO 4113
Combination No. : 0 402 744 801
Injection pump
Pump designation : PES4P120A320RS7380
EP type number : 0 412 724 802
Governor
Governor design. : RQV275...1300PA1232K
Governor no. : 0 421 815 469

Cust. part No. : CCEP 5149 66-237

Customer-spec. information
Customer : RVI
Motor : MIDR 04-02-26 B4
Power KW : 110.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Overflow quantity
min. L/h : 95
Tolerance L/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 11.00
Tolerance mm : ± 0.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1200

Rack travel in mm : 12.70
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 236.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
 cm³/1000S. : +- 4.0

 Spreed
 Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0

 Rated speed rpm : 325

 Rack travel in mm : -6.60
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 40.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 325
 guide sleeve
 travel mm : 1.57
 Tolerance mm : +- 0.25

 Rated speed rpm : 1381
 guide sleeve
 travel mm : 10.37
 Tolerance mm : +- 0.25

 Rated speed rpm : 940
 guide sleeve
 travel mm : 6.87
 Tolerance mm : +- 0.25

 Rated speed rpm : 390
 guide sleeve
 travel mm : 2.39
 Tolerance mm : +- 0.25

 Rated speed rpm : 440
 guide sleeve
 travel mm : 2.90
 Tolerance mm : +- 0.25

 Rated speed rpm : 560

guide sleeve
 travel mm : 4.01
 Tolerance mm : +- 0.25

 Rated speed rpm : 1650
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1500

 Rack travel in mm : 11.10
 Tolerance mm : +- 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
 Aneroid pressure
 hPa : 1200
 Del. quantity
 cm³/1000 strokes : 236.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 302.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.60
 Rated speed rpm : 1352
 Tolerance 1/min : +- 5

 rack travel mm : -8.70
 Rated speed rpm : 1465
 Tolerance 1/min : +- 15

 rack travel mm : -12.20
 Tolerance mm : +- 0.50
 Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 253.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 325
rack travel mm : -6.60
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : < -4.60

Rated speed rpm : 390

TORQUE CONTROL

Rated speed rpm : 1200

Rated speed rpm : 700
rack travel mm : -1.15
Tolerance mm : +- 0.10

Rated speed rpm : 1300
rack travel mm : -0.50
Tolerance mm : +- 0.25

Rated speed rpm : 350
rack travel mm : -2.90
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1200
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -4.20
Tolerance mm : +- 0.20

Rated speed rpm : 1200

Pressure hPa : 320
rack travel mm : -3.60
Tolerance mm : +- 0.20

Pressure hPa : 520
rack travel mm : -2.50

Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 130
Rated speed rpm : < 275

Check
speed 1/min : > 110
Check
speed 1/min : < 285

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 237.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : 1200
Rated speed rpm : 1300
Del. quantity
cm³/1000 strokes : 225.0
Tolerance
cm³/1000 strokes : +- 6.0
Check tolerance
cm³/1000S. : +- 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.60
Rated speed rpm : 1352
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100

Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000s. : +- 19.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 40.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.05.95
Test oil : ISO 4113
Combination No. : 0 402 746 924
Injection pump
Pump designation : PES6P110A32ORS7243
EP type number : 0 412 716 806
Governor
Governor design. : RQV275...1250PA942
: -2K
Governor no. : 0 421 815 288
Cust. part No. : CCEP5124B

Customer-spec. information
Customer : RVI
Motor : MIDR06-06-26 L/2
Power KW : 132.5

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

C20

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.90
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 13.50
Tolerance mm : ± 0.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250
Rack travel in mm : 13.05
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 141.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000s. : ± 3.5

Spreed
 Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 7.5

Rated speed rpm : 275

Rack travel in mm : -7.60
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 26.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1320
 guide sleeve
 travel mm : 9.80
 Tolerance mm : +- 0.10

Rated speed rpm : 1000
 guide sleeve
 travel mm : 7.20
 Tolerance mm : +- 0.20

Rated speed rpm : 275
 guide sleeve
 travel mm : 1.00
 Tolerance mm : +- 0.10

Rated speed rpm : 600
 guide sleeve
 travel mm : 4.40
 Tolerance mm : +- 0.20

Rated speed rpm : 1600
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1450
 Rack travel in mm : 10.10
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 141.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.5

CONTROL LEVER

control lever
 position degree : 276.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1325
 Tolerance 1/min : +- 5

rack travel mm : -9.00
 Rated speed rpm : 1475
 Tolerance 1/min : +- 15

rack travel mm : -12.55
 Tolerance mm : +- 0.55
 Rated speed rpm : 1600

LOW IDLE

control lever
 position degree : 222.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
 rack travel mm : -7.60
 Tolerance mm : +- 0.10

Rated speed rpm : 200
CRT mm min. : < -7.00
Rated speed rpm : 415

TORQUE CONTROL

Rated speed rpm : 1250
Rated speed rpm : 650
rack travel mm : -1.00
Tolerance mm : +- 0.10
Rated speed rpm : 650
rack travel mm : -6.00
Tolerance mm : +- 0.10
Rated speed rpm : 300
rack travel mm : -1.60
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : -2.70
Tolerance mm : +- 0.20
Rated speed rpm : 1250
Pressure hPa : 180
rack travel mm : -2.25
Tolerance mm : +- 0.15
Pressure hPa : 280
rack travel mm : -1.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 225
Check speed 1/min : > 155
Check speed 1/min : < 245

C22

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 126.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 40.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0
Speed
Tolerance
cm³/1000 strokes : 10.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 80.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.5
Speed
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1325
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 115.0
Tolerance
cm³/1000 strokes : +- 15.0

Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.05.95
Test oil : ISO 4113
Combination No. : 0 402 746 928
Injection pump
Pump designation : PES6P110A320RS7243
EP type number : 0 412 716 806
Governor
Governor design. : RQV275...1175PA942
: -3K
Governor no. : 0 421 815 294
Cust. part No. : CCEP5125B

Customer-spec. information
Customer : RVI
Motor : MIDR06-06-26 M/2
Power KW : 132.5

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.90
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 13.50
Tolerance mm : ± 0.05
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1175
Rack travel in mm : 13.45
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.5

Spreed
 Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 7.5

Rated speed rpm : 275

Rack travel in mm : -8.30
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 25.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1250
 guide sleeve
 travel mm : 9.20
 Tolerance mm : +- 0.10

Rated speed rpm : 1000
 guide sleeve
 travel mm : 7.20
 Tolerance mm : +- 0.20

Rated speed rpm : 275
 guide sleeve
 travel mm : 1.00
 Tolerance mm : +- 0.10

Rated speed rpm : 600
 guide sleeve
 travel mm : 4.40
 Tolerance mm : +- 0.20

Rated speed rpm : 1600
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1450
 Rack travel in mm : 10.10
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1175
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 153.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.5

CONTROL LEVER

control lever
 position degree : 294.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1260
 Tolerance 1/min : +- 5

rack travel mm : -9.45
 Rated speed rpm : 1440
 Tolerance 1/min : +- 15

rack travel mm : -12.95
 Tolerance mm : +- 0.55
 Rated speed rpm : 1550

rack travel mm : 4.00

LOW IDLE

control lever
 position degree : 242.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
 rack travel mm : -8.30

Tolerance mm : +- 0.10
Rated speed rpm : 200
CRT mm min. : < -7.70
Rated speed rpm : 415

TORQUE CONTROL

Rated speed rpm : 1175
Rated speed rpm : 700
rack travel mm : -0.75
Tolerance mm : +- 0.10
Rated speed rpm : 700
rack travel mm : -6.50
Tolerance mm : +- 0.10
Rated speed rpm : 300
rack travel mm : -1.50
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1175
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1175
rack travel mm : -3.40
Tolerance mm : +- 0.10
Rated speed rpm : 1175
Pressure hPa : 240
rack travel mm : 0.10
Tolerance mm : +- 2.70
Pressure hPa : 420
rack travel mm : -1.70
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 225
Check
speed 1/min : > 155

Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 151.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 40.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0
Speed
Tolerance
cm³/1000 strokes : 10.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 80.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.5
Speed
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1260
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 115.0

Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 12.05.95
Test oil : ISO 4113

Combination No. : 0 402 746 952

Injection pump
Pump designation : PES6P120A32ORS7294
EP type number : 0 412 726 895

Governor
Governor design. : RQV275...1000PA1001
: -2
Governor no. : 0 421 813 989

Cust. part No. : CCEP-5136 66-214

Customer-spec. information
Customer : RVI
Motor : MIDR 063540 N/3
Power KW : 283.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5
Tolerance bar : +- 0.1

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 19.50
Tolerance mm : +- 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance *NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : -7.25
Tolerance mm : +- 0.30

Del. quantity
cm³/1000 strokes : 74.0

Tolerance
 cm³/1000 strokes : +- 1.0

 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.0
 Rated speed rpm : 600

 Rack travel in mm : 13.35
 Tolerance mm : +- 0.05

 Del. quantity
 cm³/1000 strokes : 290.0

 Tolerance
 cm³/1000 strokes : +- 2.0

 Check tolerance
 cm³/1000S. : +- 5.0

 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0
 Rated speed rpm : 300

 Rack travel in mm : -8.20
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 31.0
 Tolerance
 cm³/1000 strokes : +- 2.5
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.66
 Tolerance mm : +- 0.10
 Rated speed rpm : 1086
 guide sleeve
 travel mm : 8.46
 Tolerance mm : +- 0.10
 Rated speed rpm : 773
 guide sleeve
 travel mm : 6.09
 Tolerance mm : +- 0.20
 Rated speed rpm : 343
 guide sleeve
 travel mm : 2.33
 Tolerance mm : +- 0.20
 Rated speed rpm : 393
 guide sleeve
 travel mm : 2.99
 Tolerance mm : +- 0.20
 Rated speed rpm : 490
 guide sleeve
 travel mm : 3.81
 Tolerance mm : +- 0.20
 Rated speed rpm : 1370
 guide sleeve
 travel mm : 11.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1200
 Rack travel in mm : 12.20
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 290.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 301.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1070
Tolerance 1/min : +- 5

rack travel mm : -9.30
Rated speed rpm : 1205
Tolerance 1/min : +- 15

rack travel mm : -12.85
Tolerance mm : +- 0.55
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 247.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -8.20
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm max. : < -6.80

Rated speed rpm : 365

TORQUE CONTROL

Rated speed rpm : 600

Rated speed rpm : 1000
Tolerance mm : +- 0.10

Rated speed rpm : 600
rack travel mm : -4.50
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.80
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 240
rack travel mm : -2.60
Tolerance mm : +- 0.20

Pressure hPa : 480
rack travel mm : -0.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

Check
speed 1/min : > 80
Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 270.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 7.0

Aneroid pressure
hPa : 1000
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 159.0
Tolerance
cm³/1000 strokes : +- 5.0

Check tolerance
cm³/1000S. : +- 8.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 167.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1070
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 31.0
Tolerance
cm³/1000 strokes : +- 2.5
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.08.95
Test oil : ISO 4113
Combination No. : 0 402 744 804
Injection pump
Pump designation : PES4P120A320RS7402
EP type number : 0 412 724 804
Governor
Governor design. : RQV275...1300PA1257K
Governor no. : 0 421 815 494
Cust. part No. : CCEP 5154 66-238

Customer-spec. information
Customer : RVI
Motor : MIDR 04-02-26 A4
Power KW : 100.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 071
Inlet press. bar : 2.5
Test nozzle holder assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 5.20
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 13.00
Tolerance mm : +- 0.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1200

Rack travel in mm : 14.10
Tolerance mm : +- 0.05

Del. quantity cm³/1000 strokes : 245.0

Tolerance cm³/1000 strokes : +- 1.0

Check tolerance cm³/1000S. : +- 4.0

Speed

Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 325

Rack travel in mm : -8.80
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 28.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 325
 guide sleeve
 travel mm : 1.52
 Tolerance mm : +- 0.20

Rated speed rpm : 1377
 guide sleeve
 travel mm : 10.32
 Tolerance mm : +- 0.15

Rated speed rpm : 938
 guide sleeve
 travel mm : 6.86
 Tolerance mm : +- 0.25

Rated speed rpm : 550
 guide sleeve
 travel mm : 3.92
 Tolerance mm : +- 0.25

Rated speed rpm : 1650
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1464

Rack travel in mm : 13.10
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
 Aneroid pressure
 hPa : 1200
 Del. quantity
 cm³/1000 strokes : 245.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 300.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1365
 Tolerance 1/min : +- 5

rack travel mm : -10.10
 Rated speed rpm : 1495
 Tolerance 1/min : +- 15

rack travel mm : -14.05
 Tolerance mm : +- 0.50
 Rated speed rpm : 1550

LOW IDLE

control lever
 position degree : 252.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 325
 rack travel mm : -8.80
 Tolerance mm : +- 0.10

Rated speed rpm : 225

CRT mm min. : > 6.54

Rated speed rpm : 390

TORQUE CONTROL

Rated speed rpm : 1200

Rated speed rpm : 850
rack travel mm : -1.05
Tolerance mm : +- 0.10

Rated speed rpm : 1300
rack travel mm : -0.45
Tolerance mm : +- 0.25

Rated speed rpm : 700
rack travel mm : -6.00
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1200
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1200
rack travel mm : -2.50
Tolerance mm : +- 0.20

Rated speed rpm : 1200

Pressure hPa : 200
rack travel mm : -1.95
Tolerance mm : +- 0.20

Pressure hPa : 440
rack travel mm : -0.70
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 130
Rated speed rpm : < 275

Check
speed 1/min : > 110
Check
speed 1/min : < 285

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 850
Del. quantity
cm³/1000 strokes : 235.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : 1200
Rated speed rpm : 1300
Del. quantity
cm³/1000 strokes : 235.0
Tolerance
cm³/1000 strokes : +- 6.0
Check tolerance
cm³/1000S. : +- 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 1200
Del. quantity
cm³/1000 strokes : 183.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1365
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 325

Del. quantity
cm³/1000 strokes : 28.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 18.07.95
Test oil : ISO 4113

Combination No. : 0 402 746 894

Injection pump
Pump designation : PES6P110A320RS7208
EP type number : 0 412 716 803

Governor
Governor design. : RQV275...1175PA942
: -1K
Governor no. : 0 421 815 244

Cust. part No. : CCEP 5100A

Customer-spec. information
Customer : RVI
Motor : MIDR060226 M
Power KW : 210.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.15
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 13.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1175

Rack travel in mm : 14.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 171.0

Tolerance
 cm³/1000 strokes : +- 1.0

Check tolerance
 cm³/1000S. : +- 3.5

Spreed
 Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 7.5

Rated speed rpm : 275

Rack travel in mm : -8.80
 Tolerance mm : +- 0.20
 Del. quantity
 cm³/1000 strokes : 21.0
 Tolerance
 cm³/1000 strokes : +- 2.5
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.5

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
 guide sleeve
 travel mm : 1.00
 Tolerance mm : +- 0.25

Rated speed rpm : 1256
 guide sleeve
 travel mm : 9.17
 Tolerance mm : +- 0.25

Rated speed rpm : 888
 guide sleeve
 travel mm : 6.57
 Tolerance mm : +- 0.25

Rated speed rpm : 390
 guide sleeve
 travel mm : 2.39
 Tolerance mm : +- 0.25

Rated speed rpm : 440
 guide sleeve
 travel mm : 3.01

Tolerance mm : +- 0.25

Rated speed rpm : 550
 guide sleeve
 travel mm : 3.92
 Tolerance mm : +- 0.25

Rated speed rpm : 1650
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1400

Rack travel in mm : 13.00
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1175
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 171.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 7.5

CONTROL LEVER

control lever
 position degree : 114.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1245
 Tolerance 1/min : +- 5

rack travel mm : -10.05
 Rated speed rpm : 1430
 Tolerance 1/min : +- 15

rack travel mm : -13.55
 Tolerance mm : +- 0.55
 Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 60.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -8.80
Tolerance mm : +- 0.20

Rated speed rpm : 200

CRT mm max. : < -8.20

Rated speed rpm : 415

TORQUE CONTROL

Rated speed rpm : 1175

Rated speed rpm : 700
rack travel mm : -0.70
Tolerance mm : +- 0.10

Rated speed rpm : 700
rack travel mm : -6.05
Tolerance mm : +- 0.10

Rated speed rpm : 800
rack travel mm : -0.35
Tolerance mm : +- 0.15

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1175
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1175
rack travel mm : -3.30
Tolerance mm : +- 0.20

Rated speed rpm : 1175

Pressure hPa : 240
rack travel mm : -2.70
Tolerance mm : +- 0.20

Pressure hPa : 520
rack travel mm : -1.45
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 150
Rated speed rpm : < 200

Check
speed 1/min : > 130
Check
speed 1/min : < 220

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 151.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 55.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0
Spreed
Tolerance
cm³/1000 strokes : 8.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 75.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.5

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1245
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : +- 2.5
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.08.95
Test oil : ISO 4113

Combination No. : 0 402 746 909

Injection pump
Pump designation : PES6P120A320RS7236
EP type number : 0 412 726 848

Governor
Governor design. : RQV275...1000PA1001
: -1
Governor no. : 0 421 813 936

Cust. part No. : CCEP 5116A PROJ.171

Customer-spec. information

Customer : RVI
Motor : MIDR 063540 J/3
Power KW : 306.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.55
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 13.50
Tolerance mm : +- 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 13.80
Tolerance mm : +- 0.05

Del. quantity cm³/1000 strokes : 310.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : -8.60
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 31.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1150

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 310.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 302.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1070
Tolerance 1/min : +- 5

rack travel mm : -9.70
Rated speed rpm : 1210
Tolerance i/min : +- 15

rack travel mm : -13.25
Tolerance mm : +- 0.55
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 246.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -8.60
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm max. : < -7.20

Rated speed rpm : 370

TORQUE CONTROL

Rated speed rpm : 600

Rated speed rpm : 1000
Tolerance mm : +- 0.10

Rated speed rpm : 500
rack travel mm : -5.50
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -5.00
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 240
rack travel mm : -3.80
Tolerance mm : +- 0.20

Pressure hPa : 600
rack travel mm : -0.95
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 225

Check
speed 1/min : > 80
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 287.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 138.0
Tolerance
cm³/1000 strokes : +- 5.0

Check tolerance
cm³/1000S. : +- 8.0

Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 152.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1070
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 31.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.08.95
Test oil : ISO 4113

Combination No. : 0 402 746 931

Injection pump
Pump designation : PES6P120A320RS7236
EP type number : 0 412 726 848

Governor
Governor design. : RQV275...1000PA1001
: -2
Governor no. : 0 421 813 989

Cust. part No. : CCEP5128A 66-194

Customer-spec. information

Customer : RVI
Motor : MIDR 063540 N/3
Power KW : 283.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5
Tolerance bar : +- 0.1

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 19.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : -7.25
Tolerance mm : +- 0.30

Del. quantity
cm³/1000 strokes : 74.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.0

Rated speed rpm : 600

Rack travel in mm : 13.35
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 290.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 300

Rack travel in mm : -8.20
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 31.0

Tolerance
cm³/1000 strokes : +- 2.5

Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1190

Rack travel in mm : 13.20
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure

hPa : 1000
Del. quantity

cm³/1000 strokes : 290.0
Tolerance

cm³/1000 strokes : +- 2.0
Check tolerance

cm³/1000S. : +- 5.0
Speed

Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 301.0

tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1070

Tolerance 1/min : +- 5

rack travel mm : -9.30
Rated speed rpm : 1205

Tolerance 1/min : +- 15

rack travel mm : -12.85
Tolerance mm : +- 0.55

Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 247.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -8.20

Tolerance mm : +- 0.10

Rated speed rpm : 200
CRT mm max. : < -6.80
Rated speed rpm : 365

TORQUE CONTROL

Rated speed rpm : 600
Rated speed rpm : 1000
Tolerance mm : +- 0.10
Rated speed rpm : 600
rack travel mm : -4.50
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.80
Tolerance mm : +- 0.30

Rated speed rpm : 500
Pressure hPa : 240
rack travel mm : -2.60
Tolerance mm : +- 0.20

Pressure hPa : 480
rack travel mm : -0.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195
Check speed 1/min : > 80
Check speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 270.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 159.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 167.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1070
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 300

Del. quantity
cm³/1000 strokes : 31.0
Tolerance
cm³/1000 strokes : ± 2.5
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.09.95
Test oil : ISO 4113

Combination No. : 0 401 446 151

Injection pump
Pump designation : PE6R120/720RS1507
EP type number : 0 411 426 004

Governor
Governor design. : RQV300...950R5K
Governor no. : 0 421 415 005

Cust. part No. : 11032038
: -P03 V.02/95

Customer-spec. information
Customer : VME
Motor : TD164 KAE
Power KW : 503.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 078

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.45
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.75

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 875

Rack travel in mm : 14.25
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 382.0

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance
 cm3/1000S. : +- 4.0

Spreed
 Tolerance
 cm3/1000 strokes : 8.0

Check tolerance
 cm3/1000S. : 11.0

Rated speed rpm : 300

Rack travel in mm : 6.20
 Tolerance mm : +- 0.30
 Del. quantity
 cm3/1000 strokes : 38.0
 Tolerance
 cm3/1000 strokes : +- 2.5
 Check tolerance
 cm3/1000S. : +- 5.0
 Spreed
 Tolerance
 cm3/1000 strokes : 5.0
 Check tolerance
 cm3/1000S. : 8.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 2.09
 Tolerance mm : +- 0.25

Rated speed rpm : 978
 guide sleeve
 travel mm : 9.28
 Tolerance mm : +- 0.25

Rated speed rpm : 705
 guide sleeve
 travel mm : 6.07
 Tolerance mm : +- 0.25

Rated speed rpm : 316
 guide sleeve
 travel mm : 2.30
 Tolerance mm : +- 0.25

Rated speed rpm : 366
 guide sleeve
 travel mm : 2.90
 Tolerance mm : +- 0.25

Rated speed rpm : 450
 guide sleeve
 travel mm : 3.68
 Tolerance mm : +- 0.25

Rated speed rpm : 1240
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1100
 Rack travel in mm : 8.50
 Tolerance mm : +- 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 875
 Aneroid pressure
 hPa : 1500
 Del. quantity
 cm3/1000 strokes : 382.0
 Tolerance
 cm3/1000 strokes : +- 1.0
 Check tolerance
 cm3/1000S. : +- 4.0
 Spreed
 Tolerance
 cm3/1000 strokes : 8.0
 Check tolerance
 cm3/1000S. : 11.0

CONTROL LEVER

control lever
 position degree : 63.0
 tolerance degree : +- 4.0

control lever
 position degree : 118.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.25
 Rated speed rpm : 965
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1080
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50

Rated speed rpm : 1150

LOW IDLE

control lever
position degree : 78.0
tolerance degree : +- 4.0

control lever
position degree : 23.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 6.20
Tolerance mm : +- 0.30

Rated speed rpm : 200

CRT mm min. : > 8.40

Rated speed rpm : 390

TORQUE CONTROL

Rated speed rpm : 875
rack travel mm : 14.25
Tolerance mm : +- 0.05

Rated speed rpm : 550
rack travel mm : 13.20
Tolerance mm : +- 0.10

Rated speed rpm : 950
rack travel mm : 13.95
Tolerance mm : +- 0.15

Rated speed rpm : 350
rack travel mm : 12.00
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 875
Pressure hPa : 1500
rack travel mm : 14.25
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 875
rack travel mm : 10.20
Tolerance mm : +- 0.10

Rated speed rpm : 875

Pressure hPa : 480
rack travel mm : 2.00
Tolerance mm : +- 0.20

Pressure hPa : 200
rack travel mm : 0.25
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 399.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

Aneroid pressure
hPa : -
Rated speed rpm : 550
Del. quantity
cm³/1000 strokes : 256.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 13.25
Rated speed rpm : 965
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 10.10
Tolerance mm : +- 0.50

Del. quantity
cm³/1000 strokes : 220.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 38.0
Tolerance
cm³/1000 strokes : +- 2.5
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 06.09.95
Test oil : ISO 4113
Combination No. : 0 402 046 789

Injection pump
Pump designation : PES6P120A32ORS3139
EP type number : 0 412 026 718

Governor
Governor design. : RQV275...1000PA728
: -3
Governor no. : 0 421 813 657

Cust. part No. : CCEP 5070 -116

Customer-spec. information

Customer : RVI
Motor : MIDR 062045 H
Power KW : 227.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Test nozzle holde
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 11.15
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 197.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed
 Tolerance
 cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -5.30
 Tolerance mm : +- 0.15
 Del. quantity
 cm³/1000 strokes : 27.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 5.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1170
 Rack travel in mm : 16.50
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1000
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm³/1000 strokes : 197.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 119.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1080
 Tolerance 1/min : +- 5
 rack travel mm : -7.15
 Rated speed rpm : 1195
 Tolerance 1/min : +- 15
 rack travel mm : -10.65
 Tolerance mm : +- 0.50
 Rated speed rpm : 1300

LOW IDLE

control lever
 position degree : 67.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
 rack travel mm : -5.30
 Tolerance mm : +- 0.15
 Rated speed rpm : 200
 CRT mm max. : < -3.80
 Rated speed rpm : 370

TORQUE CONTROL

Rated speed rpm : 600

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
 Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
 Rated speed rpm : 500
 rack travel mm : -2.20

Tolerance mm : \pm 0.20
Rated speed rpm : 500
Pressure hPa : 160
rack travel mm : -1.70
Tolerance mm : \pm 0.10
Pressure hPa : 280
rack travel mm : -0.75
Tolerance mm : \pm 0.05

START CUT-OUT

Rated speed rpm : $>$ 100
Rated speed rpm : $<$ 195
Check speed 1/min : $>$ 80
Check speed 1/min : $<$ 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1000
Rated speed rpm : 600
Del. quantity cm³/1000 strokes : 197.0
Tolerance cm³/1000 strokes : \pm 3.0
Check tolerance cm³/1000S. : \pm 6.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm³/1000 strokes : 104.0
Tolerance cm³/1000 strokes : \pm 1.0
Check tolerance cm³/1000S. : \pm 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1080
Tolerance 1/min : \pm 5

STARTING FUEL DELIVERY

Rated speed rpm : 100

Del. quantity cm³/1000 strokes : 145.0
Tolerance cm³/1000 strokes : \pm 10.0
Check tolerance cm³/1000S. : \pm 14.0

LOW IDLE

Rated speed rpm : 275
Del. quantity cm³/1000 strokes : 27.0
Tolerance cm³/1000 strokes : \pm 2.0
Check tolerance cm³/1000S. : \pm 5.0
Speed Tolerance cm³/1000 strokes : 8.0
Check tolerance cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 27.09.95
Test oil : ISO 4113
Combination No. : 0 402 746 603
Injection pump
Pump designation : PES6P120A320RS7359
EP type number : 0 412 726 925
Governor
Governor design. : RQ275/1050PA999-7
Governor no. : 0 421 801 799
Cust. part No. : CCEP 5153 66-224

Customer-spec. information
Customer : RVI
Motor : MIHR062045 A41
Power KW : 185.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 078
Inlet press. bar : 2.5
Tolerance bar : ± 0.1
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.70
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 20.25
Tolerance mm : ± 0.75
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 600
Rack travel in mm : 12.70
Tolerance mm : ± 0.05
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 191.0
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -5.70
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 34.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.75
Tolerance mm : +- 0.20

Rated speed rpm : 1145
guide sleeve
travel mm : 6.55
Tolerance mm : +- 0.15

Rated speed rpm : 1050
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 594
guide sleeve
travel mm : 5.11
Tolerance mm : +- 0.10

Rated speed rpm : 720
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 1380

guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 191.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 274.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1138
Tolerance 1/min : +- 5

rack travel mm : -8.70
Rated speed rpm : 1265
Tolerance 1/min : +- 15

rack travel mm : -12.20
Tolerance mm : +- 0.50
Rated speed rpm : 1375

LOW IDLE

control lever
position degree : 255.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -5.70
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 585
Tolerance 1/min : +- 20

Rated speed rpm : 175
CRT mm min. : > -3.80

TORQUE CONTROL

Rated speed rpm : 600
Tolerance mm : +- 0.05

Rated speed rpm : 1050
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -1.10
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 140
rack travel mm : -0.66
Tolerance mm : +- 0.15

Pressure hPa : 200
rack travel mm : -0.25
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

Check
speed 1/min : > 80

Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 198.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 156.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1138
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 34.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spread

Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 09.10.95
Test oil : ISO 4113
Combination No. : 0 403 548 033AC
Injection pump
Pump designation : PE8MW100/720LS1173
EP type number : 0 413 508 108
Governor
Governor design. : RQV450...1150MW70-1
Governor no. : 0 420 083 179

Cust. part No. :

Customer-spec. information
Customer : KHD
Motor : F8L513
Power KW : 202.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

E02

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0

Prestroke mm : 3.15
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 8- 7- 2- 6
 : - 5- 4- 3

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1125

Rack travel in mm : 13.00
Tolerance mm : +- 0.05

Del. quantity cm3/1000 strokes : 130.0

Tolerance cm3/1000 strokes : +- 1.0

Check tolerance cm3/1000S. : +- 4.0

Speed
Tolerance cm3/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.0

Rated speed rpm : 450

Rack travel in mm : 5.00

Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 13.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spread
Tolerance

cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1150

Rack travel in mm : 16.50

Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1125

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 130.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance

cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.0

CONTROL LEVER

control lever
position degree : 125.0

tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.00
Rated speed rpm : 1160
Tolerance 1/min : +- 5

rack travel mm : 3.50
Rated speed rpm : 1215
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1320

LOW IDLE

control lever
position degree : 84.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 450
rack travel mm : 5.00
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.50

TORQUE CONTROL

Rated speed rpm : 1125
rack travel mm : 13.00
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 370

Check
speed 1/min : > 80
Check
speed 1/min : < 390

BREAKAWAY

Rack travel in mm : 12.00
Rated speed rpm : 1160

Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.11.95
Test oil : ISO 4113
Combination No. : 0 402 048 705
Injection pump
Pump designation : PES8P120A320RS3199
EP type number : 0 412 028 705
Governor
Governor design. : RQV275...1050PA665
Governor no. : 0 421 813 370

Cust. part No. :

Customer-spec. information
Customer : RVI
Motor : MIVR083530
Power KW : 320.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder assembly : 1 688 901 019
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

E05

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.55
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 8- 4- 2- 7
 : - 3- 6- 5

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark

°NW after s.o.d. : 13.00
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050
Rack travel in mm : 11.45
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 203.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -7.50
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 20.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 0.89
Tolerance mm : +- 0.20

Rated speed rpm : 1135
guide sleeve
travel mm : 8.32
Tolerance mm : +- 0.15

Rated speed rpm : 781
guide sleeve
travel mm : 5.68
Tolerance mm : +- 0.25

Rated speed rpm : 480
guide sleeve
travel mm : 3.60
Tolerance mm : +- 0.25

Rated speed rpm : 1430

guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1250

Rack travel in mm : 10.45
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure

hPa : 700

Del. quantity
cm³/1000 strokes : 203.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 300.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1120
Tolerance 1/min : +- 5

rack travel mm : -7.45
Rated speed rpm : 1225
Tolerance 1/min : +- 15

rack travel mm : -10.95
Tolerance mm : +- 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 245.0
tolerance degree : ± 4.0

control lever
position degree : 10.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.50
Tolerance mm : ± 0.10

Rated speed rpm : 200

CRT mm max. : < -5.80

Rated speed rpm : 343

TORQUE CONTROL

Rated speed rpm : 1050

Rated speed rpm : 650

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -2.60
Tolerance mm : ± 0.10

Rated speed rpm : 500

Pressure hPa : 360
rack travel mm : -1.90
Tolerance mm : ± 0.10

Pressure hPa : 420
rack travel mm : -0.75
Tolerance mm : ± 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

E07

Check
speed 1/min : > 80
Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 700
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 192.0
Tolerance
cm³/1000 strokes : ± 4.0
Check tolerance
cm³/1000S. : ± 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 111.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1120
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 175.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000S. : ± 6.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.01.96
Test oil : ISO 4113
Combination No. : 0 402 046 300
Injection pump
Pump designation : PES6P120A320PS419
EP type number : 0 412 026 037
Governor
Governor design. : RQV275...1100PA495
 : -5
Governor no. : 0 421 813 446
Cust. part No. : CCEP 5023 E 06-09

Customer-spec. information

Customer : RVI
Motor : MIDR 062045
Power KW : 191.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 019
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

E09

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 2.85
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
 : 4
Phasing : 0-60-120-180-240
 : -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50
Start of delivery mark
°NW after s.o.d. : 10.50
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100
Rack travel in mm : 9.05
Tolerance mm : +- 0.05
Del. quantity
cm³/1000 strokes : 163.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -4.10
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 24.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 250
guide sleeve
travel mm : 1.10
Tolerance mm : +- 0.10

Rated speed rpm : 1100
guide sleeve
travel mm : 8.10
Tolerance mm : +- 0.10

Rated speed rpm : 450
guide sleeve
travel mm : 3.60
Tolerance mm : +- 0.20

Rated speed rpm : 850
guide sleeve
travel mm : 6.20
Tolerance mm : +- 0.10

GUIDE SLEEVE POSITION

E10

Rated speed rpm : 1150

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure

hPa : 700
Del. quantity

cm³/1000 strokes : 163.0
Tolerance

cm³/1000 strokes : +- 1.0
Check tolerance

cm³/1000S. : +- 4.0
Speed

Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 64.0
tolerance degree : +- 4.0

control lever
position degree : 124.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1175
Tolerance 1/min : +- 5

rack travel mm : -5.00
Rated speed rpm : 1240
Tolerance 1/min : +- 15

rack travel mm : -8.55
Tolerance mm : +- 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 68.0
tolerance degree : +- 4.0

control lever
position degree : 9.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -4.10
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm max. : < -2.40

Rated speed rpm : 343

TORQUE CONTROL

Rated speed rpm : 1100

Rated speed rpm : 700

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -1.10
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 195
rack travel mm : -0.80
Tolerance mm : +- 0.10

Pressure hPa : 220
rack travel mm : -0.35
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

Check
speed 1/min : > 80

Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 700
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 103.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1175
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 24.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Speed

Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 15.01.96
Test oil : ISO 4113

Combination No. : 0 402 046 824

Injection pump
Pump designation : PES6P120A32ORS3279
: -1
EP type number : 0 412 026 758

Governor
Governor design. : RQ275/1050PA999-5
Governor no. : 0 421 801 663

Cust. part No. : CCEP-5112B 66-175

Customer-spec. information

Customer : RVI
Motor : MIHR 062045 A/3
Power KW : 186.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 078

Inlet press. bar : 2.5
Tolerance bar : +- 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test Lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark
Barrel no. : 1

Beginning of delivery difference
and maximum rack
travel : 10.50
Tolerance mm : +- 0.50

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 11.25
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 158.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -4.50
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 2.35
Tolerance mm : +- 0.10

Rated speed rpm : 1126
guide sleeve
travel mm : 6.38
Tolerance mm : +- 0.10

Rated speed rpm : 1050
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 582
guide sleeve
travel mm : 5.14
Tolerance mm : +- 0.10

Rated speed rpm : 710
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 1380
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 750

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 158.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 274.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1138
Tolerance 1/min : +- 8

rack travel mm : -7.20
Rated speed rpm : 1245
Tolerance 1/min : +- 15

rack travel mm : -10.75
Tolerance mm : +- 0.55
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 253.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -4.50
Tolerance mm : +- 0.10

rack travel mm : -9.25
Rated speed rpm : 580
Tolerance 1/min : +- 20

Rated speed rpm : 200

CRT mm max. : < -3.00

TORQUE CONTROL

Rated speed rpm : 700

Rated speed rpm : 1050
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -1.20
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 220
rack travel mm : -0.45
Tolerance mm : +- 0.15

Pressure hPa : 160
rack travel mm : -0.85
Tolerance mm : +- 0.05

START CUT-OUT

E15

Rated speed rpm : > 100
Rated speed rpm : < 195

Check
speed 1/min : > 80
Check
speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 154.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 114.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1138
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.01.96
Test oil : ISO 4113
Combination No. : 0 401 496 001
Injection pump
Pump designation : PE6R120/720RS1502
EP type number : 0 411 426 002
Governor
Governor design. : RE31
Governor no. : 0 421 890 200

Cust. part No. : 1556156
: -P07 v. 12/95

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD 163 ES,EJ
Power KW : 370.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 078

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values in Section (B) must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0

Prestroke mm : 5.40
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Start of delivery mark

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(ALL P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60

Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 950
Uact V : 2.750
Del. quantity
cm³/1000 strokes : 295.0
Tolerance
cm³/1000 strokes : +/- 3.0
Check tolerance
cm³/1000S. : +/- 6.0
Spreed
Tolerance
cm³/1000 strokes : 9.0
Check tolerance
cm³/1000S. : 13.0

Rated speed rpm : 950
Uact V : 2.000
Del. quantity
cm³/1000 strokes : 163.0
Tolerance
cm³/1000 strokes : +/- 3.0
Check tolerance
cm³/1000S. : +/- 6.0

TEST POINT L1

Rated speed rpm : 300
Uact V : 1.530
Tolerance Volt : +/- 0.060
Check tolerance
Volt : +/- 0.060
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +/- 3.0
Spreed
Tolerance
cm³/1000 strokes : 7.0
Check tolerance
cm³/1000S. : 11.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.01.96
Test oil : ISO 4113

Combination No. : 0 403 546 023

Injection pump
Pump designation : PE6MW100/720RS1229
EP type number : 0 413 506 108

Governor
Governor design. : RQ250/1250MW158
Governor no. : 0 420 082 076

Cust. part No. :

Customer-spec. information
Customer : SNF
Motor : WD 612.95
Power KW : 191.0

TEST BENCH REQUIREMENTS

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 457 413 010

Inlet press. bar : 1.5

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

E20

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0

Prestroke mm : 3.65
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 14.45
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 146.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Speed
Tolerance
cm3/1000 strokes : 4.0

Check tolerance
cm3/1000S. : 7.5

Rated speed rpm : 250

Rack travel in mm : 9.20

Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spreed
Tolerance

cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 250

guide sleeve
travel mm : 1.43

Tolerance mm : +- 0.20

Rated speed rpm : 1299

guide sleeve
travel mm : 6.50

Tolerance mm : +- 0.15

Rated speed rpm : 1250

guide sleeve
travel mm : 6.00

Tolerance mm : +- 0.10

Rated speed rpm : 420

guide sleeve
travel mm : 5.00

Tolerance mm : +- 0.10

Rated speed rpm : 500

guide sleeve
travel mm : 6.00

Tolerance mm : +- 0.10

Rated speed rpm : 1480

guide sleeve
travel mm : 11.50

Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00

Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 146.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance

cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 99.0

tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.50

Rated speed rpm : 1295

Tolerance 1/min : +- 5

rack travel mm : 4.00

Rated speed rpm : 1390

Tolerance 1/min : +- 15

rack travel mm : 0.50

Tolerance mm : +- 0.50

Rated speed rpm : 1500

control lever
position degree : 76.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250

rack travel mm : 9.20

Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 10.00

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 14.45
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 14.45
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 14.45
Tolerance mm : +- 0.10

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 12.00
Tolerance mm : +- 0.05

Rated speed rpm : 500

Pressure hPa : 800
rack travel mm : 13.65
Tolerance mm : +- 0.15

Pressure hPa : 600
rack travel mm : 12.35
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 80
Rated speed rpm : < 180

Check speed 1/min : > 100
Check speed 1/min : < 200

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 700

Del. quantity
cm³/1000 strokes : 157.0
Tolerance

cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500

Del. quantity
cm³/1000 strokes : 102.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 13.50
Rated speed rpm : 1295
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 09.02.96
Test oil : ISO 4113
Combination No. : 0 402 746 994
Injection pump
Pump designation : PES6P120A32ORS7344
EP type number : 0 412 726 914
Governor
Governor design. : RQV275...1000PA1161
Governor no. : 0 421 814 100
Cust. part No. : CCEP 5143A 66-231

Customer-spec. information
Customer : RVI
Motor : MIDR 062045 E/41
Power KW : 249.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 071
Inlet press. bar : 2.5
Test nozzle holder assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

E24

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 4.50
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 11.00
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50
Start of delivery mark
°NW after s.o.d. : -0.15
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 600
Rack travel in mm : 12.60
Tolerance mm : ± 0.05
Del. quantity cm³/1000 strokes : 282.0

Tolerance	
cm ³ /1000 strokes	: +- 1.0

Check tolerance	
cm ³ /1000S.	: +- 4.0

Spreed	
Tolerance	
cm ³ /1000 strokes	: 5.0

Check tolerance	
cm ³ /1000S.	: 9.0

Rated speed rpm	: 300

Del. quantity	
cm ³ /1000 strokes	: 32.0
Tolerance	
cm ³ /1000 strokes	: +- 2.0
Check tolerance	
cm ³ /1000S.	: +- 5.0
Spreed	
Tolerance	
cm ³ /1000 strokes	: 8.0
Check tolerance	
cm ³ /1000S.	: 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm	: 300
guide sleeve	
travel mm	: 1.66
Tolerance mm	: +- 0.25

Rated speed rpm	: 1086
guide sleeve	
travel mm	: 8.09
Tolerance mm	: +- 0.25

Rated speed rpm	: 793
guide sleeve	
travel mm	: 6.00
Tolerance mm	: +- 0.25

Rated speed rpm	: 343
guide sleeve	
travel mm	: 2.33
Tolerance mm	: +- 0.25

Rated speed rpm	: 393
guide sleeve	
travel mm	: 2.95
Tolerance mm	: +- 0.25

Rated speed rpm	: 500
guide sleeve	
travel mm	: 3.72
Tolerance mm	: +- 0.25

Rated speed rpm	: 1410
guide sleeve	
travel mm	: 11.50
Tolerance mm	: +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm	: 1235

Rack travel in mm	: 11.70
Tolerance mm	: +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm	: 600
Aneroid pressure	
hPa	: 1000
Del. quantity	
cm ³ /1000 strokes	: 282.0
Tolerance	
cm ³ /1000 strokes	: +- 1.0
Check tolerance	
cm ³ /1000S.	: +- 4.0
Spreed	
Tolerance	
cm ³ /1000 strokes	: 5.0
Check tolerance	
cm ³ /1000S.	: 9.0

CONTROL LEVER

control lever	
position degree	: 120.0
tolerance degree	: +- 4.0

RATED SPEED

rack travel mm	: -1.00
Rated speed rpm	: 1080
Tolerance 1/min	: +- 5

rack travel mm	: -8.60
Rated speed rpm	: 1215
Tolerance 1/min	: +- 15

rack travel mm	: -12.10
Tolerance mm	: +- 0.50
Rated speed rpm	: 1300

LOW IDLE

control lever
position degree : 65.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 200
CRT mm max. : < -5.50
Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 600
Rated speed rpm : 1000
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.40
Tolerance mm : +- 0.30

Rated speed rpm : 500

Pressure hPa : 320
rack travel mm : -2.65
Tolerance mm : +- 0.15

Pressure hPa : 640
rack travel mm : -0.70
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 225

Check
speed 1/min : > 80

E26

Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 283.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 122.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1080
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 32.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.02.96
Test oil : ISO 4113
Combination No. : 0 403 446 317
Injection pump
Pump designation : PES6MW100/320RS1214
: -1
EP type number : 0 413 406 224
Governor
Governor design. : RQV275...1250MW115K
Governor no. : 0 420 083 994
Cust. part No. :

Customer-spec. information

Customer : RVI
Motor : MIDR 060226 W
Power KW : 151.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 033
Inlet press. bar : 2.5
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0
Prestroke mm : 4.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 18.00
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Start of delivery blocking
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250
Rack travel in mm : 14.15
Tolerance mm : ± 0.05
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 117.0
Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm3/1000S. : +- 3.0

Spread
Tolerance
cm3/1000 strokes : 3.5

Check tolerance
cm3/1000S. : 6.0

Rated speed rpm : 275

Rack travel in mm : -8.10
Tolerance mm : +- 0.10

Del. quantity
cm3/1000 strokes : 21.0

Tolerance
cm3/1000 strokes : +- 2.0

Check tolerance
cm3/1000S. : +- 4.5

Spread
Tolerance

cm3/1000 strokes : 3.5

Check tolerance
cm3/1000S. : 5.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.00
Tolerance mm : +- 0.25

Rated speed rpm : 1344
guide sleeve
travel mm : 9.99
Tolerance mm : +- 0.25

Rated speed rpm : 924
guide sleeve
travel mm : 6.77
Tolerance mm : +- 0.25

Rated speed rpm : 390
guide sleeve
travel mm : 2.39
Tolerance mm : +- 0.25

Rated speed rpm : 440
guide sleeve
travel mm : 3.01
Tolerance mm : +- 0.25

Rated speed rpm : 550

guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.25

Rated speed rpm : 1650
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1360

Rack travel in mm : 10.00
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure

hPa : 1000

Del. quantity
cm3/1000 strokes : 117.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 3.0

Spread
Tolerance

cm3/1000 strokes : 3.5

Check tolerance
cm3/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 293.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1310
Tolerance 1/min : +- 15

rack travel mm : -10.10
Rated speed rpm : 1470
Tolerance 1/min : +- 5

rack travel mm : -13.60
Tolerance mm : +- 0.50
Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 244.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -8.10
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : > -7.50

TORQUE CONTROL

Rated speed rpm : 1250
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : -0.80
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : -5.50
Tolerance mm : +- 0.10

Rated speed rpm : 350
rack travel mm : -1.60
Tolerance mm : +- 0.40

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1000
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : -3.00
Tolerance mm : +- 0.20

Rated speed rpm : 1250

Pressure hPa : 200
rack travel mm : -2.35
Tolerance mm : +- 0.15

Pressure hPa : 300
rack travel mm : -1.75

F02

Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 200
Rated speed rpm : < 230

Check
speed 1/min : > 170
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 116.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 4.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 60.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 7.5

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 78.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1310
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 95.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 21.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.02.96
 Test oil : ISO 4113
 Combination No. : 0 403 446 318
 Injection pump
 Pump designation : PES6MW100/320RS1214
 : -1
 EP type number : 0 413 406 224
 Governor
 Governor design. : RQV275...1250MW115
 : -1K
 Governor no. : 0 420 083 992
 Cust. part No. :

Customer-spec. information
 Customer : RVI
 Motor : MIDR 060226 V
 Power kW : 129.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
 Test oil inlet
 temp. °C : 40
 Tolerance °C : ± 2.0
 Overflow valve : 2 417 413 033
 Inlet press. bar : 2.5
 Test nozzle holde
 assembly : 1 688 901 101
 Opening pressure
 bar : 208.5
 Tolerance bar : ± 1.5
 Test lines : 1 680 750 008

Outside diameter : 6.0
 x inside diameter : 2.0
 x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
 Tolerance bar : ± 1.0
 Prestroke mm : 4.25
 Tolerance mm : ± 0.05
 Check
 tolerance mm : ± 0.10
 Rack travel in mm : 18.00
 Tolerance mm : ± 1.50
 Firing order : 1- 5- 3- 6- 2-
 : 4
 Phasing : 0-60-120-180-240
 : -300
 Tolerance : ± 0.50
 Check
 tolerance °NW : ± 0.75
 Start of delivery blocking
 Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250
 Rack travel in mm : 13.15
 Tolerance mm : ± 0.05
 Tolerance mm : ± 0.05
 Del. quantity
 cm³/1000 strokes : 112.0
 Tolerance
 cm³/1000 strokes : ± 1.0

Check tolerance
 cm3/1000S. : +- 3.0

Spreed
 Tolerance
 cm3/1000 strokes : 3.5

Check tolerance
 cm3/1000S. : 6.0

Rated speed rpm : 275

Rack travel in mm : -7.50
 Tolerance mm : +- 0.10
 Del. quantity
 cm3/1000 strokes : 22.0
 Tolerance
 cm3/1000 strokes : +- 2.0
 Check tolerance
 cm3/1000S. : +- 4.5
 Spreed
 Tolerance
 cm3/1000 strokes : 3.5
 Check tolerance
 cm3/1000S. : 5.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
 guide sleeve
 travel mm : 1.00
 Tolerance mm : +- 0.25

Rated speed rpm : 1314
 guide sleeve
 travel mm : 9.71
 Tolerance mm : +- 0.25

Rated speed rpm : 912
 guide sleeve
 travel mm : 6.70
 Tolerance mm : +- 0.25

Rated speed rpm : 390
 guide sleeve
 travel mm : 2.39
 Tolerance mm : +- 0.25

Rated speed rpm : 440
 guide sleeve
 travel mm : 2.90
 Tolerance mm : +- 0.25

Rated speed rpm : 560

guide sleeve
 travel mm : 4.01
 Tolerance mm : +- 0.25

Rated speed rpm : 1650
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1460
 Rack travel in mm : 10.00
 Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm3/1000 strokes : 112.0
 Tolerance
 cm3/1000 strokes : +- 1.0
 Check tolerance
 cm3/1000S. : +- 3.0
 Spreed
 Tolerance
 cm3/1000 strokes : 3.5
 Check tolerance
 cm3/1000S. : 6.0

CONTROL LEVER

control lever
 position degree : 292.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1300
 Tolerance 1/min : +- 15

rack travel mm : -9.10
 Rated speed rpm : 1455
 Tolerance 1/min : +- 5

rack travel mm : -12.60
 Tolerance mm : +- 0.50
 Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 242.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.50
Tolerance mm : ± 0.10

Rated speed rpm : 200

CRT mm min. : < -6.90

TORQUE CONTROL

Rated speed rpm : 1250
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : -0.90
Tolerance mm : ± 0.05

Rated speed rpm : 700
rack travel mm : -4.50
Tolerance mm : ± 0.10

Rated speed rpm : 350
rack travel mm : -1.60
Tolerance mm : ± 0.40

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1000
Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : -2.00
Tolerance mm : ± 0.20

Rated speed rpm : 1250

Pressure hPa : 120
rack travel mm : -1.50
Tolerance mm : ± 0.15

Pressure hPa : 240
rack travel mm : -0.50

F06

Tolerance mm : ± 0.05

START CUT-OUT

Rated speed rpm : > 200
Rated speed rpm : < 230

Check
speed 1/min : > 170
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 112.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 64.0
Tolerance
cm³/1000 strokes : ± 4.0
Check tolerance
cm³/1000S. : ± 7.5

Aneroid pressure
hPa : -
Rated speed rpm : 1250
Del. quantity
cm³/1000 strokes : 89.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1300
Tolerance 1/min : ± 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 95.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.02.96
Test oil : ISO 4113
Combination No. : 0 403 446 319
Injection pump
Pump designation : PES6MW100/320RS1216
: -1
EP type number : 0 413 406 223
Governor
Governor design. : RQV275...1250MW124K
Governor no. : 0 420 083 989

Cust. part No. :

Customer-spec. information

Customer : RVI
Motor : MIDR D60226 U
Power KW : 110.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 033
Inlet press. bar : 2.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

F08

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : ± 1.0

Prestroke mm : 4.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 13.00
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 13.25
Tolerance mm : ± 0.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 106.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Speed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 275

Rack travel in mm : -7.20
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 21.0

Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5

Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.00
Tolerance mm : ± 0.25

Rated speed rpm : 1344
guide sleeve
travel mm : 9.99
Tolerance mm : ± 0.25

Rated speed rpm : 924
guide sleeve
travel mm : 6.77
Tolerance mm : ± 0.25

Rated speed rpm : 390
guide sleeve
travel mm : 2.39
Tolerance mm : ± 0.25

Rated speed rpm : 440
guide sleeve
travel mm : 3.01
Tolerance mm : ± 0.25

Rated speed rpm : 550

guide sleeve
travel mm : 3.92
Tolerance mm : ± 0.25

Rated speed rpm : 1650
guide sleeve
travel mm : 13.50
Tolerance mm : ± 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1460

Rack travel in mm : 10.00
Tolerance mm : ± 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 106.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 3.0

Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 292.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1305
Tolerance 1/min : ± 15

rack travel mm : -9.25
Rated speed rpm : 1460
Tolerance 1/min : ± 5

rack travel mm : -12.70
Tolerance mm : ± 0.50
Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 245.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.20
Tolerance mm : +- 0.20

Rated speed rpm : 200

CRT mm min. : > -6.60

TORQUE CONTROL

Rated speed rpm : 1250
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : -1.35
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : -4.50
Tolerance mm : +- 0.10

Rated speed rpm : 350
rack travel mm : -2.40
Tolerance mm : +- 0.40

START CUT-OUT

Rated speed rpm : > 150
Rated speed rpm : < 230

Check
speed 1/min : > 130
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm3/1000 strokes : 95.0
Tolerance
cm3/1000 strokes : +- 1.5
Check tolerance
cm3/1000S. : +- 4.0
Speed

Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm3/1000 strokes : 57.0
Tolerance
cm3/1000 strokes : +- 4.0
Check tolerance
cm3/1000S. : +- 7.5

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1305
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm3/1000 strokes : 95.0
Tolerance
cm3/1000 strokes : +- 10.0
Check tolerance
cm3/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm3/1000 strokes : 21.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Speed
Tolerance
cm3/1000 strokes : 3.5
Check tolerance
cm3/1000S. : 5.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 15.02.96
Test oil : ISO 4113

Combination No. : 0 402 046 870

Injection pump
Pump designation : PES6P120A320RS3303
: -1
EP type number : 0 412 026 782

Governor
Governer design. : RQV275...1050PA1038
: -1K
Governer no. : 0 421 815 478

Cust. part No. : CCEP-5129D 66-195

Customer-spec. information

Customer : RVI
Motor : MIDR 062045 J/3
Power KW : 168.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5
Tolerance bar : +- 0.1

Overflow quantity
min. l/h : 115
Tolerance l/h : +- 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5

F11

Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 3.60
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark

°NW after s.o.d. : -0.18
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 10.30
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 159.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -5.30
Tolerance mm : +- 0.20

Del. quantity
cm³/1000 strokes : 30.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.29
Tolerance mm : +- 0.20

Rated speed rpm : 1143
guide sleeve
travel mm : 9.05
Tolerance mm : +- 0.15

Rated speed rpm : 742
guide sleeve
travel mm : 6.16
Tolerance mm : +- 0.25

Rated speed rpm : 337

guide sleeve
travel mm : 2.38
Tolerance mm : +- 0.25

Rated speed rpm : 387
guide sleeve
travel mm : 3.12
Tolerance mm : +- 0.25

Rated speed rpm : 440
guide sleeve
travel mm : 3.94
Tolerance mm : +- 0.25

Rated speed rpm : 1530
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1350

Rack travel in mm : 9.30
Tolerance mm : +- 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 159.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 59.0
tolerance degree : +- 4.0

control lever
position degree : 294.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00

Rated speed rpm : 1110
Tolerance 1/min : + 5

rack travel mm : -6.30
Rated speed rpm : 1220
Tolerance 1/min : +- 15

rack travel mm : -10.50
Tolerance mm : + 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 74.0
tolerance degree : +- 4.0

control lever
position degree : 19.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -5.30
Tolerance mm : +- 0.20

Rated speed rpm : 200

CRT mm max. : < -4.10

Rated speed rpm : 330

TORQUE CONTROL

Rated speed rpm : 1050

Rated speed rpm : 700
rack travel mm : -1.00
Tolerance mm : +- 0.10

Rated speed rpm : 350
rack travel mm : -1.50
Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 165
Rated speed rpm : < 235

Check
speed 1/min : > 145
Check
speed 1/min : < 245

F13

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 151.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1110
Tolerance 1/min : + 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 135.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.02.96
Test oil : ISO 4113
Combination No. : 0 402 046 877
Injection pump
Pump designation : PES6P120A320RS3337
: -1
EP type number : 0 412 026 772
Governor
Governor design. : RQV300...1250PA1149
: -2K
Governor no. : 0 421 815 504
Cust. part No. : CCEP 5158 66-218

Customer-spec. information
Customer : RVI
Motor : MIDR 06-02-26 V4
Power KW : 133.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 084
Inlet press. bar : 2.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 4.15
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 13.00
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50
Start of delivery mark
°NW after s.o.d. : -0.35
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 12.60
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 150.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : -8.30
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.31
Tolerance mm : +- 0.20

Rated speed rpm : 1311
guide sleeve
travel mm : 9.80
Tolerance mm : +- 0.15

Rated speed rpm : 868
guide sleeve
travel mm : 5.97
Tolerance mm : +- 0.25

Rated speed rpm : 510
guide sleeve
travel mm : 3.59
Tolerance mm : +- 0.25

Rated speed rpm : 1600
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1400
Rack travel in mm : 11.60
Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 150.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 293.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1296
Tolerance 1/min : +- 5

rack travel mm : -8.60
Rated speed rpm : 1425
Tolerance 1/min : +- 15

rack travel mm : -12.10
Tolerance mm : +- 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 241.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -8.30
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : < 7.30

Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 1250

Rated speed rpm : 850
rack travel mm : -1.75
Tolerance mm : +- 0.15

Rated speed rpm : 350
rack travel mm : -2.20
Tolerance mm : +- 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : -2.00
Tolerance mm : +- 0.20

Rated speed rpm : 1250

Pressure hPa : 280
rack travel mm : -1.20
Tolerance mm : +- 0.10

Pressure hPa : 360
rack travel mm : -0.60
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 165
Rated speed rpm : < 225

Check
speed 1/min : > 145
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 850
Del. quantity
cm³/1000 strokes : 126.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 124.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1296
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 108.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 15.02.96
Test oil : ISO 4113
Combination No. : 0 402 946 010
Injection pump
Pump designation : PES6P120A32ORS8028
EP type number : 0 412 926 021
Governor
Governor design. : RQV275...1175PA1101K
Governor no. : 0 421 815 982

Cust. part No. : CCEP 5133 A 66-193

Customer-spec. information
Customer : RVI
Motor : MIDR 060226 M51
Power KW : 158.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 078
Inlet press. bar : 2.5
Tolerance bar : +- 0.1
Test nozzle holder assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 5.00
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 13.00
Tolerance mm : +- 0.50
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark

°NW after s.o.d. : -0.15
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery difference

betw. rack trav. mm : 21.00
and maximum rack travel : 12.30
Difference °CS : 2.00

BASIC SETTING

Rated speed rpm : 1175

Rack travel in mm : 13.70
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 268.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 5.0

Check tolerance
cm3/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -7.30
Tolerance mm : +- 0.10
Del. quantity
cm3/1000 strokes : 42.0
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 6.0
Spreed
Tolerance
cm3/1000 strokes : 8.0
Check tolerance
cm3/1000S. : 12.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 1.01
Tolerance mm : +- 0.10

Rated speed rpm : 1230
guide sleeve
travel mm : 8.95
Tolerance mm : +- 0.10

Rated speed rpm : 877
guide sleeve
travel mm : 6.51
Tolerance mm : +- 0.20

Rated speed rpm : 389
guide sleeve
travel mm : 2.39
Tolerance mm : +- 0.20

Rated speed rpm : 439
guide sleeve
travel mm : 3.01
Tolerance mm : +- 0.20

Rated speed rpm : 550
guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.20

Rated speed rpm : 1650
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1430
Rack travel in mm : 11.20
Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1175
Aneroid pressure
hPa : 1600
Del. quantity
cm3/1000 strokes : 268.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 295.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1250
Tolerance 1/min : +- 15

rack travel mm : -9.70
Rated speed rpm : 1430
Tolerance 1/min : + 5

rack travel mm : -13.20
Tolerance mm : + 0.55
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 245.0
tolerance degree : + 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.30
Tolerance mm : + 0.10

Rated speed rpm : 200
CRT mm max. : < -6.40
Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 1175
Rated speed rpm : 650
rack travel mm : -1.55
Tolerance mm : + 0.10
Rated speed rpm : 350
rack travel mm : -2.80
Tolerance mm : + 0.25

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 1175
Pressure hPa : 1600

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -5.40
Tolerance mm : + 0.20

Rated speed rpm : 1175
Pressure hPa : 320
rack travel mm : -4.70
Tolerance mm : + 0.20

Pressure hPa : 560
rack travel mm : -2.95
Tolerance mm : + 0.05

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 240
Check
speed 1/min : > 155
Check
speed 1/min : < 260

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1600
Rated speed rpm : 650
Del. quantity
cm³/1000 strokes : 260.0
Tolerance
cm³/1000 strokes : + 3.0
Check tolerance
cm³/1000S. : + 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 148.0
Tolerance
cm³/1000 strokes : + 1.0
Check tolerance
cm³/1000S. : + 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1250
Tolerance 1/min : + 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 100.0

Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 42.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.02.96
Test oil : ISO 4113
Combination No. : 0 402 746 986
Injection pump
Pump designation : PES6P120A720RS7224
: -2
EP type number : 0 412 726 893
Governor
Governor design. : RQ275/1050PA1021-3
Governor no. : 0 421 801 677

Cust. part No. :

Customer-spec. information
Customer : IVECO-UNIC
Motor : 8460.41.731

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Overflow quantity
min. L/h : 140
Tolerance L/h : +- 20.0
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 5.15
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50
Start of delivery mark
Check
tolerance °NW : +- 0.40
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050
Rack travel in mm : 12.75
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 223.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : 5.00
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 223.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed

Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

RATED SPEED

rack travel mm : 11.70
Rated speed rpm : 1103
Tolerance 1/min : +- 8

rack travel mm : 4.00
Rated speed rpm : 1175
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 74.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : 5.00
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 355
Tolerance 1/min : +- 20

Rated speed rpm : 100

CRT mm min. : > 6.50

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 12.75
Tolerance mm : +- 0.05

Rated speed rpm : 550
rack travel mm : 12.80
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 12.75
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 7.65
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 290
rack travel mm : 8.90
Tolerance mm : +- 0.20

Pressure hPa : 580
rack travel mm : 11.35
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 195

Check speed 1/min : > 80
Check speed 1/min : < 215

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1200
Rated speed rpm : 550
Del. quantity cm3/1000 strokes : 270.0
Tolerance cm3/1000 strokes : +- 4.0
Check tolerance cm3/1000S. : +- 7.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm3/1000 strokes : 127.0
Tolerance cm3/1000 strokes : +- 1.0
Check tolerance cm3/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.70
Rated speed rpm : 1103
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity cm3/1000 strokes : 135.0
Tolerance cm3/1000 strokes : +- 15.0
Check tolerance cm3/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity cm3/1000 strokes : 23.0
Tolerance cm3/1000 strokes : +- 3.0
Check tolerance cm3/1000S. : +- 6.0
Spreed Tolerance cm3/1000 strokes : 8.0
Check tolerance cm3/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 26.02.96
Test oil : ISO 4113
Combination No. : 0 403 446 316
Injection pump
Pump designation : PES6MW100/320RS1216
: -1
EP type number : 0 413 406 223
Governor
Governor design. : RQV350...1175MW113
: -2
Governor no. : 0 420 083 248
Cust. part No. :

Customer-spec. information
Customer : RVI
Motor : MIDR 060226 X
Power KW : 166.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 033
Inlet press. bar : 2.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0
Prestroke mm : 4.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 13.00
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75
Start of delivery blocking
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1175
Rack travel in mm : 13.95
Tolerance mm : +- 0.05
Tolerance mm : +- 0.05
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spread
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 6.0

Rated speed rpm : 275

Rack travel in mm : -7.80
Tolerance mm : +- 0.20
Del. quantity
cm³/1000 strokes : 29.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spread
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 1.41
Tolerance mm : +- 0.25

Rated speed rpm : 1236
guide sleeve
travel mm : 7.00
Tolerance mm : +- 0.25

Rated speed rpm : 907
guide sleeve
travel mm : 5.35
Tolerance mm : +- 0.25

Rated speed rpm : 435
guide sleeve
travel mm : 2.49
Tolerance mm : +- 0.25

Rated speed rpm : 485
guide sleeve
travel mm : 3.01
Tolerance mm : +- 0.25

Rated speed rpm : 600

guide sleeve
travel mm : 3.65
Tolerance mm : +- 0.25

Rated speed rpm : 1790
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1440
Rack travel in mm : 10.00
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1175
Aneroid pressure
hPa : 1000
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0
Spread
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 6.0

CONTROL LEVER

control lever
position degree : 300.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1225
Tolerance 1/min : +- 15

rack travel mm : -9.90
Rated speed rpm : 1460
Tolerance 1/min : +- 5

rack travel mm : -13.50
Tolerance mm : +- 0.50
Rated speed rpm : 1600

LOW IDLE

control lever
position degree : 248.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.80
Tolerance mm : +- 0.20

Rated speed rpm : 200

CRT mm min. : > -7.00

TORQUE CONTROL

Rated speed rpm : 1175
Tolerance mm : +- 0.05

Rated speed rpm : 700
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : -5.50
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.80
Tolerance mm : +- 0.30

Rated speed rpm : 500

Pressure hPa : 240
rack travel mm : -3.00
Tolerance mm : +- 0.15

Pressure hPa : 520
rack travel mm : -0.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 260

Check
speed 1/min : > 80
Check
speed 1/min : < 280

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 131.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 58.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 7.5

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 68.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1225
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25

Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 29.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 07.03.96
Test oil : ISO 4113
Combination No. : 0 400 195 001
Injection pump
Pump designation : PES5M55C32ORS202
EP type number : 0 410 055 971
Governor
Governor design. : RE
Governor no. : 0 420 090 002

Cust. part No. :

Customer-spec. information
Customer : MB-PKW
Motor : OM 605
Power KW : 83.0

TEST BENCH REQUIREMENTS

Inlet line : 1.1;
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 469 990 351
Inlet press. bar : 1.0
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 111
Opening pressure
bar : 148.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

G01

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.75
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 17.00
Tolerance mm : ± 1.00

Firing order : 1- 2- 4- 5- 3

Phasing : 0-72-144-216-288

Start of delivery blocking

*NW after s.o.d. : 16.50
Tolerance : ± 0.20
Check
tolerance *NW : ± 0.30

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60

Amplitude V : 1.4
Tolerance V : +/- 0.6
Check tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1000
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 35.5
Tolerance
cm³/1000 strokes : +/- 0.5
Check tolerance
cm³/1000S. : +/- 1.2
Spreed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 3.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 2500
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 41.6
Check tolerance
cm³/1000S. : +/- 1.5
Spreed
Check tolerance
cm³/1000S. : 3.3

Rated speed rpm : 500
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 33.2
Check tolerance
cm³/1000S. : +/- 1.2
Spreed
Check tolerance
cm³/1000S. : 3.0

Rated speed rpm : 100
Uact V : 4.000
Del. quantity
cm³/1000 strokes : 52.2
Check tolerance
cm³/1000S. : +/- 3.5
Spreed

Check tolerance
cm³/1000S. : 5.5

TEST POINT L1

Rated speed rpm : 315
Uact V : 2.200
Del. quantity
cm³/1000 strokes : 7.6
Spreed
Tolerance
cm³/1000 strokes : 1.0
Check tolerance
cm³/1000S. : 1.8

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.

See microcard(s) W400/...

Edition : 08.03.96

Test oil : ISO 4113

Combination No. : 0 400 195 002

Injection pump

Pump designation : PES5M60C32ORS205

EP type number : 0 410 065 001

Governor

Governer design. : RE22

Governer no. : 0 420 090 002

Cust. part No. :

Customer-spec. information

Customer : MB-PKW

Motor : OM 605 D 25 LA

Power KW : 110.0

TEST BENCH REQUIREMENTS

Inlet line : 1.1;

Test oil inlet

temp. °C : 40

Tolerance °C : ± 2.0

Overflow valve : 1 469 990 351

Inlet press. bar : 1.0

Tolerance bar : ± 0.1

Test nozzle holde assembly

: 0 688 901 111

Opening pressure

bar : 148.5

Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

G04

x inside diameter : 2.0

x length mm : 600

REMARKS

Pump-specific values in Section (B) must be observed!

(A) INJECTION PUMP SETTINGS

No basic setting.

Setting of constant delivery under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0

Tolerance bar : ± 1.0

Prestroke mm : 1.55

Tolerance mm : ± 0.05

Check

tolerance mm : ± 0.10

Rack travel in mm : 17.00

Tolerance mm : ± 1.00

Firing order : 1- 2- 4- 5- 3

Phasing : 0-72-144-216-288

Start of delivery blocking

°NW after s.o.d. : 17.00

Tolerance : ± 0.20

Check

tolerance °NW : ± 0.30

Barrel no. : 1

(B) POSITIONER TESTING

Warm-up time: 3 minutes at

n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1000
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 58.0
Tolerance
cm³/1000 strokes : +/- 0.5
Check tolerance
cm³/1000S. : +/- 2.0
Spreed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 3.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 2200
Uact V : 3.250

Rated speed rpm : 500
Uact V : 3.250

TEST POINT L1

Rated speed rpm : 340
Uact V : 1.950
Del. quantity
cm³/1000 strokes : 10.5
Tolerance
cm³/1000 strokes : +/- 2.2
Spreed
Tolerance
cm³/1000 strokes : 1.5
Check tolerance
cm³/1000S. : 2.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 3.250

Del. quantity
cm³/1000 strokes : 52.0
Check tolerance
cm³/1000S. : +- 2.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 8.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 08.03.96
Test oil : ISO 4113
Combination No. : 0 400 195 004
Injection pump
Pump designation : PES5M60C320RS205
EP type number : 0 410 065 001
Governor
Governor design. : RE22
Governor no. : 0 420 090 003

Cust. part No. :

Customer-spec. information
Customer : MB-PKW
Motor : OM 605 D 25 LA
Power kW : 110.0

TEST BENCH REQUIREMENTS

Inlet line : 1.1;
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 469 990 351
Inlet press. bar : 1.0
Tolerance bar : ± 0.1
Test nozzle holder assembly : 0 688 901 111
Opening pressure bar : 148.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

G07

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values in Section (B) must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.55
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 17.00
Tolerance mm : ± 1.00

Firing order : 1- 2- 4- 5- 3

Phasing : 0-72-144-216-288

Start of delivery blocking

*NW after s.o.d. : 17.00
Tolerance : ± 0.20
Check tolerance *NW : ± 0.30

Barrel no. : 1

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.
CRT mm : 0.75
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1000
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 58.0
Tolerance
cm³/1000 strokes : +/- 0.5
Check tolerance
cm³/1000S. : +/- 2.0
Spreed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 3.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 2200
Uact V : 3.250
Rated speed rpm : 500
Uact V : 3.250

TEST POINT L1

Rated speed rpm : 340
Uact V : 1.950
Del. quantity
cm³/1000 strokes : 10.5
Tolerance
cm³/1000 strokes : +/- 2.2
Spreed
Tolerance
cm³/1000 strokes : 1.5
Check tolerance
cm³/1000S. : 2.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 3.250

Del. quantity
cm³/1000 strokes : 52.0
Check tolerance
cm³/1000s. : ± 2.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 8.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 08.03.96
Test oil : ISO 4113
Combination No. : 0 400 196 002
Injection pump
Pump designation : PES6M55C320RS204
EP type number : 0 410 056 969

Governor
Governor design. : RE22
Governor no. : 0 420 090 002

Cust. part No. :

Customer-spec. information
Customer : MB-PKW
Motor : OM 606
Power KW : 100.0

TEST BENCH REQUIREMENTS

Inlet line : 1.1;

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 469 990 351

Inlet press. bar : 1.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 0 688 901 111

Opening pressure
bar : 148.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

G10

x inside diameter : 2.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 1.75
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.05

Rack travel in mm : 17.00
Tolerance mm : ± 1.00

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Start of delivery blocking

°NW after s.o.d. : 16.50
Tolerance : ± 0.20
Check
tolerance °NW : ± 0.30

Barrel no. : 1

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1000
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 35.5
Tolerance
cm³/1000 strokes : +/- 0.5
Check tolerance
cm³/1000S. : +/- 1.2
Speed
Tolerance
cm³/1000 strokes : 2.5
Check tolerance
cm³/1000S. : 3.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 2500
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 41.6
Check tolerance
cm³/1000S. : +/- 1.5
Speed
Check tolerance
cm³/1000S. : 3.3

Rated speed rpm : 500
Uact V : 3.250
Del. quantity
cm³/1000 strokes : 33.2
Check tolerance
cm³/1000S. : +/- 1.2
Speed
Check tolerance
cm³/1000S. : 3.0

TEST POINT L1

Rated speed rpm : 330

Uact V : 2.200
Del. quantity
cm3/1000 strokes : 7.6
Spreed
Tolerance
cm3/1000 strokes : 1.0
Check tolerance
cm3/1000S. : 1.8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.000
Del. quantity
cm3/1000 strokes : 52.2
Check tolerance
cm3/1000S. : +- 3.5
Spreed
Check tolerance
cm3/1000S. : 5.5

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 15.03.96
Test oil : ISO 4113

Combination No. : 0 402 746 650

Injection pump
Pump designation : PES6P120A320RS7344
EP type number : 0 412 726 914

Governor
Governor design. : RQ275/1050PA999-6
Governor no. : 0 421 801 785

Cust. part No. : CCEP 5151A 66-230

Customer-spec. information

Customer : RVI
Motor : MIDR 062045 M41
Power KW : 250.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Overflow quantity
min. l/h : 145
Tolerance l/h : +- 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.50
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 11.00
Tolerance mm : +- 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark

°NW after s.o.d. : -0.15
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery differende

betw. rack trav.
mm : 21.00
and maximum rack
travel : 11.00
Difference ° CS : 2.25

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 11.60
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 288.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 275

Rack travel in mm : -7.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 37.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 275
guide sleeve
travel mm : 0.80
Tolerance mm : +- 0.10

Rated speed rpm : 1132
guide sleeve
travel mm : 6.37
Tolerance mm : +- 0.10

Rated speed rpm : 1050
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 416
guide sleeve
travel mm : 3.44
Tolerance mm : +- 0.10

Rated speed rpm : 560
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 1350
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 288.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 274.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1135
Tolerance 1/min : +- 5

rack travel mm : -7.60
Rated speed rpm : 1240
Tolerance 1/min : +- 15

rack travel mm : -11.10
Tolerance mm : +- 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 251.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 275
rack travel mm : -7.00
Tolerance mm : +- 0.10

rack travel mm : -9.50
Rated speed rpm : 365
Tolerance 1/min : +- 20

Rated speed rpm : 200

CRT mm min. : < -5.80

TORQUE CONTROL

Rated speed rpm : 600

Rated speed rpm : 1050
Tolerance mm : +- 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1000

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : -3.65
Tolerance mm : +- 0.30

Rated speed rpm : 500

Pressure hPa : 560
rack travel mm : -1.25

Tolerance mm : +- 0.15

Pressure hPa : 320
rack travel mm : -2.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 225

Check
speed 1/min : > 80
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 281.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 114.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1135
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 150.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 275
Del. quantity
cm³/1000 strokes : 37.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions. See microcard(s) W400/...

Edition : 24.04.96
Test oil : ISO 4113
Combination No. : 9 407 083 263
Injection pump
Pump designation : PES6A90D32ORS2605
EP type number : 9 400 083 078
Governor
Governor design. : RSV325...900A1C2132R
Governor no. : 9 420 083 280

Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : TD 229-6
Power kW : 89.7

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder assembly : 0 681 343 009
Opening pressure bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 003
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant. per values

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2- : 4

Phasing : 0-60-120-180-240 : -300

Beginning of delivery difference

and maximum rack travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 10.25
Tolerance mm : +- 0.05

Del. quantity cm3/1000 strokes : 73.5

Tolerance cm3/1000 strokes : +- 0.5

Check tolerance cm3/1000S. : +- 2.5

<hr/>	
Spreed	
Tolerance	
cm ³ /1000 strokes :	3.0
<hr/>	
Check tolerance	
cm ³ /1000S. :	7.0
<hr/>	
Rated speed rpm :	325
<hr/>	
Rack travel in mm :	7.00
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	15.5
Tolerance	
cm ³ /1000 strokes :	+ 2.0
Check tolerance	
cm ³ /1000S. :	+ 4.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	4.5
Check tolerance	
cm ³ /1000S. :	7.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

<hr/>	
GUIDE SLEEVE POSITION	
<hr/>	
Rated speed rpm :	800
<hr/>	
Rack travel in mm :	0.65
Tolerance mm :	+ 0.35
<hr/>	
governor spring	
pre-tension	
click setting x :	4.25

<hr/>	
FULL LOAD DELIVERY AT FULL LOAD STOP	
<hr/>	
Rated speed rpm :	900
Aneroid pressure	
hPa :	-
Del. quantity	
cm ³ /1000 strokes :	73.5
Tolerance	
cm ³ /1000 strokes :	+ 0.5
Check tolerance	
cm ³ /1000S. :	+ 2.5
Spreed	
Tolerance	
cm ³ /1000 strokes :	3.0
Check tolerance	
cm ³ /1000S. :	7.0

<hr/>	
CONTROL LEVER	
<hr/>	
control lever	
position degree :	97.0
tolerance degree :	+ 4.0

<hr/>	
ASSEMBLY GOVERNOR SETTING	
<hr/>	
Rated speed rpm :	923
rack travel mm :	9.20
<hr/>	
Rated speed rpm :	958
Tolerance 1/min :	+ 4
rack travel mm :	4.00
<hr/>	
rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1050
<hr/>	
Rated speed rpm :	924
rack travel mm :	9.20
<hr/>	
Rated speed rpm :	959
Tolerance 1/min :	+ 4
rack travel mm :	4.00
<hr/>	
rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1050
<hr/>	
Rated speed rpm :	925
rack travel mm :	9.20
<hr/>	
Rated speed rpm :	960
Tolerance 1/min :	+ 4
rack travel mm :	4.00
<hr/>	
rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1050
<hr/>	
Rated speed rpm :	926
rack travel mm :	9.20
<hr/>	
Rated speed rpm :	961
Tolerance 1/min :	+ 4
rack travel mm :	4.00
<hr/>	
rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1050
<hr/>	
Rated speed rpm :	927
rack travel mm :	9.20
<hr/>	
Rated speed rpm :	962
Tolerance 1/min :	+ 4

rack travel mm : 4.00
rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1050
Rated speed rpm : 928
rack travel mm : 9.20
Rated speed rpm : 963
Tolerance 1/min : + 4
rack travel mm : 4.00
rack travel mm : 0.85
Tolerance mm : + 0.55
Rated speed rpm : 1050

LOW IDLE

control lever
position degree : 74.0
tolerance degree : + 4.0
Setting point w/out bumper spring

Rated speed rpm : 325
rack travel mm : 6.50

Testing:

Rated speed rpm : 325
rack travel mm : 7.00
Tolerance mm : + 0.10
rack travel mm : 2.00
Rated speed rpm : 395
Tolerance 1/min : + 30
Rated speed rpm : 100
CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 10.25
Tolerance mm : + 0.05
Rated speed rpm : 500
rack travel mm : 10.30
Tolerance mm : + 0.10
Rated speed rpm : 375
rack travel mm : 11.30
Tolerance mm : + 0.30

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : + 1.00

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 15.5
Tolerance
cm³/1000 strokes : + 2.0
Check tolerance
cm³/1000S. : + 4.0
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113
Combination No. : 9 407 083 270
Injection pump
Pump designation : PES6A90D410RS2293
EP type number : 0 410 896 031
Governor
Governor design. : RQV300...1400AB740
 : -1L
Governor no. : 9 420 080 153
Cust. part No. :

Customer-spec. information
Customer : MBA
Motor : OM352-A
Power KW : 117.8

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 1.5
Test nozzle holde
assembly : 0 681 343 009
Opening pressure
bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

G20

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 2.20
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
 : 4
Phasing : 0-60-120-180-240
 : -300

BASIC SETTING

Rated speed rpm : 1400
Rack travel in mm : 11.05
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 71.5
Tolerance
cm3/1000 strokes : +- 0.5
Check tolerance
cm3/1000S. : +- 2.5
Spreed
Tolerance
cm3/1000 strokes : 3.0
Check tolerance
cm3/1000S. : 7.0

Rated speed rpm : 300

Rack travel in mm : 7.50
 Tolerance mm : +- 0.10
 Del. quantity
 cm3/1000 strokes : 11.0
 Tolerance
 cm3/1000 strokes : +- 2.0
 Check tolerance
 cm3/1000S. : +- 4.0
 Spread
 Tolerance
 cm3/1000 strokes : 4.5
 Check tolerance
 cm3/1000S. : 7.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1460
 guide sleeve
 travel mm : 8.50
 Tolerance mm : +- 0.10

Rated speed rpm : 775
 guide sleeve
 travel mm : 4.35
 Tolerance mm : +- 0.25

Rated speed rpm : 300
 guide sleeve
 travel mm : 0.95
 Tolerance mm : +- 0.25

Rated speed rpm : 550
 guide sleeve
 travel mm : 2.85
 Tolerance mm : +- 0.15

Rated speed rpm : 950
 guide sleeve
 travel mm : 5.35
 Tolerance mm : +- 0.15

GUIDE SLEEVE POSITION

Rated speed rpm : 1420

Rack travel in mm : 16.50
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1400
 Aneroid pressure
 hPa : -
 Del. quantity
 cm3/1000 strokes : 71.5
 Tolerance
 cm3/1000 strokes : +- 0.5
 Check tolerance
 cm3/1000S. : +- 2.5
 Spread
 Tolerance
 cm3/1000 strokes : 3.0
 Check tolerance
 cm3/1000S. : 7.0

CONTROL LEVER

control lever
 position degree : 116.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.00
 Rated speed rpm : 1445
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1570
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1700

LOW IDLE

control lever
 position degree : 68.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 7.50
 Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 9.00

Rated speed rpm : 435

TORQUE CONTROL

Rated speed rpm : 1400
rack travel mm : 11.05
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 11.10
Tolerance mm : ± 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check speed 1/min : > 80
Check speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 54.0
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000s. : ± 3.5

BREAKAWAY

Rack travel in mm : 10.00
Rated speed rpm : 1445
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 13.90
Tolerance mm : ± 0.20
Del. quantity
cm³/1000 strokes : 78.0
Tolerance
cm³/1000 strokes : ± 7.5
Check tolerance
cm³/1000s. : ± 10.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 11.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000s. : 7.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113
Combination No. : 9 407 083 279
Injection pump
Pump designation : PES6A80D320RS1271
EP type number : 9 400 083 058
Governor
Governor design. : RSV350...1400A2C2179
: R
Governor no. : 9 420 083 281
Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : D229-6
Power KW : 100.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 0 681 343 009
Opening pressure
bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 003
Outside diameter : 6.0

G23

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Beginning of delivery differende

and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1400

Rack travel in mm : 9.65
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 55.0

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000s. : +- 2.0

Spreed
 Tolerance
 cm³/1000 strokes : 2.5

 Check tolerance
 cm³/1000S. : 4.0

 Rated speed rpm : 350

 Rack travel in mm : 7.40
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 12.5
 Tolerance
 cm³/1000 strokes : +- 1.5
 Check tolerance
 cm³/1000S. : +- 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

 Rack travel in mm : 0.65
 Tolerance mm : +- 0.35

 governor spring
 pre-tension
 click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1400
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 55.0
 Tolerance
 cm³/1000 strokes : +- 0.5
 Check tolerance
 cm³/1000S. : +- 2.0
 Spreed
 Tolerance
 cm³/1000 strokes : 2.5
 Check tolerance
 cm³/1000S. : 4.0

CONTROL LEVER

control lever
 position degree : 105.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 8.60
 Rated speed rpm : 1445
 Tolerance 1/min : +- 5

 rack travel mm : 4.00
 Rated speed rpm : 1490
 Tolerance 1/min : +- 15

 rack travel mm : 0.85
 Tolerance mm : +- 0.55
 Rated speed rpm : 1650

LOW IDLE

control lever
 position degree : 72.0
 tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
 rack travel mm : 6.90

Testing:

Rated speed rpm : 350
 rack travel mm : 7.40
 Tolerance mm : +- 0.10

rack travel mm : 2.00
 Rated speed rpm : 660
 Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1400
 rack travel mm : 9.65
 Tolerance mm : +- 0.05

Rated speed rpm : 500
 rack travel mm : 10.65
 Tolerance mm : +- 0.05

Rated speed rpm : 800
rack travel mm : 10.40
Tolerance mm : +- 0.10

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 50.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 53.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 8.60
Rated speed rpm : 1445
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 12.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.5
Spreed

G25

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113

Combination No. : 9 407 083 281

Injection pump
Pump designation : PES6A80D320RS1271
EP type number : 9 400 083 058

Governor
Governor design. : RSV350...1150A2C2129
: -1R
Governor no. : 9 420 083 282

Cust. part No. :

Customer-spec. information

Customer : MWM
Motor : D 229-6
Power KW : 77.2

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 003

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Beginning of delivery differende

and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 9.45
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 50.0

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000S. : +- 2.0

Spreed
 Tolerance
 cm³/1000 strokes : 2.5

 Check tolerance
 cm³/1000S. : 4.0

 Rated speed rpm : 350

 Rack travel in mm : 7.00
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 8.5
 Tolerance
 cm³/1000 strokes : +- 1.5
 Check tolerance
 cm³/1000S. : +- 3.5
 Spreed
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800
 Rack travel in mm : 0.65
 Tolerance mm : +- 0.35

 governor spring
 pre-tension
 click setting x : 4.25

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 50.0
 Tolerance
 cm³/1000 strokes : +- 0.5
 Check tolerance
 cm³/1000S. : +- 2.0
 Spreed
 Tolerance
 cm³/1000 strokes : 2.5
 Check tolerance
 cm³/1000S. : 4.0

CONTROL LEVER

control lever
 position degree : 96.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 8.50
 Rated speed rpm : 1175
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1225
 Tolerance 1/min : +- 15

rack travel mm : 0.85
 Tolerance mm : +- 0.55
 Rated speed rpm : 1400

LOW IDLE

control lever
 position degree : 73.0
 tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
 rack travel mm : 6.50

Testing:

Rated speed rpm : 350
 rack travel mm : 7.00
 Tolerance mm : +- 0.10

rack travel mm : 2.00
 Rated speed rpm : 645
 Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1150
 rack travel mm : 9.45
 Tolerance mm : +- 0.05

Rated speed rpm : 500
 rack travel mm : 11.05
 Tolerance mm : +- 0.05

Rated speed rpm : 900
rack travel mm : 10.+0
Tolerance mm : +- 0.10

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 54.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 52.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 8.50
Rated speed rpm : 1175
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 8.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.5
Speed

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113

Combination No. : 9 407 083 283

Injection pump
Pump designation : PES3A80D320RS1281
EP type number : 9 400 083 054

Governor
Governor design. : RSV350...1150A2C2129
: -1R
Governor no. : 9 420 083 282

Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : D 229-3
Power KW : 55.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 046

Inlet press. bar : 1.5

Test nozzle holde
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 003

Outside diameter : 6.0

H01

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 2- 3

Phasing : 0-120-240

Beginning of delivery differende

and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 9.45
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 51.5

Tolerance
cm3/1000 strokes : +- 0.5

Check tolerance
cm3/1000S. : +- 2.0

Spread

Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

Rated speed rpm : 350

Rack travel in mm : 7.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 11.0

Tolerance
cm³/1000 strokes : +- 1.5

Check tolerance
cm³/1000S. : +- 3.5

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
Tolerance mm : +- 0.35

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 51.5

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000S. : +- 2.0

Spreed
Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

CONTROL LEVER

control lever
position degree : 99.0

H02

tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 8.40
Rated speed rpm : 1195

Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1250

Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55

Rated speed rpm : 1400

LOW IDLE

control lever
position degree : 75.0

tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
rack travel mm : 6.50

Testing:

Rated speed rpm : 350
rack travel mm : 7.00

Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 680

Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 9.45

Tolerance mm : +- 0.05

Rated speed rpm : 500
rack travel mm : 10.85

Tolerance mm : +- 0.05

Rated speed rpm : 900

rack travel mm : 10.15

Tolerance mm : +- 0.15

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 53.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 54.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 8.40
Rated speed rpm : 1195
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 11.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.5
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.04.96
Test oil : ISO 4113
Combination No. : 9 407 083 284
Injection pump
Pump designation : PES4A80D320RS1282
EP type number : 9 400 083 056
Governor
Governor design. : RSV350...1150A2C2129
: -1R
Governor no. : 9 420 083 282
Cust. part No. :

Customer-spec. information

Customer : MWM
Motor : D 229-4
Power KW : 53.5

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 0 681 343 009
Opening pressure
bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 003
Outside diameter : 6.0

H04

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270
Beginning of delivery differende
and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1150
Rack travel in mm : 8.85
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 50.0
Tolerance
cm3/1000 strokes : +- 0.5
Check tolerance
cm3/1000s. : +- 2.0
Spreed

Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

Rated speed rpm : 350

Rack travel in mm : 6.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 8.5

Tolerance
cm³/1000 strokes : ± 1.5

Check tolerance
cm³/1000S. : ± 3.5

Spread
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
Tolerance mm : ± 0.35

governor spring
pre-tension
click setting x : 4.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 50.0

Tolerance
cm³/1000 strokes : ± 0.5

Check tolerance
cm³/1000S. : ± 2.0

Spread
Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 7.90
Rated speed rpm : 1175
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1225
Tolerance 1/min : ± 15

rack travel mm : 0.85
Tolerance mm : ± 0.55
Rated speed rpm : 1400

LOW IDLE

control lever
position degree : 73.0
tolerance degree : ± 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
rack travel mm : 6.00

Testing:

Rated speed rpm : 350
rack travel mm : 6.50
Tolerance mm : ± 0.10

rack travel mm : 2.00
Rated speed rpm : 625
Tolerance 1/min : ± 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 8.85
Tolerance mm : ± 0.05

Rated speed rpm : 500
rack travel mm : 10.65
Tolerance mm : ± 0.05

Rated speed rpm : 900
rack travel mm : 9.95
Tolerance mm : +- 0.15

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 55.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 900
Del. quantity
cm³/1000 strokes : 54.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 7.90
Rated speed rpm : 1175
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 8.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 3.5
Spreed

H06

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113

Combination No. : 9 407 083 290

Injection pump
Pump designation : PES6A80D320RS1271
EP type number : 9 400 083 058

Governor
Governor design. : RSV350...1000A1C2029
: -1R
Governor no. : 9 420 083 285

Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : D 229-6

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 003

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Beginning of delivery difference

and maximum rack
travel : 10.50
Tolerance mm : ± 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1000

Rack travel in mm : 9.75
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 49.5

Tolerance
cm³/1000 strokes : ± 0.5

Check tolerance
cm³/1000S. : ± 2.0

<hr/>	
Spreed	
Tolerance	
cm ³ /1000 strokes :	2.5
<hr/>	
Check tolerance	
cm ³ /1000S.	: 4.0
<hr/>	
Rated speed rpm :	350
<hr/>	
Rack travel in mm :	7.00
Tolerance mm :	+ 0.10
Del. quantity	
cm ³ /1000 strokes :	8.5
Tolerance	
cm ³ /1000 strokes :	+ 1.5
Check tolerance	
cm ³ /1000S.	: + 3.5
Spreed	
Tolerance	
cm ³ /1000 strokes :	4.0
Check tolerance	
cm ³ /1000S.	: 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm :	800
<hr/>	
Rack travel in mm :	0.65
Tolerance mm :	+ 0.35
<hr/>	
governor spring	
pre-tension	
click setting x :	5.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm :	1000
Aneroid pressure	
hPa :	-
Del. quantity	
cm ³ /1000 strokes :	49.5
Tolerance	
cm ³ /1000 strokes :	+ 0.5
Check tolerance	
cm ³ /1000S.	: + 2.0
Spreed	
Tolerance	
cm ³ /1000 strokes :	2.5
Check tolerance	
cm ³ /1000S.	: 4.0

CONTROL LEVER

control lever	
position degree :	58.0
tolerance degree :	+ 4.0

control lever	
position degree :	108.0
tolerance degree :	+ 4.0

RATED SPEED

rack travel mm :	8.70
Rated speed rpm :	1045
Tolerance 1/min :	+ 5

rack travel mm :	4.00
Rated speed rpm :	1085
Tolerance 1/min :	+ 15

rack travel mm :	0.85
Tolerance mm :	+ 0.55
Rated speed rpm :	1200

LOW IDLE

control lever	
position degree :	80.0
tolerance degree :	+ 4.0

control lever	
position degree :	30.0
tolerance degree :	+ 4.0

Setting point w/out bumper spring

Rated speed rpm :	350
rack travel mm :	6.50

Testing:

Rated speed rpm :	350
rack travel mm :	7.00
Tolerance mm :	+ 0.10

rack travel mm :	2.00
Rated speed rpm :	555
Tolerance 1/min :	+ 30

Rated speed rpm :	100
-------------------	-----

CRT mm min. :	> 19.00
---------------	---------

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 9.75
Tolerance mm : +- 0.05

Rated speed rpm : 500
rack travel mm : 11.25
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 10.75
Tolerance mm : +- 0.15

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 8.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000s. : +- 3.5
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000s. : 6.0

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 54.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000s. : +- 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 54.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000s. : +- 3.0

BREAKAWAY

Rack travel in mm : 8.70
Rated speed rpm : 1045
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00

LOW IDLE

H09

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.04.96
Test oil : ISO 4113

Combination No. : 9 407 083 296

Injection pump
Pump designation : PES4A80D32ORS1282
EP type number : 9 400 083 056

Governor
Governor design. : RSV350...1500A2C2122
: -2R
Governor no. : 9 420 083 286

Cust. part No. :

Customer-spec. information

Customer : MWM
Motor : D 229-4
Power KW : 64.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holder
assembly : 0 681 343 009

Opening pressure
bar : 173.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 003

Outside diameter : 6.0

H10

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270

Beginning of delivery difference

and maximum rack
travel : 10.50
Tolerance mm : +- 1.50
Difference ° CS : 4.50

BASIC SETTING

Rated speed rpm : 1500

Rack travel in mm : 9.65
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 62.0

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000S. : +- 2.0

Speed

Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

Rated speed rpm : 350

Rack travel in mm : 7.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 13.5

Tolerance
cm³/1000 strokes : +- 1.5

Check tolerance
cm³/1000S. : +- 3.5

Spread
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.65
Tolerance mm : +- 0.35

governor spring
pre-tension
click setting x : 4.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1500

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 62.0

Tolerance
cm³/1000 strokes : +- 0.5

Check tolerance
cm³/1000S. : +- 2.0

Spread
Tolerance
cm³/1000 strokes : 2.5

Check tolerance
cm³/1000S. : 4.0

CONTROL LEVER

control lever
position degree : 112.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 8.60
Rated speed rpm : 1575
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1625
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1800

LOW IDLE

control lever
position degree : 74.0
tol. degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
rack travel mm : 6.50

Testing:

Rated speed rpm : 350
rack travel mm : 7.00
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 650
Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1500
rack travel mm : 9.65
Tolerance mm : +- 0.05

Rated speed rpm : 500
rack travel mm : 10.75
Tolerance mm : +- 0.05

Rated speed rpm : 800
rack travel mm : 10.50
Tolerance mm : \pm 0.10

Rated speed rpm : 1100
rack travel mm : 10.15
Tolerance mm : \pm 0.15

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 57.0
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 60.5
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.0

Aneroid pressure
hPa : -
Rated speed rpm : 1100
Del. quantity
cm³/1000 strokes : 63.5
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.0

BREAKAWAY

Rack travel in mm : 8.60
Rated speed rpm : 1575
Tolerance 1/min : \pm 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : \pm 1.00

H12

Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : \pm 8.0
Check tolerance
cm³/1000S. : \pm 39.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 13.5
Tolerance
cm³/1000 strokes : \pm 1.5
Check tolerance
cm³/1000S. : \pm 3.5
Speed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.05.96
Test oil : ISO 4113
Combination No. : 9 400 085 339
Injection pump
Pump designation : PES4A95D410RS2774
EP type number : 9 400 084 019
Governor
Governor design. : RQV300...1300AB1066
: -11L
Governor no. : 9 420 080 309
Cust. part No. : 0200742602

Customer-spec. information

Customer : MBB
Motor : OM 364 LA
Power KW : 100.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holder
assembly : 0 681 343 009
Opening pressure
bar : 173.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

H13

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 3.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270

BASIC SETTING

Rated speed rpm : 1300
Rack travel in mm : 11.55
Tolerance mm : +- 0.05
Del. quantity
cm³/1000 strokes : 103.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0
Speed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 8.0
Rated speed rpm : 300

Rack travel in mm : 7.00
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 9.5
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 4.5
 Spread
 Tolerance
 cm³/1000 strokes : 5.5
 Check tolerance
 cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1350
 guide sleeve
 travel mm : 8.20
 Tolerance mm : +- 0.10

Rated speed rpm : 1000
 guide sleeve
 travel mm : 5.75
 Tolerance mm : +- 0.25

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.05
 Tolerance mm : +- 0.25

Rated speed rpm : 700
 guide sleeve
 travel mm : 4.25
 Tolerance mm : +- 0.25

Rated speed rpm : 1450
 guide sleeve
 travel mm : 9.15
 Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

Rated speed rpm : 1395
 Rack travel in mm : 16.50
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1300

Aneroid pressure
 hPa : 800
 Del. quantity
 cm³/1000 strokes : 103.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.0
 Spread
 Tolerance
 cm³/1000 strokes : 3.5
 Check tolerance
 cm³/1000S. : 8.0

CONTROL LEVER

control lever
 position degree : 63.0
 tolerance degree : +- 4.0

control lever
 position degree : 112.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.50
 Rated speed rpm : 1360
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1475
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1630

LOW IDLE

control lever
 position degree : 68.0
 tolerance degree : +- 4.0

control lever
 position degree : 20.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
 rack travel mm : 7.00
 Tolerance mm : +- 0.10

Rated speed rpm : 100

1.00
135
5

Rated speed rpm : 500
Pressure hPa : 560
rack travel mm : -1.25
G15
cm3/1000 strokes : +- 15.0
check tolerance
cm3/1000S. : +- 19.0

800
103.0
1.0
3.0
3.5
8.0
63.0
4.0
112.0
4.0
10.50
360
5
4.00
475
15
0.50
0.50
630
68.0
4.0
20.0
4.0
300
7.00
0.10
100

CRT mm min. : > 9.00
Rated speed rpm : 525
TORQUE CONTROL
Rated speed rpm : 1300
rack travel mm : 11.55
Tolerance mm : +- 0.05
Rated speed rpm : 700
rack travel mm : 11.85
Tolerance mm : +- 0.05
Rated speed rpm : 1100
rack travel mm : 11.75
Tolerance mm : +- 0.05
Rated speed rpm : 950
rack travel mm : 11.85
Tolerance mm : +- 0.05
ANEROID/ALTITUDE
COMPENSATOR TEST
SETTING
Rated speed rpm : 500
Pressure hPa : 800
rack travel mm : 11.85
Tolerance mm : +- 0.05
MEASUREMENT
Pressure hPa : -
Rated speed rpm : 500
Rated speed rpm : 500
Pressure hPa : 500
rack travel mm : 1.45
Tolerance mm : +- 0.15
Pressure hPa : 360
rack travel mm : 0.40
Tolerance mm : +- 0.10
START CUT-OUT
Rated speed rpm : > 100
Rated speed rpm : < 250
Check
speed 1/min : > 80
H15
Check
speed 1/min : < 270
FUEL DELIVERY CHARACTERISTICS
Aneroid pressure
hPa : 800
Rated speed rpm : 700
Del. quantity
cm3/1000 strokes : 97.5
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.0
Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 59.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 3.0
BREAKAWAY
Rack travel in mm : 10.50
Rated speed rpm : 1360
Tolerance 1/min : +- 5
STARTING FUEL DELIVERY
Rated speed rpm : 100
rack travel mm : 13.40
Tolerance mm : +- 0.10
Del. quantity
cm3/1000 strokes : 86.0
Tolerance
cm3/1000 strokes : +- 7.5
Check tolerance
cm3/1000S. : +- 10.0
LOW IDLE
Rated speed rpm : 300
Del. quantity
cm3/1000 strokes : 9.5
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
MEASUREMENT
Check tolerance
cm3/1000S. : +- 19.0

15

MEASUREMENT
Check tolerance
cm3/1000S. : +- 19.0

Spreed

Tolerance

cm³/1000 strokes : 5.5

Check tolerance

cm³/1000s. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 09.05.96
Test oil : ISO 4113

Combination No. : 9 400 087 497

Injection pump
Pump designation : PES6P120A120RS3344
EP type number : 9 400 087 090

Governor
Governor design. : RQV350...1100PA1207
Governor no. : 9 420 080 379

Cust. part No. : 3355976

Customer-spec. information
Customer : CUMMINS
Motor : 6 CTAA - 290
Power KW : 214.6

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 3.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.15
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 15.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Start of delivery blocking

*NW after s.o.d. : 7.50
Tolerance : +- 0.10
Check
tolerance °NW : +- 0.23

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 15.55
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 207.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 325

Rack travel in mm : 7.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 44.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 1150
guide sleeve
travel mm : 8.40
Tolerance mm : +- 0.10

Rated speed rpm : 650
guide sleeve
travel mm : 5.55
Tolerance mm : +- 0.25

Rated speed rpm : 350
guide sleeve
travel mm : 1.55
Tolerance mm : +- 0.25

Rated speed rpm : 500
guide sleeve
travel mm : 4.05
Tolerance mm : +- 0.25

Rated speed rpm : 1400
guide sleeve
travel mm : 10.55
Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

Rated speed rpm : 1150

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1300

Del. quantity
cm³/1000 strokes : 207.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 63.0
tolerance degree : +- 4.0

control lever
position degree : 118.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 14.50
Rated speed rpm : 1150
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1360
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1500

LOW IDLE

control lever
position degree : 69.0

tolerance degree : +- 4.0
control lever
position degree : 14.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 325
rack travel mm : 7.00
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 9.50

Rated speed rpm : 375

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 15.55
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 15.95
Tolerance mm : +- 0.05

Rated speed rpm : 720
rack travel mm : 15.95
Tolerance mm : +- 0.05

Rated speed rpm : 960
rack travel mm : 15.55
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1300
rack travel mm : 15.95
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500

Rated speed rpm : 500

Pressure hPa : 800
rack travel mm : 2.75
Tolerance mm : +- 0.15

Pressure hPa : 400
rack travel mm : 1.10
Tolerance mm : +- 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 270

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1300
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 217.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 125.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000s. : +- 4.0

BREAKAWAY

Rack travel in mm : 14.50
Rated speed rpm : 1150
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 190.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000s. : +- 14.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 44.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.05.96
Test oil : ISO 4113

Combination No. : 0 402 736 905

Injection pump
Pump designation : PES6P120A120RS7416
EP type number : 0 412 726 959

Governor
Governor design. : RQV400...1250PA1060
 : -3K
Governor no. : 0 421 815 513

Cust. part No. : 3928145

Customer-spec. information
Customer : CDC
Motor : 6BTA-A
Power KW : 119.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 093

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
 : 4

Phasing : 0-60-120-180-240
 : -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

°NW after s.o.d. : 6.25
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 13.35
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 153.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

Rated speed rpm : 420

Rack travel in mm : 6.00
Tolerance mm : +- 0.20
Del. quantity
cm³/1000 strokes : 15.5
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 400
guide sleeve
travel mm : 1.44
Tolerance mm : +- 0.20

Rated speed rpm : 1329
guide sleeve
travel mm : 7.83
Tolerance mm : +- 0.15

Rated speed rpm : 939
guide sleeve
travel mm : 5.18
Tolerance mm : +- 0.25

Rated speed rpm : 640
guide sleeve
travel mm : 3.56
Tolerance mm : +- 0.25

Rated speed rpm : 1690
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 153.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.30
Rated speed rpm : 1325
Tolerance 1/min : +- 15

rack travel mm : 4.00
Rated speed rpm : 1475
Tolerance 1/min : +- 5

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 71.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 420
rack travel mm : 6.00
Tolerance mm : +- 0.20

Rated speed rpm : 400
CRT mm min. : > 5.80
Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 1250
rack travel mm : 13.35
Tolerance mm : +- 0.05

Rated speed rpm : 800
rack travel mm : 12.00
Tolerance mm : +- 0.20

Rated speed rpm : 500
rack travel mm : 11.60
Tolerance mm : +- 0.20

Rated speed rpm : 900
rack travel mm : 12.40
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1250
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1250
rack travel mm : 10.40
Tolerance mm : +- 0.20

Rated speed rpm : 1250

Pressure hPa : 350
rack travel mm : 12.70
Tolerance mm : +- 0.30

Pressure hPa : 265
rack travel mm : 11.80
Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 280

Check
speed 1/min : > 80

H23

Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 133.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1250
Del. quantity
cm³/1000 strokes : 106.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 12.30
Rated speed rpm : 1325
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 13.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 155.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Rated speed rpm : 420

Del. quantity
cm³/1000 strokes : 15.5
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 22.05.96
Test oil : ISO 4113
Combination No. : 0 401 496 003
Injection pump
Pump designation : PE6R120/72ORS1504
EP type number : 0 411 426 003

Governor
Governor design. : RE31
Governor no. : 0 421 890 200

Cust. part No. : 1556415
: -P08 v. 12/95

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD 164
Power KW : 382.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 078

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.45
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.
CRT mm : 0.75
Tolerance mm : +/- 0.25
Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60

Amplitude V : 1.4
Tolerance V : +/- 0.6
Check tolerance V : +/- 1.20

Engine speed min-1: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 525
Uact V : 2.950
Del. quantity
cm³/1000 strokes : 390.0
Tolerance
cm³/1000 strokes : +/- 1.0
Check tolerance
cm³/1000S. : +/- 4.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 900
Uact V : 3.240
Del. quantity
cm³/1000 strokes : 386.0
Tolerance
cm³/1000 strokes : +/- 3.0
Check tolerance
cm³/1000S. : +/- 6.0
Speed
Tolerance
cm³/1000 strokes : 9.0
Check tolerance
cm³/1000S. : 13.0

Rated speed rpm : 900
Uact V : 2.000
Del. quantity
cm³/1000 strokes : 163.0
Tolerance
cm³/1000 strokes : +/- 3.0
Check tolerance
cm³/1000S. : +/- 6.0

TEST POINT L1

Rated speed rpm : 265
Uact V : 1.630
Tolerance Volt : +/- 0.060

Check tolerance
Volt : ± 0.060
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Speed
Tolerance
cm³/1000 strokes : 7.0
Check tolerance
cm³/1000S. : 11.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions. See microcard(s) W400/...

Edition : 22.05.96
Test oil : ISO 4113

Combination No. : 0 401 876 801

Injection pump
Pump designation : PE6P120A32ORS3375
EP type number : 0 411 826 817

Governor
Governor design. : RSV250...900POA646
Governor no. : 0 421 833 562

Cust. part No. : 3826154 P01 v.11/95

Customer-spec. information
Customer : PENTA
Motor : TWD 710P
Power KW : 153.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Vibration damper (RoBo diaphragm) : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 457 413 010

Inlet press. bar : 1.5
Tolerance bar : +- 0.1

Overflow quantity min. l/h : 240
Tolerance l/h : +- 20.0

Test nozzle holder assembly : 1 688 901 019

Opening pressure bar : 208.5
Tolerance bar : +- 1.5

Test Lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant. per values

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 2.65
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 0.50

Firing order : 1- 5- 3- 6- 2- : 4

Phasing : 0-60-120-180-240 : -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 8.15

Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 155.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 5.0

Check tolerance
cm3/1000S. : 9.0

Rated speed rpm : 250

Rack travel in mm : 4.80
Tolerance mm : +- 0.10
Del. quantity
cm3/1000 strokes : 23.0
Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 5.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : -
Del. quantity
cm3/1000 strokes : 155.0

Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 37.0
tolerance degree : +- 4.0

control lever
position degree : 87.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 7.15
Rated speed rpm : 920
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 955
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1050

LOW IDLE

control lever
position degree : 69.0
tolerance degree : +- 4.0

control lever
position degree : 19.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 250
rack travel mm : 4.30

Testing:

Rated speed rpm : 250
rack travel mm : 4.80
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 335
Tolerance 1/min : +- 30

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 8.15
Tolerance mm : +- 0.05

BREAKAWAY

Rack travel in mm : 7.15
Rated speed rpm : 920
Tolerance 1/min : +- 5

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 20.05.96
Test oil : ISO 4113
Combination No. : 0 401 878 140
Injection pump
Pump designation : PE8P120A520/5RS427
EP type number : 0 411 828 048
Governor
Governor design. : RSUV300...900^oOA320
: -1
Governor no. : 0 421 829 107
Cust. part No. :

Customer-spec. information
Customer : MWM
Motor : TBD 234 V8
Power KW : 400.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 019
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

J03

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 2.85
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 8- 5- 4- 7
: - 2- 3- 6

Phasing : 0-30-90-120-180
: -210-270-300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Start of delivery mark
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 750
Rack travel in mm : 13.75
Tolerance mm : ± 0.05
Del. quantity
cm³/1000 strokes : 250.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.60
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 23.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 3.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 750
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 250.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed

Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.70
Rated speed rpm : 945
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 980
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1130

LOW IDLE

control lever
position degree : 76.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 300
rack travel mm : 5.10

Testing:

Rated speed rpm : 300
rack travel mm : 5.60
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 350
Tolerance 1/min : +- 30

TORQUE CONTROL

Dimension a mm : 3.90
Rated speed rpm : 750
rack travel mm : 13.75

Tolerance mm : +- 0.05

Rated speed rpm : 900

rack travel mm : 13.75
Tolerance mm : +- 0.10

Rated speed rpm : 450
rack travel mm : 13.75
Tolerance mm : +- 0.10

Rated speed rpm : 280
rack travel mm : 15.20
Tolerance mm : + 0.30

BREAKAWAY

Rack travel in mm : 12.70
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 23.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 12.06.96
Test oil : ISO 4113

Combination No. : 0 400 876 430

Injection pump
Pump designation : PES6A95D410RS2864
EP type number : 0 410 896 888

Governor
Governor design. : RSV400...1050A0C2263
 : -10L
Governor no. : 0 420 232 619

Cust. part No. : 87 800 862

Customer-spec. information
Customer : FNH-GEOTECH
Motor : P 396
Power kW : 142.0

TEST BENCH REQUIREMENTS

Inlet line : 1.3

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 419 992 198

Inlet press. bar : 1.5

Test nozzle holde
assembly : 5 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

J06

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 2.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
 : 4

Phasing : 0-60-120-180-240
 : -300

BASIC SETTING

Rated speed rpm : 750

Rack travel in mm : 15.20
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 154.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 3.0

Spreed
Tolerance
cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

Rated speed rpm : 450

Rack travel in mm : 5.50

Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 15.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spreed
Tolerance

cm³/1000 strokes : 5.5

Check tolerance
cm³/1000S. : 9.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50

Tolerance mm : +- 0.20

governor spring
pre-tension

click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 750

Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 154.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance

cm³/1000 strokes : 3.5

Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : +- 4.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 1093
rack travel mm : 12.40

Rated speed rpm : 1158
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1270

Rated speed rpm : 1094
rack travel mm : 12.40

Rated speed rpm : 1159
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1270

Rated speed rpm : 1095
rack travel mm : 12.40

Rated speed rpm : 1160
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1270

Rated speed rpm : 1096
rack travel mm : 12.40

Rated speed rpm : 1161
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1270

Rated speed rpm : 1097
rack travel mm : 12.40

Rated speed rpm : 1162
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85

Tolerance mm : +- 0.55
Rated speed rpm : 1270

Rated speed rpm : 1098
rack travel mm : 12.40

Rated speed rpm : 1163
Tolerance 1/min : +- 5
rack travel mm : 4.00

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1270

LOW IDLE

control lever
position degree : 73.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 5.00

Testing:

Rated speed rpm : 450
rack travel mm : 5.50
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 575
Tolerance 1/min : +- 30

TORQUE CONTROL

Rated speed rpm : 750
rack travel mm : 15.20
Tolerance mm : +- 0.05

Rated speed rpm : 500
rack travel mm : 15.25
Tolerance mm : +- 0.10

Rated speed rpm : 1050
rack travel mm : 12.90
Tolerance mm : +- 0.05

Rated speed rpm : 1050
rack travel mm : 13.40
Tolerance mm : +- 0.10

Rated speed rpm : 950
rack travel mm : 14.25
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 15.25
Tolerance mm : +- 0.10

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.20
Tolerance mm : +- 0.05

Rated speed rpm : 500

Pressure hPa : 750
rack travel mm : 13.70
Tolerance mm : +- 0.05

Pressure hPa : 500
rack travel mm : 11.50
Tolerance mm : +- 0.20

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 76.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.00
Tolerance mm : +- 0.20
Del. quantity
cm³/1000 strokes : 160.0
Tolerance
cm³/1000 strokes : +- 8.0
Check tolerance
cm³/1000S. : +- 11.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 15.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 5.5
Check tolerance
cm³/1000s. : 9.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 29.05.96
Test oil : ISO 4113

Combination No. : 9 400 030 750

Injection pump
Pump designation : PES4A95D320/3RS2880
EP type number : 9 410 037 214

Governor
Governor design. : RSV475...1100A0C865R
Governor no. : F 002 A20 201

Cust. part No. : 3930156

Customer-spec. information

Customer : CUMMINS
Motor : CUMMINS-4BTA-3.9
Power KW : 79.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 2.45
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1-3-4-2

Phasing : 0-90-180-270
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Start of delivery blocking

°NW after s.o.d. : 9.00
Tolerance : +- 0.10
Check
tolerance °NW : +- 0.29

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 13.30
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 115.0

Tolerance
 cm³/1000 strokes : +- 1.0

Check tolerance
 cm³/1000S. : +- 3.0

Spreed
 Tolerance
 cm³/1000 strokes : 4.0

Check tolerance
 cm³/1000S. : 6.5

Rated speed rpm : 475

Rack travel in mm : 6.25
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 22.0
 Tolerance
 cm³/1000 strokes : +- 2.0
 Check tolerance
 cm³/1000S. : +- 4.5
 Spreed
 Tolerance
 cm³/1000 strokes : 6.0
 Check tolerance
 cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
 Tolerance mm : +- 0.20

governor spring
 pre-tension
 click setting x : 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
 Aneroid pressure
 hPa : 900
 Del. quantity
 cm³/1000 strokes : 115.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 3.0
 Spreed

Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 6.5

CONTROL LEVER

control lever
 position degree : 98.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.30
 Rated speed rpm : 1110
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1190
 Tolerance 1/min : +- 15

rack travel mm : 0.85
 Tolerance mm : +- 0.55
 Rated speed rpm : 1260

rack travel mm : 4.00
 Rated speed rpm : 1195

LOW IDLE

control lever
 position degree : 78.0
 tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 475
 rack travel mm : 5.75

Testing:

Rated speed rpm : 475
 rack travel mm : 6.25
 Tolerance mm : +- 0.10

rack travel mm : 2.00
 Rated speed rpm : 565
 Tolerance 1/min : +- 30

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 13.30
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 14.30
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.90
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 600
rack travel mm : 13.30
Tolerance mm : +- 0.20

Pressure hPa : 400
rack travel mm : 12.10
Tolerance mm : +- 0.20

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 129.2
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 71.8
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 12.30
Rated speed rpm : 1110
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 121.4
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 15.0

LOW IDLE

Rated speed rpm : 475
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.06.96
Test oil : ISO 4113
Combination No. : 0 402 046 866
Injection pump
Pump designation : PES6P120A720RS3346
EP type number : 0 412 026 778
Governor
Governor design. : RQ300/1025PA1213
Governor no. : 0 421 801 783
Cust. part No. :

Customer-spec. information
Customer : IVECO-FIAT
Motor : 8360.46.4649

TEST BENCH REQUIREMENTS

Inlet line : 2.4
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 034
Inlet press. bar : 2.5
Test nozzle holde
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0
x inside diameter : 3.0

J13

x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

BASIC SETTING

Rated speed rpm : 1025
Rack travel in mm : 11.90
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 175.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 5.0

Check tolerance
cm³/1000s. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.50
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 20.0

Tolerance
cm³/1000 strokes : ± 3.0

Check tolerance
cm³/1000s. : ± 6.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000s. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 550

Rack travel in mm : 14.30
Tolerance mm : ± 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1025

Aneroid pressure
hPa : 900

Del. quantity
cm³/1000 strokes : 175.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000s. : ± 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000s. : 9.0

RATED SPEED

rack travel mm : 10.90
Rated speed rpm : 1078
Tolerance 1/min : ± 8

rack travel mm : 4.00
Rated speed rpm : 1150

Tolerance 1/min : ± 15

rack travel mm : 0.50

Tolerance mm : ± 0.50

Rated speed rpm : 1300

LOW IDLE

control lever

position degree : 70.0

tolerance degree : ± 4.0

Testing:

Rated speed rpm : 300

rack travel mm : 5.50

Tolerance mm : ± 0.10

rack travel mm : 2.00

Rated speed rpm : 380

Tolerance 1/min : ± 20

Rated speed rpm : 200

CRT mm min. : > 7.00

TORQUE CONTROL

Rated speed rpm : 1025

rack travel mm : 11.90

Tolerance mm : ± 0.05

Rated speed rpm : 500

rack travel mm : 11.95

Tolerance mm : ± 0.10

Rated speed rpm : 1025

rack travel mm : 12.35

Tolerance mm : ± 0.05

Rated speed rpm : 500

rack travel mm : 12.40

Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500

Pressure hPa : 900

rack travel mm : 11.90

Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 270
rack travel mm : 10.00
Tolerance mm : +- 0.20

Pressure hPa : 500
rack travel mm : 11.30
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 168.0
Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm3/1000 strokes : 102.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 10.90
Rated speed rpm : 1078
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm3/1000 strokes : 90.0
Tolerance
cm3/1000 strokes : +- 15.0

Check tolerance
cm3/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm3/1000 strokes : 20.0
Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 6.0
Speed
Tolerance
cm3/1000 strokes : 8.0
Check tolerance
cm3/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 07.06.96
Test oil : ISO 4113

Combination No. : 0 402 640 845

Injection pump
Pump designation : PE12P120A320LS7896
EP type number : 0 412 620 847

Governor
Governor design. : RQV350...1050PA1306
Governor no. : 0 421 814 179

Cust. part No. : 0270749102

Customer-spec. information
Customer : MB-NFZ
Motor : OM 444 LA
Power KW : 500.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5

Overflow quantity
min. l/h : 160
Tolerance l/h : +- 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 075
Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 5.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 20.50
Tolerance mm : +- 0.50

Firing order : 12- 1- 5- 9- 8
 : - 3- 4- 11- 10
 : - 2- 6- 7

Phasing : 0-45-60-105-120
 : -165-180-225-240
 : -285-300-345
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 15.10
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 227.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

Rated speed rpm : 350

Rack travel in mm : 5.70
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 19.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance

cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 1.48
Tolerance mm : +- 0.20

Rated speed rpm : 1107
guide sleeve
travel mm : 8.04
Tolerance mm : +- 0.15

Rated speed rpm : 900
guide sleeve
travel mm : 5.69
Tolerance mm : +- 0.25

Rated speed rpm : 580
guide sleeve
travel mm : 3.62
Tolerance mm : +- 0.25

Rated speed rpm : 1204
guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.25

Rated speed rpm : 1300

guide sleeve
travel mm : 1.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1154

Rack travel in mm : 14.10
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure

hPa : 1300

Del. quantity
cm³/1000 strokes : 227.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance

cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 14.00
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1190
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1300

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 753
Tolerance 1/min : +- 3
rack travel mm : 10.80

Rated speed rpm : 785
Tolerance 1/min : +- 5

rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 900
 rack travel mm : 10.80
 rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 rack travel mm : 10.80
 rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 rack travel mm : 10.80
 rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 rack travel mm : 10.80
 rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 rack travel mm : 10.80
 rack travel mm : 4.00
 rack travel mm : 0.50
 Tolerance mm : +- 0.50

LOW IDLE

control lever
 position degree : 67.0
 tolerance degree : +- 4.0
 Testing:
 Rated speed rpm : 350
 rack travel mm : 5.70
 Tolerance mm : +- 0.10
 Rated speed rpm : 250
 CRT mm min. : > 8.00
 Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 1050
 rack travel mm : 15.10
 Tolerance mm : +- 0.05
 Rated speed rpm : 800
 rack travel mm : 15.10
 Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

MEASUREMENT

Pressure hPa : -
 Rated speed rpm : 500
 Pressure hPa : 300
 rack travel mm : 1.20
 Tolerance mm : +- 0.05
 Pressure hPa : 600
 rack travel mm : 3.70
 Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 100
 Rated speed rpm : < 270
 Check
 speed 1/min : > 80
 Check
 speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
 hPa : 1300
 Rated speed rpm : 800
 Del. quantity
 cm³/1000 strokes : 226.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 10.0
 Check tolerance
 cm³/1000S. : 15.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 134.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 14.00
Rated speed rpm : 1095
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 250.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 05.06.96
Test oil : ISO 4113

Combination No. : 0 402 648 788

Injection pump
Pump designation : PE8P120A320LS7897
EP type number : 0 412 628 915

Governor
Governor design. : RQV350...1050PA1307
Governor no. : 0 421 814 180

Cust. part No. :

Customer-spec. information
Customer : MB-NFZ
Motor : OM442 LA
Power KW : 370.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 110
Tolerance l/h : ± 10.0

Test nozzle holde
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 2.5
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.80
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 8- 7- 2- 6- 3
 : - 5- 4- 1

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 8

BASIC SETTING

Rated speed rpm : 1050

Rack travel in mm : 15.35
Tolerance mm : ± 0.10

Del. quantity
cm³/1000 strokes : 272.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 5.10
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 1.48
Tolerance mm : +- 0.20

Rated speed rpm : 1108
guide sleeve
travel mm : 8.04
Tolerance mm : +- 0.15

Rated speed rpm : 900
guide sleeve
travel mm : 5.69
Tolerance mm : +- 0.25

Rated speed rpm : 570
guide sleeve
travel mm : 3.57
Tolerance mm : +- 0.25

Rated speed rpm : 1204
guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.25

Rated speed rpm : 1300
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1152

Rack travel in mm : 14.30
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : 1800
Del. quantity
cm³/1000 strokes : 272.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 14.30
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1197
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1240

LOW IDLE

control lever
position degree : 67.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.10
Tolerance mm : ± 0.10

Rated speed rpm : 250

CRT mm min. : > 8.17

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 15.35
Tolerance mm : ± 0.10

Rated speed rpm : 800
rack travel mm : 15.35
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

MEASUREMENT

Pressure hPa : 290
rack travel mm : 0.75
Tolerance mm : ± 0.05

Pressure hPa : 780
rack travel mm : 3.90
Tolerance mm : ± 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 270

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1800
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 274.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : 1800
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 156.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 130.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

BREAKAWAY

Rack travel in mm : 14.30
Rated speed rpm : 1095
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 270.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350

Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
Test oil : ISO 4113

Combination No. : 0 402 946 026

Injection pump
Pump designation : PES6P120A720RS8045
EP type number : 0 412 926 028

Governor
Governor design. : RQV350...1100PA1305K
Governor no. : 0 421 815 967

Cust. part No. : 1388631

Customer-spec. information
Customer : SCANIA
Motor : DSI1174M

TEST BENCH REQUIREMENTS

Inlet line : EH4B

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 082

Inlet press. bar : 2.5
Tolerance bar : +- 0.1

Tolerance l/h : +- 10.0

Test nozzle holder
assembly : 1 688 901 104

Opening pressure
bar : 251.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 3.65
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery blocking
Tolerance : +- 0.10
Check
tolerance °NW : +- 0.75

Barrel no. : 1

EASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 11.75
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 250.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 7.0

Spread
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 14.0

Rated speed rpm : 350

Rack travel in mm : 4.20
Tolerance mm : +- 0.30
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spread
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 2.00
Tolerance mm : +- 0.20

Rated speed rpm : 1165
guide sleeve
travel mm : 10.15
Tolerance mm : +- 0.15

Rated speed rpm : 755
guide sleeve
travel mm : 6.14
Tolerance mm : +- 0.25

Rated speed rpm : 460
guide sleeve
travel mm : 4.07
Tolerance mm : +- 0.25

Rated speed rpm : 1400
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1250
Rack travel in mm : 10.70
Tolerance mm : +- 2.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100
Aneroid pressure
hPa : 1500
Del. quantity
cm³/1000 strokes : 250.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 7.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 14.0

CONTROL LEVER

control lever
position degree : 64.0
tolerance degree : +- 4.0

control lever
position degree : 118.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.70
Rated speed rpm : 1145
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1225
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 74.0
tolerance degree : +- 4.0

control lever
position degree : 20.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 4.20
Tolerance mm : +- 0.30

Rated speed rpm : 250

CRT mm min. : > 8.42

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 11.75
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 10.90
Tolerance mm : +- 0.10

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 1100
Pressure hPa : 1500
rack travel mm : 11.75
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1100
rack travel mm : 8.00
Tolerance mm : +- 0.20

Rated speed rpm : 1100

Pressure hPa : 340
rack travel mm : 8.35
Tolerance mm : +- 0.25

Pressure hPa : 800
rack travel mm : 10.65

Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 263.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 7.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 163.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 10.70
Rated speed rpm : 1145
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 8.00
Tolerance mm : +- 0.50
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spread

Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
Test oil : ISO 4113
Combination No. : 0 403 244 045
Injection pump
Pump designation : PES4MW100/720RS1524
EP type number : 0 413 204 021
Governor
Governor design. : RQV300...1300MW132
 : -12
Governor no. : 0 420 083 329
Cust. part No. : 0240740902

Customer-spec. information
Customer : MB-NFZ
Motor : OM364LA
Power KW : 77.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 419 992 198
Inlet press. bar : 1.5
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 089
Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
Tolerance bar : +- 1.0
Prestroke mm : 4.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 21.00
Firing order : 1- 3- 4- 2
Phasing : 0-90-180-270
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

BASIC SETTING

Rated speed rpm : 1300
Rack travel in mm : 11.00
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 89.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000s. : +- 3.0
Speed
Tolerance
cm3/1000 strokes : 4.5
Check tolerance
cm3/1000s. : 7.0

Rated speed rpm : 300

Rack travel in mm : 4.40
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spreed
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 4.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 0.91
Tolerance mm : +- 0.25

Rated speed rpm : 1353
guide sleeve
travel mm : 7.14
Tolerance mm : +- 0.25

Rated speed rpm : 1130
guide sleeve
travel mm : 5.40
Tolerance mm : +- 0.25

Rated speed rpm : 610
guide sleeve
travel mm : 2.96
Tolerance mm : +- 0.25

Rated speed rpm : 660
guide sleeve
travel mm : 3.31
Tolerance mm : +- 0.25

Rated speed rpm : 780
guide sleeve
travel mm : 3.72
Tolerance mm : +- 0.25

Rated speed rpm : 1679
guide sleeve
travel mm : 12.00
Tolerance mm : +- 0.25

Rated speed rpm : 1780
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1350
Rack travel in mm : 10.00
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1300
Aneroid pressure
hPa : 700

Del. quantity
cm³/1000 strokes : 89.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.0

CONTROL LEVER

control lever
position degree : 111.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.00
Rated speed rpm : 1345
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1445
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 73.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 4.40
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : > 5.00

TORQUE CONTROL

Rated speed rpm : 1300
rack travel mm : 11.00
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 11.00
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700
rack travel mm : 11.00
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 230
rack travel mm : 0.90
Tolerance mm : +- 0.10

Pressure hPa : 150
rack travel mm : 0.30
Tolerance mm : +- 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 200

Check
speed 1/min : > 80

Check
speed 1/min : < 220

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 700
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 81.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 56.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 10.00
Rated speed rpm : 1345
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 12.0

Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Speed
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 4.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
 Test oil : ISO 4113
 Combination No. : 0 403 244 048
 Injection pump
 Pump designation : PES4MW100/720RS1524
 EP type number : 0 413 204 021
 Governor
 Governor design. : RQV300...1300MW132
 : -12
 Governor no. : 0 420 083 329
 Cust. part No. : 0240741002

Customer-spec. information
 Customer : MB-NFZ
 Motor : OM364LA
 Power KW : 77.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
 Test oil inlet
 temp. °C : 40
 Tolerance °C : ± 2.0
 Overflow valve : 1 419 992 198
 Inlet press. bar : 1.5
 Test nozzle holde
 assembly : 1 688 901 101
 Opening pressure
 bar : 208.5
 Tolerance bar : ± 1.5
 Test lines : 1 680 750 089
 Outside diameter : 8.0

K04

x inside diameter : 3.0
 x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 31.0
 Tolerance bar : ± 1.0
 Prestroke mm : 4.55
 Tolerance mm : ± 0.05
 Check
 tolerance mm : ± 0.10
 Rack travel in mm : 21.00
 Firing order : 1- 3- 4- 2
 Phasing : 0-90-180-270
 Tolerance : ± 0.50
 Check
 tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 1300
 Rack travel in mm : 11.00
 Tolerance mm : ± 0.05
 Del. quantity
 cm³/1000 strokes : 89.0
 Tolerance
 cm³/1000 strokes : ± 1.0
 Check tolerance
 cm³/1000S. : ± 3.0
 Spreed
 Tolerance
 cm³/1000 strokes : 4.5
 Check tolerance
 cm³/1000S. : 7.0

Rated speed rpm : 300

Rack travel in mm : 4.40
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 12.0
Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.5

Spread
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 4.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 0.91
Tolerance mm : +- 0.20

Rated speed rpm : 1353
guide sleeve
travel mm : 7.14
Tolerance mm : +- 0.15

Rated speed rpm : 1130
guide sleeve
travel mm : 5.40
Tolerance mm : +- 0.25

Rated speed rpm : 610
guide sleeve
travel mm : 2.96
Tolerance mm : +- 0.25

Rated speed rpm : 660
guide sleeve
travel mm : 3.31
Tolerance mm : +- 0.25

Rated speed rpm : 780
guide sleeve
travel mm : 3.72
Tolerance mm : +- 0.25

Rated speed rpm : 1679
guide sleeve
travel mm : 12.00
Tolerance mm : +- 0.25

Rated speed rpm : 1780
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1350

Rack travel in mm : 10.00
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1300
Aneroid pressure
hPa : 700

Del. quantity
cm³/1000 strokes : 89.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spread
Tolerance
cm³/1000 strokes : 4.5
Check tolerance
cm³/1000S. : 7.0

CONTROL LEVER

control lever
position degree : 111.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 10.00
Rated speed rpm : 1345
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1445
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 74.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 4.40
Tolerance mm : +- 0.10

Rated speed rpm : 200
CRT mm min. : > 5.00

TORQUE CONTROL

Rated speed rpm : 1300
rack travel mm : 11.00
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 11.00
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 700
rack travel mm : 11.00
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
Tolerance mm : +- 0.10

Rated speed rpm : 500
Pressure hPa : 230
rack travel mm : 0.90
Tolerance mm : +- 0.10

Pressure hPa : 150
rack travel mm : 0.30
Tolerance mm : +- 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 200

Check
speed 1/min : > 80

Check
speed 1/min : < 220

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 700
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 81.0
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 56.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 10.00
Rated speed rpm : 1345
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 5.0
Check tolerance
cm³/1000S. : +- 8.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 12.0

Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 2.0
Check tolerance
cm³/1000S. : 4.0

End of test specification sheet



BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.06.96
Test oil : ISO 4113
Combination No. : 9 400 087 487
Injection pump
Pump designation : PES6P120A720LS7176
: -10
EP type number : 0 412 726 869
Governor
Governor design. : RQV300...1050PA1142
Governor no. : 9 420 080 368

Cust. part No. :

Customer-spec. information
Customer : MBB
Motor : OM447 A
Power KW : 210.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

K08

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values -----

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 6- 2- 4- 1- 5-
: 3

Phasing : 0-60-120-180-240
: -300

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 12.75
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 177.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
 cm³/1000S. : 9.0
 Rated speed rpm : 300
 Rack travel in mm : 6.20
 Tolerance mm : +- 0.20
 Del. quantity
 cm³/1000 strokes : 13.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.40
 Tolerance mm : +- 0.20

Rated speed rpm : 1100
 guide sleeve
 travel mm : 7.65
 Tolerance mm : +- 0.25

Rated speed rpm : 500
 guide sleeve
 travel mm : 3.25
 Tolerance mm : +- 0.25

Rated speed rpm : 900
 guide sleeve
 travel mm : 5.85
 Tolerance mm : +- 0.25

Rated speed rpm : 1210
 guide sleeve
 travel mm : 9.55
 Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

Rated speed rpm : 1140
 Rack travel in mm : 16.50
 Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600
 Aneroid pressure
 hPa : 600
 Del. quantity
 cm³/1000 strokes : 177.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 59.0
 tolerance degree : +- 4.0

control lever
 position degree : 114.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.00
 Rated speed rpm : 1103
 Tolerance 1/min : +- 8

rack travel mm : 4.00
 Rated speed rpm : 1185
 Tolerance 1/min : +- 15

rack travel mm : 0.75
 Tolerance mm : +- 0.75
 Rated speed rpm : 1300

LOW IDLE

control lever
 position degree : 68.0
 tolerance degree : +- 4.0

control lever
 position degree : 13.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 6.20
Tolerance mm : +- 0.20

Rated speed rpm : 100
CRT mm min. : > 8.00

Rated speed rpm : 375

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 12.75
Tolerance mm : +- 0.05

Rated speed rpm : 1050
rack travel mm : 13.05
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 13.05
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

MEASUREMENT

Pressure hPa : 250
rack travel mm : -1.30
Tolerance mm : +- 0.10

Pressure hPa : 380
rack travel mm : -0.40
Tolerance mm : +- 0.10

Pressure hPa : 690

Pressure hPa : 770
rack travel mm : 0.30
Tolerance mm : +- 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check speed 1/min : > 80
Check speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure hPa : 1000
Rated speed rpm : 1050
Del. quantity cm³/1000 strokes : 182.0
Tolerance cm³/1000 strokes : +- 2.0
Check tolerance cm³/1000S. : +- 5.0

Aneroid pressure hPa : 1000
Rated speed rpm : 750
Del. quantity cm³/1000 strokes : 186.5
Tolerance cm³/1000 strokes : +- 2.0
Check tolerance cm³/1000S. : +- 5.0

Aneroid pressure hPa : -
Rated speed rpm : 500
Del. quantity cm³/1000 strokes : 132.0
Tolerance cm³/1000 strokes : +- 1.0
Check tolerance cm³/1000S. : +- 4.0
Spread Tolerance cm³/1000 strokes : 5.0
Check tolerance cm³/1000S. : 9.0

BREAKAWAY

Rack travel in mm : 12.00
Rated speed rpm : 1103
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity cm³/1000 strokes : 210.0
Tolerance cm³/1000 strokes : +- 10.0
Check tolerance cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.06.96
Test oil : ISO 4113

Combination No. : 0 402 076 785

Injection pump
Pump designation : PES6P120A720RS3352
EP type number : 0 412 026 780

Governor
Governor design. : RSV400...750P4A611
: -1
Governor no. : 0 421 833 514

Cust. part No. : RE66449

Customer-spec. information
Customer : DEERE
Motor : 6081AF001
Power KW : 135.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 457 413 010

Inlet press. bar : 2.0

Test nozzle holde
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 3.60
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.75

Start of delivery mark

°NW after s.o.d. : 7.00
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery differende
and maximum rack
travel : 14.00
Difference ° CS : 2.50

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 13.90
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 226.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.90
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 30.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 5.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600

Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 226.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 90.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.90
Rated speed rpm : 760
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 795
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 950

rack travel mm : 4.00
Rated speed rpm : 830

LOW IDLE

control lever
position degree : 73.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.40

Testing:

Rated speed rpm : 400
rack travel mm : 5.90
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 13.90
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100

Check
speed 1/min : > 80

BREAKAWAY

Rack travel in mm : 12.90
Rated speed rpm : 760
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.06.96
Test oil : ISO 4113
Combination No. : 0 402 076 786
Injection pump
Pump designation : PES6P120A720RS3352
EP type number : 0 412 026 780
Governor
Governor design. : RSV400...750P4A606
: -1
Governor no. : 0 421 833 515
Cust. part No. : RE66456

Customer-spec. information
Customer : DEERE
Motor : 6081AF001
Power KW : 135.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 457 413 010
Inlet press. bar : 2.0
Test nozzle holder
assembly : 1 688 901 103
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 015
Outside diameter : 6.0

K15

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75
Start of delivery mark
°NW after s.o.d. : 7.00
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1
Beginning of delivery difference
and maximum rack
travel : 14.00
Difference ° CS : 2.50

BASIC SETTING

Rated speed rpm : 600

Rack travel in mm : 13.90
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 226.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 400

Rack travel in mm : 5.90
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 30.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 5.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 4.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 600

Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 226.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 90.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.90
Rated speed rpm : 760
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 795
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 950

rack travel mm : 4.00
Rated speed rpm : 830

LOW IDLE

control lever
position degree : 73.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 400
rack travel mm : 5.40

Testing:

Rated speed rpm : 400
rack travel mm : 5.90
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 600
rack travel mm : 13.90
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Check
speed 1/min : > 80

BREAKAWAY

Rack travel in mm : 12.90
Rated speed rpm : 760
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Rated speed rpm : 400
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.06.96
Test oil : ISO 4113

Combination No. : 0 403 466 151

Injection pump
Pump designation : PES6MW100/120RS1238
EP type number : 0 413 406 237

Governor
Governor design. : RSV450...1100MW2A367
Governor no. : 0 420 085 250

Cust. part No. : 3926877

Customer-spec. information
Customer : CDC
Motor : 6 CT
Power KW : 138.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : +- 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0

Prestroke mm : 2.80
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Start of delivery blocking

°NW after s.o.d. : 8.00
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery differende

and maximum rack
travel : 15.00
Difference ° CS : 2.00

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 10.80
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 130.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 4.0

Check tolerance
cm3/1000S. : 7.5

Rated speed rpm : 450

Rack travel in mm : 5.40
Tolerance mm : +- 0.10
Del. quantity
cm3/1000 strokes : 24.5
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Spreed
Tolerance
cm3/1000 strokes : 3.5
Check tolerance
cm3/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 3.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1200
Del. quantity
cm3/1000 strokes : 130.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 4.0
Check tolerance
cm3/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 90.5
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 9.80
Rated speed rpm : 1165
Tolerance 1/min : +- 5

rack travel mm : 6.40
Rated speed rpm : 1230
Tolerance 1/min : +- 5

rack travel mm : 1.00
Tolerance mm : +- 0.70
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 84.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 4.90

Testing:

Rated speed rpm : 450
rack travel mm : 5.40
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 10.80
Tolerance mm : \pm 0.05

Rated speed rpm : 750
rack travel mm : 11.35
Tolerance mm : \pm 0.10

Rated speed rpm : 1000
rack travel mm : 11.15
Tolerance mm : \pm 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.50
Tolerance mm : \pm 0.20

Rated speed rpm : 500

Pressure hPa : 550
rack travel mm : 10.90
Tolerance mm : \pm 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 140.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 121.0
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 3.0

BREAKAWAY

Rack travel in mm : 9.80
Rated speed rpm : 1165
Tolerance 1/min : \pm 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : \pm 1.00
Del. quantity
cm³/1000 strokes : 177.0
Tolerance
cm³/1000 strokes : \pm 10.0
Check tolerance
cm³/1000S. : \pm 13.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 24.5
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.06.96
Test oil : ISO 4113
Combination No. : 0 403 466 158
Injection pump
Pump designation : PES6MW100/120RS1240
EP type number : 0 413 406 239

Governor
Governor design. : RSV425...1100MW2A376
Governor no. : 0 420 085 259

Cust. part No. : 3929837

Customer-spec. information
Customer : CDC
Motor : 6 CTA-A
Power KW : 172.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 047
Inlet press. bar : 2.0
Tolerance bar : +- 0.1
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 014
Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : +- 1.0
Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75
Start of delivery blocking
°NW after s.o.d. : 8.50
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75
Barrel no. : 1
Beginning of delivery difference
and maximum rack
travel : 15.00
Difference ° CS : 1.50

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.75
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 144.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 4.0

Check tolerance
cm3/1000S. : 7.5

Rated speed rpm : 435

Rack travel in mm : 6.20
Tolerance mm : +- 0.10
Del. quantity
cm3/1000 strokes : 22.5
Tolerance
cm3/1000 strokes : +- 2.0
Check tolerance
cm3/1000S. : +- 4.5
Spreed
Tolerance
cm3/1000 strokes : 3.5
Check tolerance
cm3/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 3.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 900

Del. quantity
cm3/1000 strokes : 144.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0
Spreed
Tolerance
cm3/1000 strokes : 4.0
Check tolerance
cm3/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 93.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.70
Rated speed rpm : 1165
Tolerance 1/min : +- 5

rack travel mm : 6.50
Rated speed rpm : 1230
Tolerance 1/min : +- 5

rack travel mm : 1.00
Tolerance mm : +- 0.70
Rated speed rpm : 1350

rack travel mm : 6.50
Rated speed rpm : 1230

LOW IDLE

control lever
position degree : 70.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 435
rack travel mm : 5.70

Testing:

Rated speed rpm : 435
rack travel mm : 6.20
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.75
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 12.05
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 600
rack travel mm : 12.20
Tolerance mm : +- 0.20

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 133.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 11.70
Rated speed rpm : 1165
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 145.5
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 435
Del. quantity
cm³/1000 strokes : 22.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.06.96
Test oil : ISO 4113

Combination No. : 0 403 466 161

Injection pump
Pump designation : PES6MW100/120RS1240
EP type number : 0 413 406 239

Governor
Governor design. : RSV500...1100MW2A379
Governor no. : 0 420 085 262

Cust. part No. : 3926882

Customer-spec. information
Customer : CDC
Motor : 6 CT
Power KW : 161.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 014

Outside diameter : 6.0

K24

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.75

Start of delivery blocking

°NW after s.o.d. : 8.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery differende
and maximum rack
travel : 15.00
Difference ° CS : 1.50

BASIC SETTING

Rated speed rpm : 1100

Rack travel in mm : 12.25
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 144.5

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 7.5

Rated speed rpm : 500

Rack travel in mm : 5.20
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 21.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 5.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1100

Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 144.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 7.5

CONTROL LEVER

control lever
position degree : 105.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.20
Rated speed rpm : 1160
Tolerance 1/min : +- 5

rack travel mm : 5.80
Rated speed rpm : 1230
Tolerance 1/min : +- 5

rack travel mm : 1.00
Tolerance mm : +- 0.70
Rated speed rpm : 1375

rack travel mm : 5.80
Rated speed rpm : 1235

LOW IDLE

control lever
position degree : 85.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 500
rack travel mm : 4.70

Testing:

Rated speed rpm : 500
rack travel mm : 5.20
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1100
rack travel mm : 12.25
Tolerance mm : +- 0.05

Rated speed rpm : 750
rack travel mm : 12.70
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 790
rack travel mm : 11.90
Tolerance mm : +- 0.20

Pressure hPa : 620
rack travel mm : 11.30
Tolerance mm : +- 0.20

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 155.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 119.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 3.0

BREAKAWAY

Rack travel in mm : 11.20
Rated speed rpm : 1160
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 145.5
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

LOW IDLE

Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 21.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 3.5
Check tolerance
cm³/1000S. : 5.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 11.05.95
Test oil : ISO 4113

Combination No. : 0 401 846 826

Injection pump
Pump designation : PE6P120A32ORS3178
EP type number : 0 411 826 752

Governor
Governor design. : RQV250...1025PA921
: -2
Governor no. : 0 421 813 785

Cust. part No. : 470930-P06 V. 06/92

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD122FS
Power KW : 287.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Vibration damper
(RoBo diaphragm) : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 046

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holder assembly : 1 688 901 019

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

K27

Test lines : 1 680 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 3.65
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 14.05

Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 259.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 5.0

Check tolerance
cm3/1000S. : 9.0

Rated speed rpm : 250

Rack travel in mm : 4.95
Tolerance mm : +- 0.15
Del. quantity
cm3/1000 strokes : 20.0
Tolerance
cm3/1000 strokes : +- 2.5
Check tolerance
cm3/1000S. : +- 5.0
Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 7.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1130

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 1200
Del. quantity
cm3/1000 strokes : 259.0
Tolerance
cm3/1000 strokes : +- 1.0
Check tolerance
cm3/1000S. : +- 4.0

Spreed
Tolerance
cm3/1000 strokes : 5.0
Check tolerance
cm3/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 120.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.05
Rated speed rpm : 1060
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1155
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 63.0
tolerance degree : +- 4.0

control lever
position degree : 10.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 4.95
Tolerance mm : +- 0.15

Rated speed rpm : 100

CRT mm min. : > 6.40

Rated speed rpm : 325

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 14.05
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.40
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 780
rack travel mm : 3.30
Tolerance mm : +- 0.20

Pressure hPa : 105
rack travel mm : 0.25
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 169.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 13.05
Rated speed rpm : 1060
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50

L01

Del. quantity
cm³/1000 strokes : 290.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.5
Check tolerance
cm³/1000S. : +- 5.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 13.06.96
Test oil : ISO 4113
Combination No. : 0 402 076 795
Injection pump
Pump designation : PES6P120A72ORS3369
EP type number : 0 412 026 789
Governor
Governor design. : RSV450...1075P1A631
Governor no. : 0 421 833 538

Cust. part No. :

Customer-spec. information
Customer : IVECO-FIAT
Motor : 8365.26.584
Power KW : 144.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 2 417 413 034
Inlet press. bar : 2.5
Test nozzle holder assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : ± 1.5
Test Lines : 1 680 750 089
Outside diameter : 8.0

L02

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 3.55
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 1.50

BASIC SETTING

Rated speed rpm : 1075
Rack travel in mm : 10.75
Tolerance mm : ± 0.05
Del. quantity cm3/1000 strokes : 136.0
Tolerance cm3/1000 strokes : ± 1.0
Check tolerance cm3/1000S. : ± 4.0
Speed Tolerance cm3/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 450

Rack travel in mm : 5.90
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 25.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spreed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 3.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1075
Aneroid pressure
hPa : 900

Del. quantity
cm³/1000 strokes : 136.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 97.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 9.60
Rated speed rpm : 1150
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1400

rack travel mm : 4.00
Rated speed rpm : 1235

LOW IDLE

control lever
position degree : 73.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 5.40

Testing:

Rated speed rpm : 450
rack travel mm : 5.90
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 600
Tolerance 1/min : +- 50

TORQUE CONTROL

Rated speed rpm : 1075
rack travel mm : 10.75
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 10.80
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 10.70
Tolerance mm : \pm 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.40
Tolerance mm : \pm 0.10

Rated speed rpm : 500

Pressure hPa : 515
rack travel mm : 10.35
Tolerance mm : \pm 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 145.0
Tolerance
cm³/1000 strokes : \pm 3.0
Check tolerance
cm³/1000s. : \pm 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 85.0
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000s. : \pm 4.0

BREAKAWAY

Rack travel in mm : 9.60
Rated speed rpm : 1150
Tolerance 1/min : \pm 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : \pm 0.75
Del. quantity
cm³/1000 strokes : 145.0

L04

Tolerance
cm³/1000 strokes : \pm 15.0
Check tolerance
cm³/1000s. : \pm 19.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : \pm 3.0
Check tolerance
cm³/1000s. : \pm 6.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.94
Test oil : ISO 4113
Combination No. : 0 402 646 865
Injection pump
Pump designation : PE6P120A720RS7020
EP type number : 0 412 626 828
Governor
Governor design. : RQV200...1000PA539
 : -8
Governor no. : 0 421 813 635
Cust. part No. : 1121370

Customer-spec. information
Customer : SCANIA
Motor : DS11 34

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Vibration damper
(RoBo diaphragm) : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder
assembly : 1 688 901 019
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015
Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
 : 4
Phasing : 0-60-120-180-240
 : -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50
Start of delivery mark
Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 12.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 209.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 225

Rack travel in mm : 4.70
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 20.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 3.0

Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1050

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700

Aneroid pressure
hPa : 900

Del. quantity
cm³/1000 strokes : 209.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed

Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 59.0
tolerance degree : +- 4.0

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 9.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 225
rack travel mm : 4.70
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 6.10

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 1000

rack travel mm : 12.95
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 12.95
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 320
rack travel mm : 11.20
Tolerance mm : +- 0.15

Pressure hPa : 520
rack travel mm : 12.35
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

L07

Rack travel in mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 300.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 225
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0
Speed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 17.06.96
Test oil : ISO 4113
Combination No. : 0 402 646 877
Injection pump
Pump designation : PE6P130A720RS7122-1
EP type number : 0 412 636 812
Governor
Governor design. : RQV225...930PA922
Governor no. : 0 421 813 763
Cust. part No. : 1556029 P02

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD162 FL,FJ,
Power KW : 331.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Test nozzle holde
assembly : 1 688 901 019
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

L08

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 3.65
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 0.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50
Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 13.50
Tolerance mm : +- 0.05
Del. quantity
cm3/1000 strokes : 302.5
Tolerance
cm3/1000 strokes : +- 1.5

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

Rated speed rpm : 250

Rack travel in mm : 5.00
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 28.0

Tolerance
cm³/1000 strokes : +- 2.5

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 250
guide sleeve
travel mm : 1.20
Tolerance mm : +- 0.20

Rated speed rpm : 975
guide sleeve
travel mm : 8.30
Tolerance mm : +- 0.10

Rated speed rpm : 350
guide sleeve
travel mm : 2.40
Tolerance mm : +- 0.30

Rated speed rpm : 700
guide sleeve
travel mm : 5.90
Tolerance mm : +- 0.30

Rated speed rpm : 1090
guide sleeve
travel mm : 9.70
Tolerance mm : +- 0.20

GUIDE SLEEVE POSITION

Rated speed rpm : 1100

Rack travel in mm : 9.00
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 1200

Del. quantity
cm³/1000 strokes : 302.5

Tolerance
cm³/1000 strokes : +- 1.5

Check tolerance
cm³/1000S. : +- 5.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

CONTROL LEVER

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 120.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.50
Rated speed rpm : 975
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1105
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1200

LOW IDLE

control lever
position degree : 64.0

tolerance degree : +- 4.0

control lever
position degree : 10.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 5.00
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 6.50

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.50
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 13.50
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 9.60
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 720
rack travel mm : 3.60
Tolerance mm : +- 0.10

Pressure hPa : 85
rack travel mm : 0.25
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 182.5
Tolerance
cm³/1000 strokes : +- 1.5
Check tolerance
cm³/1000S. : +- 5.0

BREAKAWAY

Rack travel in mm : 12.50
Rated speed rpm : 975
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 9.60
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 130.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 28.0
Tolerance
cm³/1000 strokes : +- 2.5
Check tolerance
cm³/1000S. : +- 5.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.94
Test oil : ISO 4113

Combination No. : 0 402 646 878

Injection pump
Pump designation : PE6P120A720RS7020
EP type number : 0 412 626 828

Governor
Governor design. : RQV200...1000PA539
: -11
Governor no. : 0 421 813 813

Cust. part No. : 1121371

Customer-spec. information
Customer : SCANIA
Motor : DS11 34

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Vibration damper
(RoBo diaphragm) : 3.1

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5

Test nozzle holder assembly : 1 688 901 019

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015
Outside diameter : 6.0
x inside diameter : 1.5
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark
Tolerance : ± 0.10
Check tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 12.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 209.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rack travel in mm : 4.70
Tolerance mm : ± 0.10

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1050

Rack travel in mm : 16.50
Tolerance mm : ± 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 209.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

Spreed
Tolerance
cm³/1000 s+rokes : 6.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 59.0
tolerance degree : ± 4.0

control lever
position degree : 117.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 65.0
tolerance degree : ± 4.0

control lever
position degree : 9.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 225
rack travel mm : 4.70
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 6.10

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 12.95
Tolerance mm : ± 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900

rack travel mm : 12.95
Tolerance mm : + 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 320
rack travel mm : 11.20
Tolerance mm : + 0.15

Pressure hPa : 520
rack travel mm : 12.35
Tolerance mm : + 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50

L13

Del. quantity
cm³/1000 strokes : 300.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 14.06.96
Test oil : ISO 4113

Combination No. : 0 402 648 602

Injection pump
Pump designation : PE8P110A32ORS7398
EP type number : 0 412 618 800

Governor
Governor design. : RQV300...900PA1252K
Governor no. : 0 421 815 484

Cust. part No. :

Customer-spec. information
Customer : TATRA
Motor : T3B-928.60
Power KW : 255.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Overflow quantity
min. l/h : 110
Tolerance l/h : ± 20.0

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 13.00
Tolerance mm : ± 1.00

Firing order : 1- 8- 5- 4- 7
 : - 2- 3- 6

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 14.00
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 191.0

Tolerance
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 250

Rack travel in mm : 5.40
Tolerance mm : ± 0.10
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.63
Tolerance mm : ± 0.20

Rated speed rpm : 958
guide sleeve
travel mm : 8.79
Tolerance mm : ± 0.15

Rated speed rpm : 777
guide sleeve
travel mm : 6.70
Tolerance mm : ± 0.25

Rated speed rpm : 520
guide sleeve
travel mm : 3.73
Tolerance mm : ± 0.25

Rated speed rpm : 1260
guide sleeve
travel mm : 13.50
Tolerance mm : ± 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1115
Rack travel in mm : 13.00
Tolerance mm : ± 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : 1500
Del. quantity
cm³/1000 strokes : 191.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 65.0
tolerance degree : ± 4.0

control lever
position degree : 119.0
tolerance degree : ± 4.0

RATED SPEED

rack travel mm : 13.00
Rated speed rpm : 945
Tolerance 1/min : ± 5

rack travel mm : 4.00
Rated speed rpm : 1065
Tolerance 1/min : ± 15

rack travel mm : 0.50
Tolerance mm : ± 0.50
Rated speed rpm : 1150

LOW IDLE

control lever
position degree : 70.0
tolerance degree : +- 4.0

control lever
position degree : 16.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 5.40
Tolerance mm : +- 0.10

Rated speed rpm : 150

CRT mm min. : > 6.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 14.00
Tolerance mm : +- 0.05

Rated speed rpm : 600
rack travel mm : 13.10
Tolerance mm : +- 0.10

Rated speed rpm : 300
rack travel mm : 12.60
Tolerance mm : +- 0.20

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1500
rack travel mm : 14.00
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 8.60
Tolerance mm : +- 0.20

Rated speed rpm : 900

Pressure hPa : 375
rack travel mm : 10.15

Tolerance mm : +- 0.15

Pressure hPa : 750
rack travel mm : 12.75
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 170

Check
speed 1/min : > 80
Check
speed 1/min : < 190

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 198.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 13.00
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 255.0
Tolerance
cm³/1000 strokes : +- 20.0

Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.04.96
Test oil : ISO 4113
Combination No. : 0 402 648 602A
Injection pump
Pump designation : PE8P110A320RS7398
EP type number : 0 412 618 800
Governor
Governor design. : RQV300...900PA1252K
Governor no. : 0 421 815 484

Cust. part No. :

Customer-spec. information
Customer : TATRA
Motor : T3B-928.50
Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Test nozzle holde
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 008
Outside diameter : 6.0

L18

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 5.05
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 13.00
Tolerance mm : +- 1.00

Firing order : 1- 8- 5- 4- 7
 : - 2- 3- 6

Phasing : 0-45-90-135-180
 : -225-270-315
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark
Tolerance : +- 0.50
Check
tolerance °NW : +- 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 13.30
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 175.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 250

Rack travel in mm : 5.40
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.63
Tolerance mm : +- 0.20

Rated speed rpm : 957
guide sleeve
travel mm : 8.79
Tolerance mm : +- 0.15

Rated speed rpm : 776
guide sleeve
travel mm : 6.70
Tolerance mm : +- 0.25

Rated speed rpm : 520
guide sleeve
travel mm : 3.73
Tolerance mm : +- 0.25

Rated speed rpm : 1260
guide sleeve
travel mm : 13.50

Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1120
Rack travel in mm : 12.30
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 175.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 61.0
tolerance degree : +- 4.0

control lever
position degree : 115.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.30
Rated speed rpm : 945
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1095
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1100

LOW IDLE

control lever
position degree : 72.0
tolerance degree : +- 4.0

control lever
position degree : 18.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 5.40
Tolerance mm : +- 0.10

Rated speed rpm : 150

CRT mm min. : > 6.00

Rated speed rpm : 350

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 13.30
Tolerance mm : +- 0.05

Rated speed rpm : 600
rack travel mm : 12.30
Tolerance mm : +- 0.10

Rated speed rpm : 300
rack travel mm : 11.50
Tolerance mm : +- 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 900
Pressure hPa : 1500
rack travel mm : 13.30
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 900
rack travel mm : 8.60
Tolerance mm : +- 0.20

Rated speed rpm : 900

Pressure hPa : 425
rack travel mm : 10.00
Tolerance mm : +- 0.15

Pressure hPa : 750
rack travel mm : 12.25
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 170

Check
speed 1/min : > 80
Check
speed 1/min : < 190

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 182.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 129.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 12.30
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 255.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 19.06.96
Test oil : ISO 4113
Combination No. : 0 402 744 804
Injection pump
Pump designation : PES4P120A320RS7402
EP type number : 0 412 724 804
Governor
Governor design. : RQV275...1200PA1257K
Governor no. : 0 421 815 494

Cust. part No. : CCEP 5154A 66-238

Customer-spec. information

Customer : RENAULT V.I.
Motor : MIDR 04-02-26 A4
Power KW : 100.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 2 417 413 071

Inlet press. bar : 2.5

Test nozzle holder assembly : 1 688 901 105

Opening pressure bar : 20±.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 5.10
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10

Rack travel in mm : 13.00
Tolerance mm : +- 0.50

Firing order : 1- 3- 4- 2

Phasing : 0-90-180-270
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50

Start of delivery mark

°NW after s.o.d. : -0.30
Tolerance : +- 0.50
Check tolerance °NW : +- 0.75

Barrel no. : 1

Beginning of delivery difference

betw. rack trav. mm : 21.00
and maximum rack travel : 13.00
Difference °CS : 2.40

BASIC SETTING

Rated speed rpm : 1200

Rack travel in mm : 13.20
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 250.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 325

Rack travel in mm : -8.50

Tolerance mm : +- 0.10

Del. quantity

cm³/1000 strokes : 29.0

Tolerance

cm³/1000 strokes : +- 2.0

Check tolerance

cm³/1000S. : +- 6.0

Speed

Tolerance

cm³/1000 strokes : 8.0

Check tolerance

cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 325
guide sleeve
travel mm : 1.52
Tolerance mm : +- 0.20

Rated speed rpm : 1260
guide sleeve
travel mm : 10.32
Tolerance mm : +- 0.15

Rated speed rpm : 938
guide sleeve
travel mm : 6.86
Tolerance mm : +- 0.25

Rated speed rpm : 550

guide sleeve
travel mm : 3.92
Tolerance mm : +- 0.25

Rated speed rpm : 1650
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1450

Rack travel in mm : 12.10
Tolerance mm : +- 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1200
Aneroid pressure
hPa : 1200

Del. quantity

cm³/1000 strokes : 250.0

Tolerance

cm³/1000 strokes : +- 1.0

Check tolerance

cm³/1000S. : +- 4.0

Speed

Tolerance

cm³/1000 strokes : 5.0

Check tolerance

cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 298.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1260
Tolerance 1/min : +- 5

rack travel mm : -9.20
Rated speed rpm : 1410
Tolerance 1/min : +- 15

rack travel mm : -12.70
Tolerance mm : +- 0.50
Rated speed rpm : 1500

LOW IDLE

control lever
position degree : 255.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 325
rack travel mm : -8.50
Tolerance mm : ± 0.10

Rated speed rpm : 225

CRT mm min. : < 7.00

Rated speed rpm : 390

TORQUE CONTROL

Rated speed rpm : 1200

Rated speed rpm : 850
rack travel mm : -1.00
Tolerance mm : ± 0.10

Rated speed rpm : 700
rack travel mm : -1.80
Tolerance mm : ± 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1200
Pressure hPa : 1200

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1200
rack travel mm : -2.70
Tolerance mm : ± 0.20

Rated speed rpm : 1200

Pressure hPa : 200
rack travel mm : -2.10
Tolerance mm : ± 0.20

Pressure hPa : 440
rack travel mm : -0.80
Tolerance mm : ± 0.05

START CUT-OUT

L24

Rated speed rpm : > 130
Rated speed rpm : < 265

Check
speed 1/min : > 110
Check
speed 1/min : < 275

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 850
Del. quantity
cm³/1000 strokes : 239.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 1200
Del. quantity
cm³/1000 strokes : 185.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1260
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 110.0
Tolerance
cm³/1000 strokes : ± 15.0
Check tolerance
cm³/1000S. : ± 19.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 29.0

Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000s. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 31.05.96
Test oil : ISO 4113

Combination No. : 0 402 746 844

Injection pump
Pump designation : PES6P120A320RS7162
EP type number : 0 412 726 819

Governor
Governor design. : RQ750PA836-2
Governor no. : 0 421 801 628

Cust. part No. :

Customer-spec. information
Customer : PERKINS
Motor : 2006 TAG
Power KW : 280.0

TEST BENCH REQUIREMENTS

Inlet line : 4.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 067

Outside diameter : 6.0

x inside diameter : 1.5
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.55
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 4- 2- 6- 3-
: 5

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 13.05
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 380.0

Tolera.
cm³/1000 strokes : ± 1.0

Check tolerance
cm³/1000S. : ± 4.0

Speed

Tolerance
 cm³/1000 strokes : 5.0

 Check tolerance
 cm³/1000S. : 9.0
 Rated speed rpm : 300
 Del. quantity
 cm³/1000 strokes : 41.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spreed
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 757
 guide sleeve
 travel mm : 1.84
 Tolerance mm : +- 0.25

 Rated speed rpm : 930
 guide sleeve
 travel mm : 42.98
 Tolerance mm : +- 0.25

 Rated speed rpm : 820
 guide sleeve
 travel mm : 9.41
 Tolerance mm : +- 0.25

 Rated speed rpm : 824
 guide sleeve
 travel mm : 10.00
 Tolerance mm : +- 0.25

 Rated speed rpm : 880
 guide sleeve
 travel mm : 11.50
 Tolerance mm : +- 0.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 380.0

Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spreed
 Tolerance
 cm³/1000 strokes : 5.0
 Check tolerance
 cm³/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 89.0
 tolerance degree : +- 4.0

ASSEMBLY GOVERNOR SETTING

Rated speed rpm : 750
 rack travel mm : 12.00

 Rated speed rpm : 784
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 820

 Rated speed rpm : 751
 rack travel mm : 12.00

 Rated speed rpm : 785
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 820

 Rated speed rpm : 752
 rack travel mm : 12.00

 Rated speed rpm : 786
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

 rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 820

 Rated speed rpm : 753
 rack travel mm : 12.00

 Rated speed rpm : 787
 Tolerance 1/min : +- 4
 rack travel mm : 4.00

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 820

Rated speed rpm : 754
rack travel mm : 12.00

Rated speed rpm : 788
Tolerance 1/min : +- 4
rack travel mm : 4.00

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 820

Rated speed rpm : 755
rack travel mm : 12.00

Rated speed rpm : 789
Tolerance 1/min : +- 4
rack travel mm : 4.00

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 820

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 13.05
Tolerance mm : +- 0.05

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm3/1000 strokes : 320.0
Tolerance
cm3/1000 strokes : +- 20.0
Check tolerance
cm3/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm3/1000 strokes : 41.0

L28

Tolerance
cm3/1000 strokes : +- 3.0
Check tolerance
cm3/1000S. : +- 6.0
Spreed
Tolerance
cm3/1000 strokes : 8.0
Check tolerance
cm3/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
Test oil : ISO 4113
Combination No. : 9 400 087 424
Injection pump
Pump designation : PE6P120A720RS7020
EP type number : 0 412 626 828
Governor
Governor design. : RQV200...1000PA539
: -8
Governor no. : 0 421 813 635
Cust. part No. : 1670638

Customer-spec. information
Customer : SCANIA
Motor : DS 11 34

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Vibration damper
(RoBo diaphragm) : 3.1
Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Test nozzle holder assembly : 1 688 901 019
Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015
Outside diameter : 6.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0
Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50
Start of delivery mark
Tolerance : ± 0.10
Check tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 12.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 209.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 225

Rack travel in mm : 4.70
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 225
guide sleeve
travel mm : 1.40
Tolerance mm : +- 0.20

Rated speed rpm : 1045
guide sleeve
travel mm : 8.50
Tolerance mm : +- 0.10

Rated speed rpm : 350
guide sleeve
travel mm : 2.70
Tolerance mm : +- 0.30

Rated speed rpm : 650
guide sleeve
travel mm : 4.80
Tolerance mm : +- 0.30

Rated speed rpm : 1150

guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.20

GUIDE SLEEVE POSITION

Rated speed rpm : 1050

Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 900
Del. quantity
cm³/1000 strokes : 209.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 59.0
tolerance degree : +- 4.0

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 9.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 225
rack travel mm : 4.70
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 6.10

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 12.95
Tolerance mm : +- 0.05

Rated speed rpm : 1000
rack travel mm : 12.95
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 12.95
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 320
rack travel mm : 11.25
Tolerance mm : +- 0.15

Pressure hPa : 520
rack travel mm : 12.35
Tolerance mm : +- 0.05

M03

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 900
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 300.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 225
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Spread

Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000s. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
Test oil : ISO 4113

Combination No. : 9 400 087 428

Injection pump
Pump designation : PE6P120A720RS7020
EP type number : 0 412 626 828

Governor
Governor design. : RQV200...1000PA539
: -11
Governor no. : 0 421 813 813

Cust. part No. : 1121371

Customer-spec. information
Customer : SCANIA
Motor : DS 11 34

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Vibration
damper
(RoBo diaphragm) : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.05
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 12.95
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 209.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spreed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 225

Rack travel in mm : 4.70
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000S. : 6.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 225
guide sleeve
travel mm : 1.40
Tolerance mm : +- 0.20

Rated speed rpm : 1045
guide sleeve
travel mm : 8.50
Tolerance mm : +- 0.10

Rated speed rpm : 350
guide sleeve
travel mm : 2.70
Tolerance mm : +- 0.30

Rated speed rpm : 650
guide sleeve
travel mm : 4.80
Tolerance mm : +- 0.30

Rated speed rpm : 1150
guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.20

GUIDE SLEEVE POSITION

Rated speed rpm : 1050
Rack travel in mm : 16.50
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
Aneroid pressure
hPa : 1500
Del. quantity
cm³/1000 strokes : 209.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 59.0
tolerance degree : +- 4.0

control lever
position degree : 117.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1250

LOW IDLE

control lever
position degree : 65.0
tolerance degree : +- 4.0

control lever
position degree : 9.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 225
rack travel mm : 4.70
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 6.10

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 12.95
Tolerance mm : +- 0.05

Rated speed rpm : 1000
rack travel mm : 12.95
Tolerance mm : +- 0.05

ANEROID/ALTITUDE COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 12.95
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.70
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 320
rack travel mm : 11.25
Tolerance mm : +- 0.15

Pressure hPa : 520
rack travel mm : 12.35

MO7

Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1500
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 11.90
Rated speed rpm : 1045
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : +- 0.50
Del. quantity
cm³/1000 strokes : 300.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 225
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000s. : +- 5.0
Spreed
Tolerance
cm³/1000 strokes : 3.0
Check tolerance
cm³/1000s. : 6.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 10.06.96
Test oil : ISO 4113
Combination No. : 9 400 087 434
Injection pump
Pump designation : PE6P120A32ORS3178
EP type number : 0 411 826 752
Governor
Governor design. : RQV250...1025PA921
 : -2
Governor no. : 0 421 813 785
Cust. part No. : 470930-P06

Customer-spec. information
Customer : VOLVO-TRUCK
Motor : TD 122 FS
Power KW : 287.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Vibration damper
(RoBo diaphragm) : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 046
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Test nozzle holder assembly : 1 688 901 019
Opening pressure bar : 208.5
Tolerance bar : +- 1.5

M09

Test lines : 1 680 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 3.65
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
 : 4
Phasing : 0-60-120-180-240
 : -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50
Start of delivery mark
Tolerance : +- 0.10
Check tolerance °NW : +- 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700
Rack travel in mm : 14.05
Tolerance mm : +- 0.05

Del. quantity	
cm ³ /1000 strokes :	259.0

Tolerance	
cm ³ /1000 strokes :	+ - 1.0

Check tolerance	
cm ³ /1000S.	: + - 4.0

Spread	
Tolerance	
cm ³ /1000 strokes :	5.0

Check tolerance	
cm ³ /1000S.	: 9.0

Rated speed rpm	: 250

Rack travel in mm :	4.95
Tolerance mm :	+ - 0.15
Del. quantity	
cm ³ /1000 strokes :	20.0
Tolerance	
cm ³ /1000 strokes :	+ - 2.5
Check tolerance	
cm ³ /1000S.	: + - 5.0
Spread	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S.	: 7.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm	: 250
guide sleeve	
travel mm	: 1.20
Tolerance mm	: + - 0.20

Rated speed rpm	: 1070
guide sleeve	
travel mm	: 8.10
Tolerance mm	: + - 0.10

Rated speed rpm	: 450
guide sleeve	
travel mm	: 3.90
Tolerance mm	: + - 0.30

Rated speed rpm	: 800
guide sleeve	
travel mm	: 6.50
Tolerance mm	: + - 0.20

Rated speed rpm	: 1180
guide sleeve	
travel mm	: 10.10
Tolerance mm	: + - 0.20

GUIDE SLEEVE POSITION

Rated speed rpm	: 1130
Rack travel in mm	: 16.50
Tolerance mm	: + - 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm	: 700
Aneroid pressure	
hPa	: 1200
Del. quantity	
cm ³ /1000 strokes :	259.0
Tolerance	
cm ³ /1000 strokes :	+ - 1.0
Check tolerance	
cm ³ /1000S.	: + - 4.0
Spread	
Tolerance	
cm ³ /1000 strokes :	5.0
Check tolerance	
cm ³ /1000S.	: 9.0

CONTROL LEVER

control lever	
position degree	: 65.0
tolerance degree	: + - 4.0

control lever	
position degree	: 120.0
tolerance degree	: + - 4.0

RATED SPEED

rack travel mm	: 13.00
Rated speed rpm	: 1060
Tolerance 1/min	: + - 5

rack travel mm	: 4.00
Rated speed rpm	: 1155
Tolerance 1/min	: + - 15

rack travel mm	: 0.50
Tolerance mm	: + - 0.50
Rated speed rpm	: 1250

LOW IDLE

control lever
position degree : 63.0
tolerance degree : ± 4.0

control lever
position degree : 10.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 250
rack travel mm : 4.95
Tolerance mm : ± 0.15

Rated speed rpm : 100

CRT mm min. : > 6.40

Rated speed rpm : 325

TORQUE CONTROL

Rated speed rpm : 700
rack travel mm : 14.05
Tolerance mm : ± 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1200
rack travel mm : 14.05
Tolerance mm : ± 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500

Rated speed rpm : 500

Pressure hPa : 780
rack travel mm : 3.30
Tolerance mm : ± 0.20

Pressure hPa : 105
rack travel mm : 0.25
Tolerance mm : ± 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 169.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0

BREAKAWAY

Rack travel in mm : 13.00
Rated speed rpm : 1060
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.50
Tolerance mm : ± 0.50
Del. quantity
cm³/1000 strokes : 290.0
Tolerance
cm³/1000 strokes : ± 20.0
Check tolerance
cm³/1000S. : ± 24.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : ± 2.5
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 7.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.96
Test oil : ISO 4113
Combination No. : 0 400 876 426
Injection pump
Pump designation : PES6A100D410RS2762
: -1
EP type number : 0 410 806 008
Governor
Governor design. : RSV400...1050A2C2283
Governor no. : 0 420 232 607
Cust. part No. : RE62527

Customer-spec. information
Customer : DEERE
Motor : 6076AT033
Power KW : 131.5

TEST BENCH REQUIREMENTS

Inlet line : 2.4
Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0
Overflow valve : 1 457 413 010
Inlet press. bar : 1.5
Tolerance bar : ± 0.1
Test nozzle holder
assembly : 1 688 901 101
Opening pressure
bar : 208.5
Tolerance bar : ± 1.5
Test lines : 1 680 750 008

Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0
Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10
Rack travel in mm : 10.50
Tolerance mm : ± 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Start of delivery mark
°NW after s.o.d. : 13.50
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1050
Rack travel in mm : 10.80
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 101.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0

Spreed
Tolerance
cm³/1000 strokes : 4.0

Check tolerance
cm³/1000S. : 6.5

Rated speed rpm : 450

Rack travel in mm : 5.60
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 5.00

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1050
Aneroid pressure
hPa : -
Del. quantity
cm³/1000 strokes : 101.0
Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

CONTROL LEVER

control lever
position degree : 93.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 9.80
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1150
Tolerance 1/min : +- 5

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1300

rack travel mm : 4.00
Rated speed rpm : 1150

LOW IDLE

control lever
position degree : 72.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 450
rack travel mm : 5.10

Testing:

Rated speed rpm : 450
rack travel mm : 5.60
Tolerance mm : +- 0.10

Rated speed rpm : 100

CRT mm min. : > 19.00

TORQUE CONTROL

Rated speed rpm : 1050
rack travel mm : 10.80
Tolerance mm : +- 0.05

Rated speed rpm : 700
rack travel mm : 13.00
Tolerance mm : +- 0.10

Check tolerance : 8.0
cm³/1000S.

End of test specification sheet

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 700
Del. quantity
cm³/1000 strokes : 134.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 9.80
Rated speed rpm : 1095
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 105.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 15.0

LOW IDLE

Rated speed rpm : 450
Del. quantity
cm³/1000 strokes : 20.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0
Speed
Tolerance
cm³/1000 strokes : 6.0

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 02.01.96
Test oil : ISO 4113
Combination No. : 0 402 046 859
Injection pump
Pump designation : PES6P110A320LS3330
EP type number : 0 412 016 745
Governor
Governor design. : RQV350...1150PA1129K
Governor no. : 0 421 815 385

Cust. part No. : 1823109C91

Customer-spec. information
Customer : NAVISTAR
Motor : DT-466
Power KW : 141.5

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 076

Inlet press. bar : 2.8
Tolerance bar : ± 0.1

Test nozzle holde assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test Lines : 1 680 750 015

Outside diameter : 6.0

M15

x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.00
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

BASIC SETTING

Rated speed rpm : 750

Rack travel in mm : 12.35
Tolerance mm : ± 0.05

Del. quantity cm³/1000 strokes : 130.5

Tolerance cm³/1000 strokes : ± 1.0

Check tolerance cm³/1000S. : ± 3.0

Speed Tolerance cm³/1000 strokes : 8.0

Check tolerance cm³/1000S. : 12.0

Rated speed rpm : 325

Rack travel in mm : 6.85
Tolerance mm : \pm 0.10
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : \pm 2.0
Check tolerance
cm³/1000S. : \pm 4.5
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 750
Aneroid pressure
hPa : 1200
Del. quantity
cm³/1000 strokes : 130.5
Tolerance
cm³/1000 strokes : \pm 1.0
Check tolerance
cm³/1000S. : \pm 3.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : \pm 6.0

RATED SPEED

rack travel mm : 12.10
Rated speed rpm : 1200
Tolerance 1/min : \pm 15
rack travel mm : 4.00
Rated speed rpm : 1350
Tolerance 1/min : \pm 5
rack travel mm : 0.50

M16

Tolerance mm : \pm 0.50
Rated speed rpm : 1500

LOW IDLE

control lever
position degree : 78.0
tolerance degree : \pm 6.0

Testing:

Rated speed rpm : 325
rack travel mm : 6.85
Tolerance mm : \pm 0.10

Rated speed rpm : 275

CRT mm min. : $>$ 7.30

Rated speed rpm : 435

TORQUE CONTROL

Rated speed rpm : 750
rack travel mm : 12.35
Tolerance mm : \pm 0.05

Rated speed rpm : 1150
rack travel mm : 13.10
Tolerance mm : \pm 0.10

Rated speed rpm : 500
rack travel mm : 11.50
Tolerance mm : \pm 0.20

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1150
Pressure hPa : 1200
rack travel mm : 13.10
Tolerance mm : \pm 0.10

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1150
rack travel mm : 10.90
Tolerance mm : \pm 0.20

Rated speed rpm : 1150

Pressure hPa : 350
rack travel mm : 12.10
Tolerance mm : +- 0.20

Pressure hPa : 180
rack travel mm : 11.30
Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 280

Check speed 1/min : > 80
Check speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1200
Rated speed rpm : 1150
Del. quantity
cm³/1000 strokes : 145.5
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1150
Del. quantity
cm³/1000 strokes : 94.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 12.10
Rated speed rpm : 1200
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100

M17

rack travel mm : 20.50
Tolerance mm : +- 1.00
Del. quantity
cm³/1000 strokes : 140.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 25.0

LOW IDLE

Rated speed rpm : 325
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 4.5
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 6.5

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.06.96
Test oil : ISO 4113

Combination No. : 0 402 196 705

Injection pump
Pump designation : PES6P120A720RS3347
EP type number : 0 412 026 777

Governor
Governor design. : RE30
Governor no. : 0 421 890 029

Cust. part No. : RE 63514

Customer-spec. information

Customer : DEERE
Motor : 6076 HRW35
Power KW : 181.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 077

Inlet press. bar : 1.5
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 101

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 015

Outside diameter : 6.0

M18

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Start of delivery blocking

*NW after s.o.d. : 10.50
Tolerance : ± 0.50
Check
tolerance *NW : ± 0.75

Barrel no. : 1

(B) POSITIONER TESTING
Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR POSITION

Engine speed min-1: 0

Setting point
(P, R and H pump)

Uact V : 3.100
 CRT mm : 13.00
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
 CRT mm : 6.15
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
 CRT mm : 12.50
 Tolerance mm : +/- 0.05
 Check tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
 CRT mm : 5.50
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
 Tolerance mm : +/- 0.25
 Check tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min-1: 60
 Amplitude V : 1.4
 Tolerance V : +/- 0.6
 Check tolerance V : +/- 1.20

Engine speed min-1: 600
 Difference
 Amplitude to
 Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1100
 Uact V : 2.710
 Del. quantity
 cm3/1000 strokes : 141.0
 Tolerance
 cm3/1000 strokes : +/- 1.0
 Check tolerance
 cm3/1000S. : +/- 4.0
 Spreed
 Tolerance
 cm3/1000 strokes : 5.0
 Check tolerance
 cm3/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 700
 Uact V : 2.710
 Del. quantity
 cm3/1000 strokes : 142.0
 Tolerance
 cm3/1000 strokes : +/- 3.0
 Check tolerance
 cm3/1000S. : +/- 6.0
 Spreed
 Tolerance
 cm3/1000 strokes : 8.0
 Check tolerance
 cm3/1000S. : 12.0

TEST POINT L1

Rated speed rpm : 425
 Uact V : 1.400
 Tolerance Volt : +/- 0.060
 Check tolerance
 Volt : +/- 0.060
 Del. quantity
 cm3/1000 strokes : 19.0

Tolerance
cm³/1000 strokes : +- 3.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.600
Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 13.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.06.96
Test oil : ISO 4113

Combination No. : 0 402 796 823

Injection pump
Pump designation : PES6P120A720RS7356
EP type number : 0 412 726 919

Governor
Governor design. : RE 1
Governor no. : G 890 017

Cust. part No. : RE 67884

Customer-spec. information
Customer : DEERE
Motor : 6081 HRW 05
Power KW : 198.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 077

Inlet press. bar : 2.0
Tolerance bar : ± 0.1

Test nozzle holder
assembly : 1 688 901 103

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 089

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 600

REMARKS

Pump-specific values
in Section (B)
must be observed!

(A) INJECTION PUMP SETTINGS
No basic setting.
Setting of constant delivery
under Section C.

BEGINNING OF DELIVERY

Test pressure bar : 17.0
Tolerance bar : ± 1.0

Prestroke mm : 3.60
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300

Start of delivery blocking

*NW after s.o.d. : 9.25
Tolerance : ± 0.50
Check
tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery difference

and maximum rack
travel : 15.00
Difference °CS : 2.50

(B) POSITIONER TESTING

Warm-up time: 3 minutes at
n=600 min⁻¹, Uact = 2.5 V

TESTING & SETTING RACK TRAVEL SENSOR
POSITION

Engine speed min⁻¹: 0

Setting point
(P, R and H pump)

Uact V : 3.100
CRT mm : 13.00
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(P, R and H pump)

Uact V : 1.700
CRT mm : 6.15
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Setting point
(M pump)

Uact V : 3.100
CRT mm : 12.50
Tolerance mm : +/- 0.05
Check
tolerance mm : +/- 0.10

Check value
(M pump)

Uact V : 1.700
CRT mm : 5.50
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.30

Stop position

Uact V : Value with
deenergised adjusting magnet
and control rod in
stop position.

CRT mm : 0.75
Tolerance mm : +/- 0.25
Check
tolerance mm : +/- 0.35

ENGINE-SPEED SENSOR
(All P and R pumps not
H and M pumps)

Test with control rod
in stop position

Engine speed min⁻¹: 60
Amplitude V : 1.4
Tolerance V : +/- 0.6
Check
tolerance V : +/- 1.20

Engine speed min⁻¹: 600
Difference
Amplitude to
Amplitude V : max.1.4

(C) INJECTION PUMP WITH POSITIONER

TEST POINT V1

Rated speed rpm : 1050
Uact V : 3.030
Del. quantity
cm³/1000 strokes : 213.0
Tolerance
cm³/1000 strokes : +/- 1.0
Check tolerance
cm³/1000S. : +/- 4.0
Spreed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

FUEL DELIVERY CHARACTERISTICS

Rated speed rpm : 700
Uact V : 3.120
Del. quantity
cm³/1000 strokes : 237.0
Tolerance
cm³/1000 strokes : +/- 3.0
Check tolerance
cm³/1000S. : +/- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

TEST POINT L1

Rated speed rpm : 450
Uact V : 1.740

Tolerance Volt : +- 0.060
Check tolerance
Volt : +- 0.060
Del. quantity
cm³/1000 strokes : 26.0
Tolerance
cm³/1000 strokes : +- 3.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000s. : 10.0

STARTING FUEL DELIVERY

Rated speed rpm : 100
Uact V : 4.550
Del. quantity
cm³/1000 strokes : 120.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000s. : +- 25.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.96
 Test oil : ISO 4113
 Combination No. : 0 402 046 864
 Injection pump
 Pump designation : PES6P120A320RS3337
 : -1
 EP type number : 0 412 026 772
 Governor
 Governor design. : RQV300...1250PA1149
 : -1K
 Governor no. : 0 421 815 421
 Cust. part No. : CCEP 5142A 66-219

Customer-spec. information
 Customer : RENAULT V.I.
 Motor : MIDR 06-02-26 W4
 Power KW : 155.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2
 Test oil inlet
 temp. °C : 40
 Tolerance °C : +- 2.0
 Overflow valve : 2 417 413 084
 Inlet press. bar : 2.5
 Test nozzle holde
 assembly : 1 688 901 105
 Opening pressure
 bar : 208.5
 Tolerance bar : +- 1.5
 Test lines : 1 680 750 089

Outside diameter : 8.0
 x inside diameter : 3.0
 x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
 Tolerance bar : +- 1.0
 Prestroke mm : 4.15
 Tolerance mm : +- 0.05
 Check
 tolerance mm : +- 0.10
 Rack travel in mm : 13.00
 Tolerance mm : +- 1.50
 Firing order : 1- 5- 3- 6- 2-
 : 4
 Phasing : 0-60-120-180-240
 : -300
 Tolerance : +- 0.30
 Check
 tolerance °NW : +- 0.50
 Start of delivery mark
 °NW after s.o.d. : -0.35
 Tolerance : +- 0.50
 Check
 tolerance °NW : +- 0.75
 Barrel no. : 1
 Beginning of delivery differende
 betw. rack trav.
 mm : 21.00
 and maximum rack
 travel : 13.00
 Difference °CS : 2.00

BASIC SETTING

Rated speed rpm : 1250

 Rack travel in mm : 13.10
 Tolerance mm : +- 0.05

 Del. quantity
 cm3/1000 strokes : 199.0

 Tolerance
 cm3/1000 strokes : +- 1.0

 Check tolerance
 cm3/1000S. : +- 4.0

 Spreed
 Tolerance
 cm3/1000 strokes : 5.0

 Check tolerance
 cm3/1000S. : 9.0

 Rated speed rpm : 300

 Rack travel in mm : -8.30
 Tolerance mm : +- 0.10
 Del. quantity
 cm3/1000 strokes : 25.0
 Tolerance
 cm3/1000 strokes : +- 2.0
 Check tolerance
 cm3/1000S. : +- 5.0
 Spreed
 Tolerance
 cm3/1000 strokes : 8.0
 Check tolerance
 cm3/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
 guide sleeve
 travel mm : 1.31
 Tolerance mm : +- 0.20

 Rated speed rpm : 1328
 guide sleeve
 travel mm : 9.98
 Tolerance mm : +- 0.15

 Rated speed rpm : 876
 guide sleeve
 travel mm : 6.02

Tolerance mm : +- 0.25

 Rated speed rpm : 510
 guide sleeve
 travel mm : 3.59
 Tolerance mm : +- 0.25

 Rated speed rpm : 1600
 guide sleeve
 travel mm : 13.50
 Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1415

 Rack travel in mm : 12.15
 Tolerance mm : +- 2.03

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
 Aneroid pressure
 hPa : 1000
 Del. quantity
 cm3/1000 strokes : 199.0
 Tolerance
 cm3/1000 strokes : +- 1.0
 Check tolerance
 cm3/1000S. : +- 4.0
 Spreed
 Tolerance
 cm3/1000 strokes : 5.0
 Check tolerance
 cm3/1000S. : 9.0

CONTROL LEVER

control lever
 position degree : 296.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
 Rated speed rpm : 1312
 Tolerance 1/min : +- 15

 rack travel mm : -9.10
 Rated speed rpm : 1440
 Tolerance 1/min : +- 5

 rack travel mm : -12.60
 Tolerance mm : +- 0.50
 Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 245.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -8.30
Tolerance mm : +- 0.10

Rated speed rpm : 200

CRT mm min. : < -7.50

Rated speed rpm : 400

TORQUE CONTROL

Rated speed rpm : 1250

Rated speed rpm : 850
rack travel mm : -1.85
Tolerance mm : +- 0.15

Rated speed rpm : 350
rack travel mm : -1.60
Tolerance mm : +- 0.30

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 1000
Pressure hPa : 1000
rack travel mm : -1.40

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 1000
rack travel mm : -3.40
Tolerance mm : +- 0.20

Rated speed rpm : 1000

Pressure hPa : 240
rack travel mm : -2.55
Tolerance mm : +- 0.10

Pressure hPa : 320
rack travel mm : -1.80

M26

Tolerance mm : +- 0.05

START CUT-OUT

Rated speed rpm : > 175
Rated speed rpm : < 240

Check
speed 1/min : > 155
Check
speed 1/min : < 260

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 850
Del. quantity
cm³/1000 strokes : 141.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 1000
Del. quantity
cm³/1000 strokes : 127.5
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1312
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 102.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 25.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000s. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.96
Test oil : ISO 4113

Combination No. : 0 402 046 872

Injection pump
Pump designation : PES6P120A320RS3337
EP type number : 0 412 026 770

Governor
Governor design. : RQV300...1250PA1246K
Governor no. : 0 421 815 480

Cust. part No. : CCEP 5155A 66-217

Customer-spec. information

Customer : RENAULT V.I.
Motor : MIDR 06-02-26 U4
Power KW : 111.0

TEST BENCH REQUIREMENTS

Inlet line : 3.2

Test oil inlet temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 2 417 413 084

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Overflow quantity min. l/h : 135
Tolerance l/h : ± 10.0

Test nozzle holder assembly : 1 688 901 101

Opening pressure bar : 208.5
Tolerance bar : ± 1.5

Test lines : 1 680 750 008

Outside diameter : 6.0

x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.10
Tolerance mm : ± 0.05
Check tolerance mm : ± 0.10

Rack travel in mm : 11.00
Tolerance mm : ± 0.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check tolerance °NW : ± 0.50

Start of delivery mark

°NW after s.o.d. : 0.08
Tolerance : ± 0.50
Check tolerance °NW : ± 0.75

Barrel no. : 1

Beginning of delivery differende

betw. rack trav. mm : 21.00
and maximum rack travel : 11.00
Difference °CS : 2.00

BASIC SETTING

Rated speed rpm : 1250

Rack travel in mm : 10.60
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 138.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : -5.60
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 30.0

Tolerance
cm³/1000 strokes : +- 2.0

Check tolerance
cm³/1000S. : +- 5.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.31
Tolerance mm : +- 0.20

Rated speed rpm : 1333
guide sleeve
travel mm : 10.40
Tolerance mm : +- 0.15

Rated speed rpm : 900
guide sleeve
travel mm : 6.50
Tolerance mm : +- 0.25

Rated speed rpm : 530
guide sleeve
travel mm : 3.77
Tolerance mm : +- 0.25

Rated speed rpm : 1580
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1400

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1250
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 138.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 296.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : -1.00
Rated speed rpm : 1315
Tolerance 1/min : +- 15

rack travel mm : -6.50
Rated speed rpm : 1410
Tolerance 1/min : +- 5

rack travel mm : -10.00

Tolerance mm : +- 0.50
Rated speed rpm : 1550

LOW IDLE

control lever
position degree : 242.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : -5.60
Tolerance mm : +- 0.10

Rated speed rpm : 200
CRT mm min. : < -4.60

Rated speed rpm : 380

TORQUE CONTROL

Rated speed rpm : 1250
Rated speed rpm : 750
rack travel mm : -1.60
Tolerance mm : +- 0.10
Rated speed rpm : 350
rack travel mm : -2.40
Tolerance mm : +- 0.15

START CUT-OUT

Rated speed rpm : > 130
Rated speed rpm : < 225
Check
speed 1/min : > 110
Check
speed 1/min : < 245

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 100.0
Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

BREAKAWAY

Rack travel in mm : -1.00
Rated speed rpm : 1315
Tolerance 1/min : +- 15

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 108.0
Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 30.0
Tolerance
cm³/1000 strokes : +- 2.0
Check tolerance
cm³/1000S. : +- 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 21.06.96
Test oil : ISO 4113

Combination No. : 0 402 076 806

Injection pump
Pump designation : PES6P120A720LS3298
EP type number : 0 412 026 754

Governor
Governor design. : RSV350...900POA553
: -1
Governor no. : 0 421 833 563

Cust. part No. :

Customer-spec. information
Customer : FINCANTIERI
Motor : L 1306 T2
Power KW : 220.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 047

Inlet press. bar : 1.5
Tolerance bar : +- 0.1

Overflow quantity
min. l/h : 110
Tolerance l/h : +- 20.0

Test nozzle holder
assembly : 1 688 901 105

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

NO3

Test lines : 1 680 750 089
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 3.55
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 10.50
Tolerance mm : +- 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

BASIC SETTING

Rated speed rpm : 900

Rack travel in mm : 15.25
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 276.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 7.50
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 18.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance

cm³/1000 strokes : 10.0

Check tolerance
cm³/1000S. : 14.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 800

Rack travel in mm : 0.50
Tolerance mm : +- 0.20

governor spring
pre-tension
click setting x : 4.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 900

Aneroid pressure
hPa : 1300

Del. quantity
cm³/1000 strokes : 276.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance

cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 89.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 14.20
Rated speed rpm : 945

Tolerance 1/min : +- 5

rack travel mm : 4.00

Rated speed rpm : 1140

Tolerance 1/min : +- 15

rack travel mm : 0.85

Tolerance mm : +- 0.55

Rated speed rpm : 1350

rack travel mm : 4.00

Rated speed rpm : 1205

LOW IDLE

control lever
position degree : 75.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 350
rack travel mm : 7.00

Testing:

Rated speed rpm : 350
rack travel mm : 7.50
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 715
Tolerance 1/min : +- 50

TORQUE CONTROL

Rated speed rpm : 900
rack travel mm : 15.25
Tolerance mm : +- 0.05

Rated speed rpm : 600

rack travel mm : 15.30
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 600
Pressure hPa : 1300
rack travel mm : 15.25
Tolerance mm : +- 0.10

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 600
rack travel mm : 11.10
Tolerance mm : +- 0.20

Rated speed rpm : 600

Pressure hPa : 900
rack travel mm : 14.65
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1300
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 282.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

Aneroid pressure
hPa : -
Rated speed rpm : 600
Del. quantity
cm³/1000 strokes : 156.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

N05

Rack travel in mm : 14.20
Rated speed rpm : 945
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 20.25
Tolerance mm : +- 0.75
Del. quantity
cm³/1000 strokes : 410.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 18.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 10.0
Check tolerance
cm³/1000S. : 14.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 20.12.95
Test oil : ISO 4113

Combination No. : 0 402 646 606

Injection pump
Pump designation : PE6P120A72DRS7188
: -100
EP type number : 0 412 626 925

Governor
Governor design. : RQV200...950PA725
: -10
Governor no. : 0 421 814 002

Cust. part No. : 1338073

Customer-spec. information
Customer : SCANIA
Motor : DSC 11 32

TEST BENCH REQUIREMENTS

Inlet line : 4.2

Vibration
damper
(RoBo diaphragm) : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 2.5
Tolerance bar : ± 0.1

Test nozzle holde
assembly : 1 688 901 104

Opening pressure
bar : 251.5
Tolerance bar : ± 1.5

N06

Test Lines : 1 680 750 008
Outside diameter : 6.0
x inside diameter : 2.0
x length mm : 600

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 4.45
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 10.50
Tolerance mm : ± 1.50

Firing order : 1- 5- 3- 6- 2-
: 4

Phasing : 0-60-120-180-240
: -300
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Barrel no. : 1

BASIC SETTING

Rated speed rpm : 700

Rack travel in mm : 12.55
Tolerance mm : ± 0.05

Del. quantity
cm³/1000 strokes : 214.0

Tolerance
 cm³/1000 strokes : +- 1.0

Check tolerance
 cm³/1000S. : +- 4.0

Spread
 Tolerance
 cm³/1000 strokes : 8.0

Check tolerance
 cm³/1000S. : 12.0

Rated speed rpm : 250

Rack travel in mm : 4.70
 Tolerance mm : +- 0.10
 Del. quantity
 cm³/1000 strokes : 16.0
 Tolerance
 cm³/1000 strokes : +- 3.0
 Check tolerance
 cm³/1000S. : +- 6.0
 Spread
 Tolerance
 cm³/1000 strokes : 4.0
 Check tolerance
 cm³/1000S. : 8.0

(B) SETTING OF INJECTION PUMP
 WITH GOVERNOR

GUIDE SLEEVE POSITION

Rated speed rpm : 1140

Rack travel in mm : 9.50
 Tolerance mm : +- 2.50

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 700
 Aneroid pressure
 hPa : -
 Del. quantity
 cm³/1000 strokes : 214.0
 Tolerance
 cm³/1000 strokes : +- 1.0
 Check tolerance
 cm³/1000S. : +- 4.0
 Spread
 Tolerance
 cm³/1000 strokes : 8.0
 Check tolerance
 cm³/1000S. : 12.0

CONTROL LEVER

control lever
 position degree : 59.0
 tolerance degree : +- 4.0

control lever
 position degree : 114.0
 tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.50
 Rated speed rpm : 995
 Tolerance 1/min : +- 5

rack travel mm : 4.00
 Rated speed rpm : 1105
 Tolerance 1/min : +- 15

rack travel mm : 0.50
 Tolerance mm : +- 0.50
 Rated speed rpm : 1250

LOW IDLE

control lever
 position degree : 64.0
 tolerance degree : +- 4.0

control lever
 position degree : 10.0
 tolerance degree : +- 4.0

Testing:

Rated speed rpm : 250
 rack travel mm : 4.70
 Tolerance mm : +- 0.10

Rated speed rpm : 150

CRT mm min. : > 6.00

Rated speed rpm : 275

TORQUE CONTROL

Rated speed rpm : 700
 rack travel mm : 12.55
 Tolerance mm : +- 0.05

Rated speed rpm : 950

rack travel mm : 12.55
Tolerance mm : +- 0.05

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 1500
rack travel mm : 12.55
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.40
Tolerance mm : +- 0.20

Rated speed rpm : 500

Pressure hPa : 270
rack travel mm : 11.00
Tolerance mm : +- 0.15

Pressure hPa : 440
rack travel mm : 12.05
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 950
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 4.0
Check tolerance
cm³/1000S. : +- 6.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 153.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

NO8

Rack travel in mm : 11.50
Rated speed rpm : 995
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : 10.40
Tolerance mm : +- 0.20
Del. quantity
cm³/1000 strokes : 165.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 250
Del. quantity
cm³/1000 strokes : 16.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 4.0
Check tolerance
cm³/1000S. : 8.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 20.06.96
Test oil : ISO 4113
Combination No. : 0 402 646 669
Injection pump
Pump designation : PE6P130A720RS7197
EP type number : 0 412 636 815
Governor
Governor design. : RQV425...975PA1292
Governor no. : 0 421 814 184

Cust. part No. :

Customer-spec. information
Customer : IVECO-FRANCE
Motor : 8215.42.985
Power KW : 260.0

TEST BENCH REQUIREMENTS

Inlet line : 4.2
Test oil inlet temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 2 417 413 076
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Test nozzle holde assembly : 1 688 901 105
Opening pressure bar : 208.5
Tolerance bar : +- 1.5
Test lines : 1 680 750 075
Outside diameter : 8.0

N09

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 5.05
Tolerance mm : +- 0.05
Check tolerance mm : +- 0.10
Rack travel in mm : 10.50
Tolerance mm : +- 1.50
Firing order : 1- 5- 3- 6- 2-
: 4
Phasing : 0-60-120-180-240
: -300
Tolerance : +- 0.30
Check tolerance °NW : +- 0.50
Start of delivery mark
Check tolerance °NW : +- 0.40
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1000
Rack travel in mm : 13.45
Tolerance mm : +- 0.05
Del. quantity cm3/1000 strokes : 257.0
Tolerance cm3/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 8.0

Rated speed rpm : 425

Rack travel in mm : 5.20
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 7.0
Spread
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 425
guide sleeve
travel mm : 2.40
Tolerance mm : +- 0.20

Rated speed rpm : 1034
guide sleeve
travel mm : 7.23
Tolerance mm : +- 0.15

Rated speed rpm : 860
guide sleeve
travel mm : 5.34
Tolerance mm : +- 0.25

Rated speed rpm : 580
guide sleeve
travel mm : 3.68
Tolerance mm : +- 0.25

Rated speed rpm : 1139
guide sleeve
travel mm : 10.00
Tolerance mm : +- 0.25

Rated speed rpm : 1220
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1125

Rack travel in mm : 10.00
Tolerance mm : +- 2.70

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 975
Aneroid pressure
hPa : 900
Del. quantity
cm³/1000 strokes : 257.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 8.0

CONTROL LEVER

control lever
position degree : 119.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 12.40
Rated speed rpm : 1020
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1080
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50
Rated speed rpm : 1350

LOW IDLE

control lever
position degree : 94.0

tolerance degree : +- 4.0

Testing:

Rated speed rpm : 425
rack travel mm : 5.20
Tolerance mm : +- 0.10

Rated speed rpm : 325

CRT mm min. : > 6.70

Rated speed rpm : 470

TORQUE CONTROL

Rated speed rpm : 1000
rack travel mm : 13.45
Tolerance mm : +- 0.05

Rated speed rpm : 500
rack travel mm : 13.50
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : 900
rack travel mm : 13.45
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 500
rack travel mm : 10.90
Tolerance mm : +- 0.10

Rated speed rpm : 500

Pressure hPa : 470
rack travel mm : 11.50
Tolerance mm : +- 0.10

Pressure hPa : 550
rack travel mm : 12.75
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 181.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

BREAKAWAY

Rack travel in mm : 12.40
Rated speed rpm : 1020
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 270.0
Tolerance
cm³/1000 strokes : +- 20.0
Check tolerance
cm³/1000S. : +- 24.0

LOW IDLE

Rated speed rpm : 425
Del. quantity
cm³/1000 strokes : 22.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 7.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.96
 Test oil : ISO 4113
 Combination No. : 0 402 646 748
 Injection pump
 Pump designation : PE6P120A320LS7834
 : -10
 EP type number : 0 412 626 853
 Governor
 Governor design. : RQ300/1050PA1030-27
 Governor no. : 0 421 801 777
 Cust. part No. : 0260744202

Customer-spec. information
 Customer : MB-NFZ
 Motor : OM441 LA
 Power KW : 230.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
 Test oil inlet
 temp. °C : 40
 Tolerance °C : +- 2.0
 Overflow valve : 1 417 413 047
 Inlet press. bar : 1.5
 Tolerance bar : +- 0.1
 Overflow quantity
 min. l/h : 140
 Tolerance l/h : +- 10.0
 Test nozzle holder
 assembly : 1 688 901 105
 Opening pressure
 bar : 208.5
 Tolerance bar : +- 1.5

Test lines : 1 680 750 075
 Outside diameter : 8.0
 x inside diameter : 3.0
 x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
 Set equal delivery quant.
 per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
 Tolerance bar : +- 1.0
 Prestroke mm : 5.25
 Tolerance mm : +- 0.05
 Check
 tolerance mm : +- 0.10
 Rack travel in mm : 20.50
 Tolerance mm : +- 0.50
 Firing order : 6- 3- 5- 2- 4-
 : 1-
 Phasing : 0-60-120-180-240
 : -300-360
 Tolerance : +- 0.30
 Check
 tolerance °NW : +- 0.50
 Start of delivery mark
 Barrel no. : 6

BASIC SETTING

Rated speed rpm : 550
 Rack travel in mm : 14.80
 Tolerance mm : +- 0.05
 Del. quantity
 cm³/1000 strokes : 230.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 5.20
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 13.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Spread
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 300
guide sleeve
travel mm : 1.78
Tolerance mm : +- 0.10

Rated speed rpm : 1104
guide sleeve
travel mm : 6.51
Tolerance mm : +- 0.10

Rated speed rpm : 1050
guide sleeve
travel mm : 6.00
Tolerance mm : +- 0.10

Rated speed rpm : 421
guide sleeve
travel mm : 4.00
Tolerance mm : +- 0.10

Rated speed rpm : 550
guide sleeve
travel mm : 6.00

Tolerance mm : +- 0.10

Rated speed rpm : 1270
guide sleeve
travel mm : 11.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 600

Rack travel in mm : 20.00
Tolerance mm : +- 0.80

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 550
Aneroid pressure
hPa : 1000

Del. quantity
cm³/1000 strokes : 230.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 99.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 13.80
Rated speed rpm : 1098
Tolerance 1/min : +- 8

rack travel mm : 4.00
Rated speed rpm : 1200
Tolerance 1/min : +- 15

rack travel mm : 0.75
Tolerance mm : +- 0.75
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 72.0
tolerance degree : +- 4.0

Testing:

Rated speed rpm : 300
rack travel mm : 5.20
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 405
Tolerance 1/min : +- 20

Rated speed rpm : 200

CRT mm min. : > 6.80

TORQUE CONTROL

Rated speed rpm : 550
rack travel mm : 14.80
Tolerance mm : +- 0.05

Rated speed rpm : 1050
rack travel mm : 14.80
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 400
Pressure hPa : 1000
rack travel mm : 14.80
Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 400
rack travel mm : 11.75
Tolerance mm : +- 0.20

Rated speed rpm : 400

Pressure hPa : 400
rack travel mm : 13.25
Tolerance mm : +- 0.20

Pressure hPa : 500
rack travel mm : 14.10
Tolerance mm : +- 0.20

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 220

Check
speed 1/min : > 80
Check
speed 1/min : < 240

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1000
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 228.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000s. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 147.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000s. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000s. : 12.0

BREAKAWAY

Rack travel in mm : 13.80
Rated speed rpm : 1098
Tolerance 1/min : +- 8

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 210.0

Tolerance
cm³/1000 strokes : +- 15.0
Check tolerance
cm³/1000S. : +- 19.0

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 13.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 18.04.96
Test oil : ISO 4113
Combination No. : 0 402 646 782
Injection pump
Pump designation : PE6P120A320LS7864-1
EP type number : 0 412 626 906
Governor
Governor design. : RQV350...1050PA1052
 : -3
Governor no. : 0 421 814 069
Cust. part No. : 0250740602

Customer-spec. information
Customer : MB-NFZ
Motor : OM401 LA
Power KW : 213.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1
Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0
Overflow valve : 1 417 413 025
Inlet press. bar : 1.5
Tolerance bar : +- 0.1
Overflow quantity
min. l/h : 135
Tolerance l/h : +- 10.0
Test nozzle holder
assembly : 1 688 901 105
Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 075
Outside diameter : 8.0
x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0
Prestroke mm : 5.25
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10
Rack travel in mm : 20.50
Tolerance mm : +- 0.50
Firing order : 6- 3- 5- 2- 4-
 : 1
Phasing : 0-60-120-180-240
 : -300
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50
Start of delivery mark
Tolerance : +- 0.10
Check
tolerance °NW : +- 0.75
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 550

Rack travel in mm : 12.45
Tolerance mm : +- 0.05

Del. quantity
cm³/1000 strokes : 201.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 5.20
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 19.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 1.22
Tolerance mm : +- 0.20

Rated speed rpm : 1108
guide sleeve
travel mm : 9.63
Tolerance mm : +- 0.15

Rated speed rpm : 403
guide sleeve
travel mm : 1.97
Tolerance mm : +- 0.25

Rated speed rpm : 453

guide sleeve
travel mm : 2.52
Tolerance mm : +- 0.25

Rated speed rpm : 770
guide sleeve
travel mm : 4.92
Tolerance mm : +- 0.25

Rated speed rpm : 1320
guide sleeve
travel mm : 13.50
Tolerance mm : +- 0.50

GUIDE SLEEVE POSITION

Rated speed rpm : 1190

Rack travel in mm : 11.40
Tolerance mm : +- 1.30

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 550
Aneroid pressure
hPa : -

Del. quantity
cm³/1000 strokes : 201.0
Tolerance

cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 105.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.40
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1160
Tolerance 1/min : +- 15

rack travel mm : 0.50
Tolerance mm : +- 0.50

Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 69.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.20
Tolerance mm : ± 0.10

Rated speed rpm : 250
CRT mm min. : > 8.70

Rated speed rpm : 425

TORQUE CONTROL

Rated speed rpm : 550
rack travel mm : 12.45
Tolerance mm : ± 0.05

Rated speed rpm : 1050
rack travel mm : 12.45
Tolerance mm : ± 0.05

Rated speed rpm : 1050
rack travel mm : 10.40
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 500
Pressure hPa : -

MEASUREMENT

Pressure hPa : 200
Rated speed rpm : 500
rack travel mm : 0.45
Tolerance mm : ± 0.05

Rated speed rpm : 500

Pressure hPa : 450
rack travel mm : 1.80
Tolerance mm : ± 0.10

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 270

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : -
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 205.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 152.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 127.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Speed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 11.40

Rated speed rpm : 1095
Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 180.0
Tolerance
cm³/1000 strokes : +- 10.0
Check tolerance
cm³/1000S. : +- 14.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Speed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 25.06.96
Test oil : ISO 4113

Combination No. : 0 402 648 904

Injection pump
Pump designation : PE8P120A320LS7801-1
EP type number : 0 412 628 818

Governor
Governor design. : RQV350...1050PA866
: -9
Governor no. : 0 421 813 906

Cust. part No. :

Customer-spec. information

Customer : MB-NFZ
Motor : OM442 LA
Power KW : 260.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : ± 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5

Overflow quantity
min. l/h : 110
Tolerance l/h : ± 10.0

Test nozzle holder
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : ± 1.5

N20

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 1000

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : ± 1.0

Prestroke mm : 5.25
Tolerance mm : ± 0.05
Check
tolerance mm : ± 0.10

Rack travel in mm : 20.50
Tolerance mm : ± 0.50

Firing order : 8- 7- 2- 6- 3
: - 5- 4- 1

Phasing : 0-45-90-135-180
: -225-270-315
Tolerance : ± 0.30
Check
tolerance °NW : ± 0.50

Start of delivery mark

Tolerance : ± 0.10
Check
tolerance °NW : ± 0.75

Barrel no. : 8

BASIC SETTING

Rated speed rpm : 500

Rack travel in mm : 13.90

Rack travel in mm : 13.90

Tolerance mm : +- 0.10
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 202.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Spread
Tolerance
cm³/1000 strokes : 5.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 350

Rack travel in mm : 5.30
Tolerance mm : +- 0.10
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spread
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

GUIDE SLEEVE TRAVEL

Rated speed rpm : 350
guide sleeve
travel mm : 1.55
Tolerance mm : +- 0.25

Rated speed rpm : 1107
guide sleeve
travel mm : 8.05
Tolerance mm : +- 0.25

Rated speed rpm : 570
guide sleeve
travel mm : 3.55
Tolerance mm : +- 0.25

Rated speed rpm : 900

guide sleeve
travel mm : 5.65
Tolerance mm : +- 0.25

Rated speed rpm : 1204
guide sleeve
travel mm : 10.05
Tolerance mm : +- 0.25

GUIDE SLEEVE POSITION

Rated speed rpm : 1130
Rack travel in mm : 17.25
Tolerance mm : +- 0.75

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 500
Aneroid pressure
hPa : 700
Del. quantity
cm³/1000 strokes : 202.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spread
Tolerance
cm³/1000 strokes : 5.0
Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 121.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.70
Rated speed rpm : 1095
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1175
Tolerance 1/min : +- 15

rack travel mm : 0.75
Tolerance mm : +- 0.75
Rated speed rpm : 1300

LOW IDLE

control lever
position degree : 70.0
tolerance degree : ± 4.0

Testing:

Rated speed rpm : 350
rack travel mm : 5.30
Tolerance mm : ± 0.10

Rated speed rpm : 100

CRT mm min. : > 6.90

Rated speed rpm : 450

TORQUE CONTROL

Rated speed rpm : 500
rack travel mm : 13.90
Tolerance mm : ± 0.10

Rated speed rpm : 1050
rack travel mm : 12.70
Tolerance mm : ± 0.10

Rated speed rpm : 750
rack travel mm : 14.10
Tolerance mm : ± 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

MEASUREMENT

Pressure hPa : 400
rack travel mm : -1.50
Tolerance mm : ± 0.05

Pressure hPa : 475
rack travel mm : -0.60
Tolerance mm : ± 0.10

Pressure hPa : 925
rack travel mm : 0.15
Tolerance mm : ± 0.05

START CUT-OUT

Rated speed rpm : > 100
Rated speed rpm : < 270

Check
speed 1/min : > 80
Check
speed 1/min : < 290

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1100
Rated speed rpm : 1050
Del. quantity
cm³/1000 strokes : 182.5
Tolerance
cm³/1000 strokes : ± 1.5
Check tolerance
cm³/1000S. : ± 4.5
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : 1100
Rated speed rpm : 750
Del. quantity
cm³/1000 strokes : 215.0
Tolerance
cm³/1000 strokes : ± 2.0
Check tolerance
cm³/1000S. : ± 5.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 144.0
Tolerance
cm³/1000 strokes : ± 1.0
Check tolerance
cm³/1000S. : ± 4.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 11.70
Rated speed rpm : 1095
Tolerance 1/min : ± 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
Del. quantity
cm³/1000 strokes : 230.0
Tolerance
cm³/1000 strokes : ± 10.0
Check tolerance
cm³/1000S. : ± 14.0

LOW IDLE

Rated speed rpm : 350
Del. quantity
cm³/1000 strokes : 19.0
Tolerance
cm³/1000 strokes : ± 3.0
Check tolerance
cm³/1000S. : ± 6.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 10.0

End of test specification sheet

BOSCH INJ. PUMP TEST SPECIFICATIONS

Note remarks

Refer to Service Info for test and adjustment instructions.
See microcard(s) W400/...

Edition : 24.06.96
Test oil : ISO 4113

Combination No. : 0 402 678 830

Injection pump
Pump designation : PE8P120A520/5RS7386
EP type number : 0 412 628 910

Governor
Governor design. : RSUV325...1150POA365
Governor no. : 0 421 829 113

Cust. part No. : 12277649KY0120-17

Customer-spec. information
Customer : MWM
Motor : TBD 616 V16
Power KW : 864.0

TEST BENCH REQUIREMENTS

Inlet line : 3.1

Test oil inlet
temp. °C : 40
Tolerance °C : +- 2.0

Overflow valve : 1 417 413 025

Inlet press. bar : 1.5
Tolerance bar : +- 0.1

Test nozzle holde
assembly : 1 688 901 019

Opening pressure
bar : 208.5
Tolerance bar : +- 1.5

Test lines : 1 680 750 075

Outside diameter : 8.0

x inside diameter : 3.0
x length mm : 100

REMARKS

(A) INJECTION PUMP SETTING VALUES
Set equal delivery quant.
per values _____

BEGINNING OF DELIVERY

Test pressure bar : 26.0
Tolerance bar : +- 1.0

Prestroke mm : 4.65
Tolerance mm : +- 0.05
Check
tolerance mm : +- 0.10

Rack travel in mm : 13.00
Tolerance mm : +- 0.10

Firing order : 1- 2- 7- 8- 3- 4-
: 5- 6

Phasing : 0-30-45-75-90-120
: -315-345
Tolerance : +- 0.30
Check
tolerance °NW : +- 0.50

Start of delivery mark
Barrel no. : 1

BASIC SETTING

Rated speed rpm : 1150

Rack travel in mm : 12.60
Tolerance mm : +- 0.05

Del. quantity
cm3/1000 strokes : 262.0

Tolerance
cm3/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

Rated speed rpm : 300

Rack travel in mm : 6.40
Tolerance mm : +- 0.10

Del. quantity
cm³/1000 strokes : 38.0

Tolerance
cm³/1000 strokes : +- 3.0

Check tolerance
cm³/1000S. : +- 6.0

Speed
Tolerance
cm³/1000 strokes : 8.0

Check tolerance
cm³/1000S. : 12.0

(B) SETTING OF INJECTION PUMP
WITH GOVERNOR

FULL LOAD DELIVERY AT FULL LOAD STOP

Rated speed rpm : 1150

Aneroid pressure
hPa : 1800

Del. quantity
cm³/1000 strokes : 262.0

Tolerance
cm³/1000 strokes : +- 1.0

Check tolerance
cm³/1000S. : +- 4.0

Speed
Tolerance
cm³/1000 strokes : 6.0

Check tolerance
cm³/1000S. : 9.0

CONTROL LEVER

control lever
position degree : 116.0
tolerance degree : +- 4.0

RATED SPEED

rack travel mm : 11.60
Rated speed rpm : 1193
Tolerance 1/min : +- 5

rack travel mm : 4.00
Rated speed rpm : 1270
Tolerance 1/min : +- 15

rack travel mm : 0.85
Tolerance mm : +- 0.55
Rated speed rpm : 1380

rack travel mm : 4.00
Rated speed rpm : 1285

LOW IDLE

control lever
position degree : 80.0
tolerance degree : +- 4.0

Setting point w/out bumper spring

Rated speed rpm : 300
rack travel mm : 5.90

Testing:

Rated speed rpm : 300
rack travel mm : 6.40
Tolerance mm : +- 0.10

rack travel mm : 2.00
Rated speed rpm : 460
Tolerance 1/min : +- 30

TORQUE CONTROL

Rated speed rpm : 1150
rack travel mm : 12.60
Tolerance mm : +- 0.05

Rated speed rpm : 800
rack travel mm : 12.60
Tolerance mm : +- 0.10

ANEROID/ALTITUDE
COMPENSATOR TEST

SETTING

Rated speed rpm : 600
Pressure hPa : 1800
rack travel mm : 12.60

Tolerance mm : +- 0.05

MEASUREMENT

Pressure hPa : -
Rated speed rpm : 600
rack travel mm : 8.50
Tolerance mm : +- 0.20

Rated speed rpm : 600

Pressure hPa : 780
rack travel mm : 9.60
Tolerance mm : +- 0.20

Pressure hPa : 1600
rack travel mm : 12.45
Tolerance mm : +- 0.05

FUEL DELIVERY CHARACTERISTICS

Aneroid pressure
hPa : 1800
Rated speed rpm : 800
Del. quantity
cm³/1000 strokes : 261.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

Aneroid pressure
hPa : -
Rated speed rpm : 500
Del. quantity
cm³/1000 strokes : 131.0
Tolerance
cm³/1000 strokes : +- 1.0
Check tolerance
cm³/1000S. : +- 4.0
Spreed
Tolerance
cm³/1000 strokes : 6.0
Check tolerance
cm³/1000S. : 12.0

BREAKAWAY

Rack travel in mm : 11.60
Rated speed rpm : 1193

N26

Tolerance 1/min : +- 5

STARTING FUEL DELIVERY

Rated speed rpm : 100
rack travel mm : > 19.50

LOW IDLE

Rated speed rpm : 300
Del. quantity
cm³/1000 strokes : 38.0
Tolerance
cm³/1000 strokes : +- 3.0
Check tolerance
cm³/1000S. : +- 6.0
Spreed
Tolerance
cm³/1000 strokes : 8.0
Check tolerance
cm³/1000S. : 12.0

End of test specification sheet